View NSN Online: https://aerobasegroup.com/nsn/8030-00-292-1102

ARMITE LABORATORIES -- LED-PLATE NO. 250/MIL-A-907 -- 8030-00-292-1102

Product ID:LED-PLATE NO. 250/MIL-A-907 MSDS Date:01/15/1993 FSC:8030 NIIN:00-292-1102 **MSDS Number: BSRXR** === Responsible Party === **Company Name: ARMITE LABORATORIES** Address:1845 RANDOLPH ST **City:LOS ANGELES** State:CA ZIP:90001 Country:US Info Phone Num:213-587-7744 Emergency Phone Num:213-587-7 744 Preparer's Name:M L WILCOX CAGE:84180 === Contractor Identification === Company Name: ARMITE LABORATORIES Address:1845 RANDOLPH ST Box:City:LOS ANGELES State:CA ZIP:90001-1435 Country:US Phone:213-587-7744 CAGE:84180 Ingred Name: METALLIC LEAD POWDER (SARA III) CAS:7439-92-1 RTECS #: OF7525000 Fraction by Wt: 70% Other REC Limits:NONE SPECIFIED

OSHA PEL:0.50 MG/M3 ACGIH TLV:0.15 MG/M3 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingre

d Name:VEHICLE: PARAFIN BASE/PETROLEUM OIL SAE Other REC Limits:NONE SPECIFIED
Ingred Name:OTHERS: PETROLEUM GREASE Other REC Limits:NONE SPECIFIED
======================================
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:LEAD: CHRONIC OVEREXPOSURE TO HIGH LEVELS OF AIRBORNE OR INGESTED LEAD MAY RESULT IN ANEMIA, INSOMNIA, WEAKNESS, CONSTIPATION, NAUSEA, AND ABDOMINAL PAIN. PROLONGED OVEREXPOSURE MAY
RESULT IN KIDNEY A ND GASTROINTESTINAL DISORDERS. NOT LIKELY WITH THIS MATERIAL.
======================================
First Aid:EYES: AS GREASE PRODUCT, WASH WELL. SKIN: REMOVE BY WIPING, WASH WELL WITH SOAP AND WATER. INHALED: N/A. SWALLOWED: DO NOT INDUCE VOMITING. CALL PHYSICIAN.
======================================
Flash Point Method:COC Flash Point:404F,207C Extinguishing Media:FOAM, CO2, DRY CHEMICAL
Fire Fight ing Procedures:NONE AS A GREASE PRODUCT Unusual Fire/Explosion Hazard:IN LARGE QUANTITY STORAGE, WITH MAJOR FIRE - FUMES MAY BE PRESENT
======================================
Spill Release Procedures:WIPE AS GREASE. TAKE UP WITH CLAY, PUMICE, ETC.
======================================
Handling and Storage Precautions:NORMAL - PREFER UNDER 125 F.
======================================
Work Hygien

ic Practices:DO NOT EAT, DRINK OR SMOKE WHEN WORKING WITH THIS PRODUCT. WASH HANDS THOROUGHLY BEFORE EATING, SMOKING OR DRINKING.

Supplemental Safety and Health

HCC:T6 Boiling Pt:B.P. Text:300F,149C Solubility in Water:INSOLUBLE Appearance and Odor:DARK GRAY, NO ODOR

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:STRONG OXID IZERS CAN CAUSE LEAD TO REACT AND LIBERATE HYDROGEN GAS. Hazardous Decomposition Products:AT TEMPERATURES ABOVE THE MELTING POINT, LEAD FUMES MAY BE EVOLVED.

Waste Disposal Methods:ANY LARGE QUANTITY - RETURN FOR RE-PROCESSING TO DISTRIBUTOR OR SMELTER, OTHERWISE CONSULT LOCAL DISPSOAL PEOPLE. ALL DISPOSAL MUST COMPLY WITH STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.