View NSN Online: https://aerobasegroup.com/nsn/8010-01-276-3638

PRATT & LAMBERT, INC; INDUSTRIAL COATINGS DIV -- COATING, ALIPH. POLYUR. TAN 686A, 33446 ID 705131 -- 8010-01-276-3638

========== Product Identification ==========

Product ID:COATING, ALIPH. POLYUR. TAN 686A, 33446 ID 705131
MSDS Date:11/01/1993
FSC:8010
NIIN:01-276-3638
MSDS Number: BSSLY
=== Responsible Party ===
Company Name:PRATT & LAMBERT, INC; INDUSTRIAL COATINGS DIV
Box:2153
City:WICHITA
State:KS
ZI
P:67201
Country:US
Info Phone Num:316-733-1361
Emergency Phone Num:716-873-6000/DOT: 800-255-3924
Preparer's Name:W A ELLISON
CAGE:FO127
=== Contractor Identification ===
Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240
Box:22
CAGE:FO127
Company Name:PRATT AND LAMBERT INC
Address:Box:6027
City:CLEVELAND
State:OH
ZIP:44101-1027
Country:US
Phone:216-566-2902
CAGE:61196

========== Composition/Information on Ingredients ==========

Ingred Name:METHYL ISOBUTYL KETONE (SOLVENT) (SARA III)
(VAPOR
PRESSURE 16 MM HG @ 20C) (LFL 1.0; UFL 8.0)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 15%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM;STEL 75 PPM
ACGIH TLV:50 PPM;STEL 75 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:SOLVENT NAPTHA, HEAVY AROMATIC (SOLVENT)
CAS:64742-94-5
RTECS #:SE7546500
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED

Ingred Name:N-BUTYL ACETATE (SOLVENT) (VAPOR PRESSURE 10 MM HG @ 20C)
(LFL 1.7; UFL 7.6)
CAS:123-86-4

00
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:150 PPM;STEL 200 PPM
ACGIH TLV:150 PPM;STEL 200 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE (SARA III) (VAPOR PRESSURE 5 MM HG @ 20C) (LFL 1.0; UFL 7.0)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: