View NSN Online: https://aerobasegroup.tw/nsn/3439-01-026-1084

ALPHA METALS -- RELIACOR 11 ROSIN CORE SOLDER -- 3439-01-026-1084

Product ID:RELIACOR 11 ROSIN CORE SOLDER MSDS Date:07/19/1990 FSC:3439 NIIN:01-026-1084 MSDS Number: BSYKV === Responsible Party === Company Name: ALPHA METALS Address:600 ROUTE 440 City: JERSEY CITY State:NJ ZIP:07304 Country:US Info Phone Num:201-434-6778 Emergency Phone Num:201-434-6778/800-424-93 00(CHEMTREC) CAGE:96613 === Contractor Identification === Company Name: FRYS METALS INC (FORMER ALPHA METALS) Address:600 ROUTE 440 Box:City:JERSEY CITY State:NJ ZIP:07304 Country:US Phone:201-434-6778 CAGE:96613

Ingred Name:LEAD (SARA III) CAS:7439-92-1 RTECS #:OF7525000 Fraction by Wt: SEE # 7% Other REC Limits:NONE RECOMMENDED OSHA PEL:SEE 1910.1025 ACGIH TLV:0.15 MG/M3,DUST;9394 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred N

ame:TIN CAS:7440-31-5 RTECS #:XP7320000 Fraction by Wt: SEE # 7% Other REC Limits:NONE RECOMMENDED OSHA PEL:2 MG/M3 ACGIH TLV:2 MG/M3; 9394

Ingred Name:SILVER (SARA III) CAS:7440-22-4 RTECS #:VW3500000 Fraction by Wt: SEE # 7% Other REC Limits:NONE RECOMMENDED OSHA PEL:0.01 MG/M3 ACGIH TLV:0.1 MG/M3; 9394 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:BISMUTH CAS:7440-69-9 RTECS #:EB2600000 Fraction by Wt: SEE # 7% Other REC Limits:NONE RECOMMENDED

Ingred Name:ANTIMONY (SARA III) CAS:7440-36 -0 RTECS #:CC4025000 Fraction by Wt: SEE # 7% Other REC Limits:NONE RECOMMENDED OSHA PEL:0.5 MG/M3 ACGIH TLV:0.5 MG (SB)/M3; 9394 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:INDIUM CAS:7440-74-6 RTECS #:NL1050000 Fraction by Wt: SEE # 7% Other REC Limits:NONE RECOMMENDED OSHA PEL:0.1 MG/M3 ACGIH TLV:0.1 MG/M3; 9394

Ingred Name:THE MANUFACTURER STATES THAT PRODUCT CONTAINS ONE/MORE OF THESE METALS IN VARING PERCENTAGE. SEE LABEL FOR COMPOSITION. RTECS #:99999992Z Other REC Limits: NONE RECOMMENDED OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Ingred Name:ROSIN ACID CAS:8050-09-7 Fraction by Wt: 1 - 4% Other REC Limits:NONE RECOMMENDED OSHA PEL:0.1MG/M3,FORMALDEHYD ACGIH TLV:AS LOW AS POSSIBLE.

LD50 LC50 Mixture:LD50 (ORAL, RAT) FOR ROSIN: >5,000 MG/KG Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO Health Hazards Acute and Chronic:ACUTE- MAY **CAUSE EYE IRRITATION &** BURNS, SKIN RASH, RESPIRATORY TRACT IRRITATION. INGESTION UNLIKELY. CHRONIC- HIGH LEVELS OF AIRBORNE/INGESTED LEAD MAY CAUSE ANEMIA, INSOMNIA, WEAKNESS, CONSTIPATION & KIDNEY, NERVOUS SYSTEM DAMGE. MAY CAUSE INJURY TO A DEVELOPING FETUS. TARGET ORGANS:CNS, EYE, SKIN, RESPIRATORY TRACT. Explanation of Carcinogenicity:CONTAINS LEAD Effects of Overexposure: EYE AND RESPIRATORY TRACT IRRITATION, SKIN BURNS & RASHES, EYE BURNS, WEAKNESS, CONSTIPATION, N AUSEA, DIZZINESS, HEADACHE, ABDOMINAL PAIN Medical Cond Aggravated by Exposure: DISEASES OF THE BLOOD AND BLOOD FORMING ORGANS, KIDNEYS, NERVOUS SYSTEM AND POSSIBLY REPRODUCTIVE SYSTEMS MAY BE AGGRAVATED BY OVEREXPOSURE TO LEAD. First Aid:EYE:IMMEDIATELY FLUSH WITH COOL WATER & OBTAIN MEDICAL AID. SKIN: FOR BURNS, FLUSH WITH COOL WATER FOR RASH REMOVE FROM EXPOSURE & CONSULT A PHYSICIAN. INHALED:REMOVE TO FR ESH AIR. PROVIDE

CPR/OXYGEN & OBTAIN MEDICAL AID. ORAL:CALL A PHYSICIAN/POISON CONTROL CENTER IMMEDIATELY.

Flash Point:NONE

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL FOR SURROUNDING FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:WHE

N HEATED TO HIGH TEMPERATURES, LEA	D
EMITS HIGHLY TOXIC FUMES.	

======================================
Spill Release Procedures:COLLECT AND USE. IF IN MOLTEN STATE, ALLOW TO COOL AND SOLIDIFY. THEN SCRAPE UP. Neutralizing Agent:NOT RELEVANT
======================================
Handling and Storage Precautions:KEEP AWAY FROM INCOMPATIBLE MATERIALS. FOOD AND DRINK SHOULD NOT BE CONSUMED IN AREAS WHERE METAL EXPOSURES ARE POSSIBLE.
Other Precautions:READ WARNING LABELS. KEEP OUT OF REACH OF CHILDREN. FOR INDUSTRIAL USE ONLY. DO NOT BREATHE FUMES. DO NOT TAKE INTERNALLY. ALWAYS WASH HANDS AFTER HANDLING CORE SOLDER AND BEFORE EATING, DRINKING OR S MOKING.
======================================
Respiratory Protection:REQUIRED IF TLV'S ARE NOT BEING MAINTAINED. USE NIOSH APPROVED RESPIRATOR FOR LEAD DUST/FUME (HIGH EFFICIENCY FILTERS) IF TLVS ARE EXCEEDED.
Ventilat ion:USE GENERAL & LOCAL EXHAUST AT FLAME TO KEEP FUMES AND GASES BELOW TLV'S IN THE WORKER'S BREATHING ZONE & GENERAL AREA. Protective Gloves:HEAT RESISTANT DURING SOLDERING Eye Protection:FACE SHIELD/GOGGLES DURING SOLDERING Other Protective Equipment:INSTALL EYE WASH STATION.
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. Supplemental Safety and Health
FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE PNI A UNDER THE SAME NSN.
======= Physical/Chemical Properties ====================================
HCC:T6 NRC/State Lic Num:NOT RELEVANT

Evaporation Rate & amp; Reference:NOT RELEVANT

Solubility in Water:INSOLUBLE

Appearance and Odor:SILVER-GRAY METAL WIRE, VARIOUS SHAPES AND SIZES -NO ODOR

Stability Indicator/Materials to Avoid:YES OXIDIZING AGENTS, STRONG ACIDS Stability Condition to Avoid:NONE Hazardous Decomposition Products:MAY FORM LEAD OXIDE FUME, CARBON

MONOXIDE, CARBON DIOXIDE, ABIETIC ACID, ALIPHATIC ALDEHYDE AND DITERPENE ACIDS.

Waste Disposal Methods:NEVER DISPOSE OF IN TRASH. HOLD FOR RECYCLING. THE ALLOY PORTION IS RECLAIMABLE. DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of D

efense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.