

EASTMAN KODAK CO. -- 139 7215 KODAK INDUSTREX DEVELOPER REPLRNISHER, PART C --
6750-01-353-4889

===== Product Identification =====

Product ID:139 7215 KODAK INDUSTREX DEVELOPER REPLRNISHER, PART C

MSDS Date:04/08/1998

FSC:6750

NIIN:01-353-4889

Kit Part:Y

MSDS Number: BVFZQ

=== Responsible Party ===

Company Name:EASTMAN KODAK CO.

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composition/Information on I

Ingredients =====

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 65-70%
Other REC Limits:NONE RECOMMENDED

Ingred Name:GLUTARALDEHYDE-BIS-SODIUM BISULFITE,
CAS:7420-89-5
Fraction by Wt: 20-25%
Other REC Limits:NONE RECOMMENDED

Ingred Name:GLUTARALDEHYDE
CAS:111-30-8
RTECS #:MA2450000
Fraction by Wt: 10-15%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C 0.2 PPM
ACGIH TLV:C 0.2 PPM; 9495

Ingred Name:ACETIC ACID (CERCLA)
CAS:64-19-7
RTECS #:AF1225000
Fraction by Wt: 212F
,>100C
Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN
Decomp Temp:Decomp Text:NOT GIVEN
Vapor Pres:18 MMHG
Vapor Density:0.6
Spec Gravity:1.155
pH:3.0
Evaporation Rate & Reference:NOT GIVEN
Solubility in Water:COMPLETE
Appearance and Odor:LIQUID, CLEAR-BROWN, ALDEHYDE ODOR.
Percent Volatiles by Volume:75-80

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURE

R.

Hazardous Decomposition Products:SULFUR DIOXIDE. CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF SULFUR.

Conditions to Avoid Polymerization:HAZARDOUS POLYMERIZATION MAY OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO FEDERAL, STATE, OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE, FOLLOW LABEL WARNINGS EV EN AFTER CONTAINER IS EMPTIED.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.