

SOUTH COAST TERMINALS INC -- 1126 ULTRALUBE ENGINE OIL SAE 30 MIL-L-2104 MC3709 --
9150-00-189-6729

===== Product Identification =====

Product ID:1126 ULTRALUBE ENGINE OIL SAE 30 MIL-L-2104 MC3709

MSDS Date:11/14/1994

FSC:9150

NIIN:00-189-6729

MSDS Number: BWBZQ

=== Responsible Party ===

Company Name:SOUTH COAST TERMINALS INC

Address:7401 WALLISVILLE RD

Box:15535

City:HOUSTON

State:TX

ZIP:77020-3

555

Country:US

Info Phone Num:713-672-2401

Emergency Phone Num:713-672-2401

CAGE:1L506

=== Contractor Identification ===

Company Name:SOUTH COAST TERMINALS, INC

Address:7401 WALLISVILLE ROAD

Box:15535

City:HOUSTON

State:TX

ZIP:77020

Country:US

Phone:713-672-2401/800-424-9300(CHEMTREC)

CAGE:1L506

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM (COAL OIL)

CAS:8002-05-9

RTECS #:SE7175000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:400 PPM

ACGIH TLV:400 PP

M

Ingred Name:ZINC SALT OF DIALKYLDITHIOPHOSPHORIC ACID

RTECS #:TD5110000

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ORAL-ACCIDENTAL INGESTION OF THIS MATERIAL MAY CAUSE IRRIATION OF DIGESTIVE TRACT. EYE-THIS MATERIAL MAY CAUSE EYE IRRITATION. SKIN-THIS MATERIAL MAY CAUSE SKIN IRRI

TATION. INHALATION-EXPOSURE TO HEAT ED MIST OR VAPORS MAY CAUSE IRRITATION TO THE NOSE AND THROAT.

Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA.

Effects of Overexposure:EYE-DIRECT CONTACT MAY CAUSE BURNING, TEARING, AND REDNESS. SKIN-PROLONGED OR REPEATED CONTACT MAY CAUSE BURNING, REDNESS AND DERMATITIS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:ORAL: DO NOT INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY. EYES: FLUSH WITH CLEAN WATER. IF IRRITATION OR REDNESS PERSISTS, SEEK MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. REMOVE CONTAMINATED C LOTHING. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION. INHALATION: MOVE AWAY FROM SOURCE OF EXPOSURE. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Po

int:392F,200C (MIN)

Extinguishing Media:EXTINGUISH WITH DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY, FOAM, DAND OR EARTH. WATER & FOAM MAY CAUSE FROTHING.

Fire Fighting Procedures:RESPIRATORY PROTECTION AND EYE PROTECTION REQUIRED FOR FIRE FIGHTING PERSONNEL.

Unusual Fire/Explosion Hazard:NONE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:TREAT AS AN OIL SPILL. CONTAIN AND REMOVE BY MECHANICAL MEANS.

=====
===== Handling and

Storage =====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.
Other Precautions:NONE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY NEEDED.
Ventilation:IF CURRENT VENTILATION PRACTICES ARE NOT ADEQUATE,
MECHANICAL VENTILATION IS RECOMMENDED.
Protective Gloves:CHEMICAL RESISTANT GLOVES, IF NEEDED.
Eye Protection:SAFETY GOGGLES OR SPLASH GOGGLES.
Other Protective Equipment:NONE
Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER HANDLING.
Supplemental Safety and Health
ADDITIONAL: MEDICAL OPINION IS DIVIDED FOR LARGE INGESTION. EMESIS OR
LAVAGE HAS BEEN RECOMMENDED FOR THOSE PETROLEUM PRODUCTS WHICH HAVE
A HIGH ORLA TOXICITY.

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:>500F,>260C
Vapor Pres:< 0.01
Vapor Density:> 1
Spec Gravity:0.87-0.88
pH:7
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:NEGLIGIBLE
Appearance and Odor:DARK AMBER LIQUID, MILD ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID STRONG OXIDIZERS
Stability Condition to Avoid:CONDITIONS OF HIGH HEAT MAY CAUSE THERMAL
DECOMPOSTION
Hazardous Decomposition Products:MAY YIELD MAJOR AMOUNTS OF OXIDES OF
CARBON & MINOR AMOUNTS OF OXIDES OF SULFUR, NITROGEN, PHOSPHORUS,
AND ZINC.

===== Disposal Considerations =====

Wast

e Disposal Methods:DISPOSAL MUST BE MADE IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE OR LOCAL REGULATIONS. ENCLOSED-CONTROLLED INCINERATION IS RECOMMENDED UNLESS DIRECTED OTHERWISE BY APPLICABLE ORDINANCES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.