

MITA COPYSTAR AMERICA,INC. -- BLACK TONER FOR DC-PART NO (SEE SUPPLEMENTAL FOR PART NO.) -- 6850-01-383-4136

===== Product Identification =====

Product ID:BLACK TONER FOR DC-PART NO (SEE SUPPLEMENTAL FOR PART NO.)

MSDS Date:04/24/1995

FSC:6850

NIIN:01-383-4136

MSDS Number: BXFZT

=== Responsible Party ===

Company Name:MITA COPYSTAR AMERICA,INC.

Address:225 SAND ROAD

Box:40008

City:FAIRFIELD (FORMAL
LY IN HASBROUCK HEIGHTS

State:NJ

ZIP:07004-0008

Country:US

Info Phone Num:201-808-8444

Emergency Phone Num:201-808-8444

CAGE:0AH08

=== Contractor Identification ===

Company Name:MITA COPYSTAR AMERICA INC

Address:2930-B S FAIRVIEW ST

Box:813

City:SANTA ANA

State:CA

ZIP:92704

Country:US

Phone:714-556-0318

CAGE:0AH08

Company Name:MITA INDUSTRIAL CO.LTD;MITA COPYSTAR AMERICA,INC.

Address:777 TERRACE AVENUE

Box:813

City:HASBROUCK HEIGHTS

State:NJ

ZIP:07604-3110

Country:US

Phone:201-288-6900

CAGE:6567

8
Company Name:MITA INDUSTRIAL COMPANY
Box:UNKNOWN
CAGE:S9463
Company Name:MONROE SYSTEMS FOR BUSINESS
Box:UNKNOWN
CAGE:0MXR4
Company Name:MONROE SYSTEMS FOR BUSINESS INC
Address:3416 WEST BROAD STREET
Box:City:RICHMOND
State:VA
ZIP:23230
Country:US
Phone:804-353-5500
CAGE:69964

===== Composition/Information on Ingredients =====

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Fraction by Wt: 8%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9
394

Ingred Name:CHROMATE(1-),BIS[1-((5-CHLORO-2-HYDROXY-PHENYL-AZO)-2-NAPHTALENOLATO(2-))],HYDROGEN
CAS:31714-55-3
Fraction by Wt: 1%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:0.5 MG/M3

Ingred Name:ALPHA-ALUMINA (ALUMINUM OXIDE) (SARA 313)
CAS:1344-28-1
RTECS #:BD1200000
Fraction by Wt: 1%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9495

Ingred Name:2-PRPENOIC ACID,2-METHYL-,BUTYL ESTER, POLYMER WITH
ETHENYLBENZENE,
CAS:25213

-39-2

Fraction by Wt: 87%

Other REC Limits:NONE RECOMMENDED

Ingred Name:SILANE, DICHLORODIMETHYL-, REACTION PRODUCTS WITH SILICA

CAS:68611-44-9

Fraction by Wt: 1%

Other REC Limits:NONE RECOMMENDED

Ingred Name:POLYPROPYLENE

CAS:9003-07-0

RTECS #:TR5000000

Fraction by Wt: 2%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Health

Acute and Chronic:TARGET-ORGANS:NONE MUTAGENICITY IS
NEGATIVE.

Explanation of Carcinogenicity:MFR GAVE THE ABOVE LISTINGS ON THE MSDS
BUT NO OTHER COMMENTS ABOUT CARCINOGENICITY WERE RECORDED.

Effects of Overexposure:MINIMAL RESPIRATORY TRACT IRRITATION MAY OCCUR
AS WITH EXPOSURE TO LARGE AMOUNTS OF ANY NON-TOXIC DUST.

Medical Conditions Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:SKIN:WASH

WITH SOAP & WATER. EYE:FLUSH THOROUGHLY WITH WATER & SEEK

MEDICAL TREATMENT. INGESTION:DILUTE STOMACH CONTENTS WITH SEVERAL
GLASSES OF WATER & SEEK MEDICAL TREATMENT. INHALATION: PROMPTLY
REMOVE FROM EXPOSURE TO FRESH AIR.

===== Fire Fighting Measures =====

Flash Point:NONFLAMMABLE

Lower Limits:NOT GIVEN

Upper Limits:NOT GIVEN

Extinguishing Media:IF PRODUCT BECOMES INVOLVED IN A FIRE, USE CARBON
DIOXIDE EXTINGUISHER.

Fire Fighting Procedures:WATER,

FOAM OR DRY CHEMICAL.

Unusual Fire/Explosion Hazard:NONE UNDER NORMAL STORAGE & USE
CONDITIONS.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP WITH A VACUUM CLEANER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:CLOSE CAP TIGHTLY AND STORE IN A COOL,
DRY AND DARK PLACE.

Other Precautions:AVOID COMBUSTION.

===== Expo
sure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED UNDER NORMAL USE.

Ventilation:NONE REQUIRED UNDER NORMAL USE.

Protective Gloves:NONE REQUIRED UNDER NORMAL USE.

Eye Protection:NONE REQUIRED UNDER NORMAL USE.

Other Protective Equipment:GLOVES AND DUST FILTER RESPIRATOR
RECOMMENDED WHEN HANDLING BULK AMOUNTS.

Work Hygienic Practices:AVOID INHALATION, INGESTION, SKIN, OR EYE
CONTACT.

Supplemental Safety and Health

FOR DC-111, 111C, 113, 114, 142RE, 211,

213RE, 313Z, 313ZD, 1001, 1205,

1255, 1415, 1435, 1455, 1605, 1656, 1685, 1824RE, 1824ZII, 1855,

2055, 2254, 2555, 2585, 3255, 3285, 4055, 4085. PER TIR, FOR P/ N

RL-912/911/911Z

===== Physical/Chemical Properties =====

HCC:N1

NRC/State Lic Num:NONE

Boiling Pt:B.P. Text:NOT GIVEN

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Vapor Pres:NOT GIVEN

Vapor Density:NOT GIVEN

Spec Gravity:1.1

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:INSOLUBLE

App

earance and Odor:FINE BLACK POWDER, PRACTICALLY ODORLESS.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:NO

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:NONE IN NORMAL HANDLING & USE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE I/A/W FEDERAL, STATE & LOCAL
REGULATIONS.

Disclaim

er (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.