

TECHNOLUBE PRODUCTS DIV (LUBRICATING SPECIALTY CO) -- MIL-H-46170 B(2) TYPE II HYD FLUID,A 1760 -- 9150-00-111-6254

===== Product Identification =====

Product ID:MIL-H-46170 B(2) TYPE II HYD FLUID,A 1760

MSDS Date:01/31/1994

FSC:9150

NIIN:00-111-6254

MSDS Number: BXQCK

=== Responsible Party ===

Company Name:TECHNOLUBE PRODUCTS DIV (LUBRICATING SPECIALTY CO)

Address:3365 E SLAUSON AVE

City:VERNON

(FORMALLY IN LOS ANGELES)

State:CA

ZIP:90058

Country:US

Info Phone Num:213-581-2036/310-928-3311

Emergency Phone Num:213-581-2036/800-424-9300(CHEMTREC)

Preparer's Name:RICHARD J. EBERHARDT

CAGE:8Y842

=== Contractor Identification ===

Company Name:LUBRICATING SPECIALTIES CO. TECHNOLUBE PRODUCTS DIV

Address:3365 E. SLAUSON AVE

Box:City:LOS ANGELES

State:CA

ZIP:90058

Country:US

Phone:562-776-4033; FAX:562-776-4003

CAGE:8Y842

Company Name:NAUGHTON ENERGY CORP

Address:RT 940

Box:709

City:POCONO PINE

S

State:PA

ZIP:18350-0709

Country:US

Phone:570-646-0422

CAGE:1DL10

===== Composition/Information on Ingredients =====

Ingred Name:POLYALPHAOLEFIN BASE STOCK

CAS:68649-12-7

Fraction by Wt: 392F,>200C

Extinguishing Media:WATER FOG, FOAM, DRY CHEMICAL/CARBON DIOXIDE. WATER  
MAY CAUSE FROTHING. COOL FIRE-EXPOSED CONTAINERS WITH WATER.

Fire Fighting Procedures:DO NOT ENTER ANY ENCLOSED OR CONFINED AREA  
WITHOUT PROPER PROTECTIVE EQUIPMENT AND NIOSH-APPROVED  
SELF-CONTAINED

D BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:COMBUSTIBLE WHEN HEATED ABOVE FLASH POINT. WILL RELEASE FLAMMABLE VAPORS WHICH CAN BURN IN OPEN/BE EXPLOSIVE IN CONFINED SPACES IF EXPOSED TO IGNITION SOURCE.

===== Accidental Release Measures =====

Spill Release Procedures:SPILLS CAN BE TAKEN UP ON SAND, CLAY, EARTH & SHOVELD INTO CONTAINERS. PREVENT RUN-OFF TO ENTER SEWERS, WATERWAYS. WASH SPILL AREA WITH SOAP AND WATER AFTER PICKUP IS COMPLETE.

TE.

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, VENTILATED PLACE AWAY FROM EXCESSIVE HEAT AND STRONG OXIDIZERS. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:AVOID CONTACT WITH EYES AND SKIN. WASH THOROUGHLY AFTER HANDLING. LAUNDRER CLOTHING BEFORE REUSE. AVOID INHALING MISTS. EMPTY CONTAINERS OF THIS PRODUCT MAY BE HAZARDOUS DUE TO THE RETENTION OF RESIDUE S. DO NOT HEAT ABOVE FLASH POINT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF WORKING IN CONFINED AREAS, IF EXCESSIVE MISTING IS EXPECTED OR IF EXPOSURE MAY OR DOES EXCEED RECOMMENDED PERMISSIBLE EXPOSURE LIMITS (PEL), WEAR NIOSH-APPROVED ORGANIC VAPO R RESPIRATOR.

Ventilation:GENERAL ROOM VENTILATION SHOULD BE SUFFICIENT.

Protective Gloves:NITRILES IF PROLONGED/REPEATED CONTACT

Eye Protection:SAFETY GOGGLES IF SPLASHING ANTICIPATED

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER. INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DISCARD CONTAMINATED LEATHER GLOVES AND SHOES.

Supplemental Safety and Health

PERCENTAGE AND TRADE NAME CHANGED; SEE PNI A, SAME NSN.

===== Physical/Chemical Properties =====

HCC:V6

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Tex

t:>572F,>300C

Vapor Pres:1

Spec Gravity:0.845

Evaporation Rate & Reference: