

CPI ENGINEERING SERVICES, INC. -- SOLEST SERIES -- 9150-01-410-8972

=====
Product Identification
=====

Product ID:SOLEST SERIES

MSDS Date:11/01/1993

FSC:9150

NIIN:01-410-8972

MSDS Number: BXVTP

=== Responsible Party ===

Company Name:CPI ENGINEERING SERVICES, INC.

Address:2300 JAMES SAVAGE RD

Box:1666

City:MIDLAND

State:MI

ZIP:48641-1924

Country:US

Info Phone Num:517-496-3780

Emergency Phone Num:5

17-496-3780

Preparer's Name:THOMAS E. RAJEWSKI

CAGE:65226

=== Contractor Identification ===

Company Name:CPI ENGINEERING SERVICES, INC.

Address:2300 JAMES SAVAGE RD

Box:1666

City:MIDLAND

State:MI

ZIP:48842

Country:US

Phone:517-496-3780

CAGE:65226

=====
Composition/Information on Ingredients
=====

Ingred Name:NON-HAZARDOUS INGREDIENTS

Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

LD50 LC50 Mixture:TLV: NOT ESTABLISHED.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:AVOID BREATHING OIL MISTS.
Explanation of Carcinogenicity:THIS PRODUCT CONTAINS NO KNOWN
CARCINOGENS.
Effects of Overexposure:INGESTION-MAY CAUSE NAUSEA AND DIARRHEA.
INHALATION-PRODUCT IS NOT TOXIC BY INHALATION.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====
=

First Aid:INGESTION-CONSULT PHYSICIAN AT ONCE. INHALATION-IF OIL MIST
IS INHALED, REMOVE TO FRESH AIR AND CONSULT PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:230C-300C
Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, FOAM, WATER FOG. USE
WATER FOG TO COOL FIRE-EXPOSED CONTAINERS.
Fire Fighting Procedures:BURNING FLUID MAY EVOLVE IRRITATING/NOXIOUS
FUMES. FIREFIGHTERS SHOULD USE NIOSH/MNSA-APPROVED SELF-CONTA
INED
BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:USE WATER CAREFULLY NEAR EXPOSED/BURNING
LIUIDS. MAY CAUSE FROTHING AND SPLASHING OF HOT MATERIAL.

=====
===== Accidental Release Measures =====

Spill Release Procedures:WEAR SUITABLE PROTECTIVE EQUIPMENT, ESPECIALLY
GOGGLES. STOP SOURCE OF SPILL. DIKE SPILL AREA. USE ABSORBENT
MATERIALS TO SOAK UP FLUID. WASH SPILL AREA WITH LARGE AMOUNTS OF
WATER. PROPERLY DISPOSE O F ALL MATERIALS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY SEALED WHEN NOT
IN USE. PRODUCT IS HYGROSCOPIC. STORE UNDER NITROGEN HIGHLY
RECOMMENDED.
Other Precautions:DO NOT TAKE INTERNALLY. AVOID CONTACT WITH SKIN, EYES
AND CLOTHING.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE IN WELL VENTILATED AREA.
Ventilation:LOCAL EXHAUST.
Protective Gloves:STRONGLY RECOMMENDED.
Eye Protec

tion:GOGGLES.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH CONTAMINATED CLOTHING BEFORE RESUE.

Supplemental Safety and Health

THIS PRODUCT MAY DEGRADE SOME PAINTS AND RUBBER MATERIALS.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>650F,>343C

Vapor Pres: