

NILES CHEMICAL PAINT CO. -- N-1301A AIRCRAFT RED 31136 -- 8010-01-144-9884

=====  
Product Identification  
=====

Product ID:N-1301A AIRCRAFT RED 31136

MSDS Date:05/25/1995

FSC:8010

NIIN:01-144-9884

Kit Part:Y

MSDS Number: BYCNM

=== Responsible Party ===

Company Name:NILES CHEMICAL PAINT CO.

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Info Phone Num:616-683-3377

Emergency

Phone Num:219-236-5856

Preparer's Name:MIKE LICHTOWICH

CAGE:02388

=== Contractor Identification ===

Company Name:NILES CHEMICAL PAINT

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Phone:616-683-3377/219-236-5856

CAGE:02388

=====  
Composition/Information on Ingredients  
=====

Ingred Name:DIATOMACEOUS SILICA

CAS:14464-46-1

Fraction by Wt: 25%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT EST.

ACGIH TLV:0.08 MG/M3

Ingred Name:METHYL ETHYL KETONE (VP =

71.2 MM @ 20C)  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 16%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:200 PPM  
ACGIH TLV:200 PPM/STEL 300 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:POLYESTER RESIN  
Fraction by Wt: 13%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:BARIUM SULFATE  
CAS:7727-43-7  
RTECS #:CR0600000  
Fraction by Wt: 12%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT EST.  
ACGIH TLV:NOT EST.

Ingred Name:PM ACETATE (VP = 3.7 MM @ 20C)  
CAS:108-65-6  
RTECS #:AI8925000  
F  
raction by Wt: 12%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT EST.  
ACGIH TLV:NOT EST.

Ingred Name:BUTYL ACETATE (VP = 10.0 MM @ 20C)  
CAS:123-86-4  
RTECS #:AF7350000  
Fraction by Wt: 10%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:150 PPM  
ACGIH TLV:150 PPM/STEL 200 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE (VP = 7.0 MM @ 20C)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 2%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM/STEL 150 PPM  
EPA Rpt Qty:10

00 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:PROPRIETARY INGREDIENTS (NON HAZ.)  
Fraction by Wt: BALANCE  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT RELEVANT  
ACGIH TLV:NOT RELEVANT

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: EYES: SEVERE IRRITATION,  
LACRIMATION, REDNESS, BLURRED VISION. SKIN: REDNESS, IRRITATION,  
DEF  
ATTING LEADING TO DERMATITIS. BREATHING: NASAL & RESPIRATORY  
IRRITATION, CNS DEPRESSION, ASPHYXIATIO N. INGESTION:  
GASTROINTESTINAL IRRITATION. CHRONIC: HISTOLOGIC FIBROSIS OF LUNGS,  
NARCOSIS, COMA.  
Explanation of Carcinogenicity:NOT LISTED BY NTP, IARC OR OSHA.  
Effects of Overexposure:BREATHING: DIZZINESS, DROWSINESS, WEAKNESS,  
FATIGUE, CONFUSION, NAUSEA, HEADACHE, VERTIGO, POSSIBLE  
UNCONSCIOUSNESS. INGESTION: ABDOMINAL PAIN, NAUSEA, VOMITING,  
DIARRHEA.  
Medical Cond Aggr  
avated by Exposure:NK. TARGET ORGANS: RESPIRATORY  
SYSTEM, CNS, LUNGS, EYES, SKIN.

=====  
===== First Aid Measures =====

First Aid:INHAL: GET FRESH AIR. IF BREATHING STOPPED, START ARTIF RESP.  
GET MED AID. SKIN: IMMEDIATELY FLUSH W/WATER. IF MAT'L PENETRATES  
CLOTHING, REMOVE CONTAM CLOTHING, FLUSH SKIN W/WATER. GET MED AID.  
EYES: IMMED FLUSH W/LRG AMT WATER 15 MIN, LIFTING EYELIDS. GET MED  
AID IMMED. INGESTION: DRINK 1-2 GLASSES WATER. DON'T I  
NDUCE  
VOMITING. CONSULT PHYSICIAN/POISON CONTROL CENTER IMMED. TREAT  
SYMPTOMATICALLY

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:20.0F,-6.7C  
Lower Limits:1.0  
Upper Limits:10.0  
Extinguishing Media:DRY CHEMICAL, FOAM, CO2.  
Fire Fighting Procedures:WEAR POS PRESS SCBA W/FULL FACEPIECE & FULL  
PROTECTIVE CLOTHING. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO  
PREVENT PRESS BLD UP & AUTOIGNIT/EXPLOS.  
Unusual Fire/Explosion

Hazard:VAPOR HEAVIER THAN AIR, TRAVEL TO IGNIT  
SOURCE. ISOLATE FROM IGNIT SOURCE. CLSD CNTNR EXPLODE W/HEAT.  
APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS.\*

===== Accidental Release Measures =====

Spill Release Procedures:NO IGNIT SOURCES. MINIMIZE BREATHING VAPORS.  
AVOID SKIN CONTACT. SM: ABSORB W/INERT MAT'L (CLAY, SOIL, COMMERC  
ABSORB) SHOVEL RECLAIMED LIQ & ABSORB INTO RECOVERY/SALVAGE DRUMS.  
LG: DIKE (NO FURTHER M OVENT) & RECLAIM  
INTO SALVAGE DRUMS/TANK  
TRUCK.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID STORAGE IN HIGH TEMP AREAS OR  
NEAR FIRE OR OPEN FLAME. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN  
USE. AVOID ROUGH HANDLING.

Other Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN  
EMPTY. DO NOT WELD OR FLAME CUT ON EMPTY DRUMS. DO NOT WEAR CONTACT  
LENSES WHEN WORKING W/THIS MATERIAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR APPROP (TC-23C-75) FITTED HALF-MASK FOR  
FULL FACEPIECE RESPIRATOR (NIOSH/MSHA) DURING/AFTER APPLICATION  
UNLESS AIR MONITERING DEMONSTRATES VAPOR/MIST LEVELS BELOW TLV.  
FOLLOW RESPIRATOR MFR DIRECTIONS FOR USE.

Ventilation:PROVIDE SUFFICIENT VENTILATION (VOLUME/PATTERN) TO KEEP AIR  
CONC BELOW TLV PEL. REMOVE DECOMP PROD. VENT VAPOR EMITTED.

Protective Gloves:CHEM RESISTANT, NITRILE OR VITON

Eye Protection:CHEM GOGGLES/SAFETY  
GLASSES/FACE SHIELDS

Work Hygienic Practices:WASH ANY CONTAM CLOTHING OR CLOTH THAT BECOMES  
WET BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING  
RESTROOM.

Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:175 TO 302F

Vapor Density:>AIR

Spec Gravity:1.343

pH:NA

VOC Grams/Liter:4.63

Viscosity:70-85 KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:SLIGHT

Appearance and Odor:LIQUID,

SOLVENT ODOR  
Percent Volatiles by Volume:63.98  
Corrosion Rate:MINIMAL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS, NITRATES, ALKALIES, ACIDS.  
Stability Condition to Avoid:NK \*OVEREXPOS TO DECOMP PROD MAY CAUSE  
HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATE APPARENT. GET MEDICAL AID.  
Hazardous Decomposition Products:CAN PRODUCE CARBON MONOXIDE &/OR  
CARBON DIOXIDE.  
Conditions to Avoid Polymerization:HIGH TEMPERATURES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, LOCAL  
REGULATIONS. EPA HAZ WASTE CODE: D001 (IGNITABLE).

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied  
, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.