

CAAP CO INC -- CAAPCOAT POLYURETHANE CURING AGENT -- 8040-01-282-7954

=====
Product Identification
=====

Product ID:CAAPCOAT POLYURETHANE CURING AGENT

MSDS Date:01/01/1994

FSC:8040

NIIN:01-282-7954

Kit Part:Y

MSDS Number: BZLMY

=== Responsible Party ===

Company Name:CAAP CO INC

Address:152 PEPES FARM RD

City:MILFORD

State:CT

ZIP:06460

Country:US

Info Phone Num:203-877-0375/202-483-7616(CHEMTREC)

Emergency Phone Num:203-877-0375/800-424-9300(CHEMTREC)

CAGE:60922

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT

ZIP:06460

Country:US

Phone:203-877-0375

CAGE:60922

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ISOBUTYL KETONE (HEXONE) (SARA 313) (CERCLA)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 35%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:50 PPM/75 STEL; 9596

E

PA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ALIPHATIC AMINE
Fraction by Wt: 65%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS UNKNOWN.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, LIVER,
KIDNEY. ACUTE- MAY CAUSE EYE DAMAGE. INHALATION MAY CAUSE
IRRITATION. MAY CAU
SE SKIN IRRITATION & BURNS. MAY BE HARMFUL IF
INGESTED. ASPIRATION HAZARD. CHRONIC- MAY CAU SE DERMATITIS,
POSSIBLY SENSITIZATION, LIVER & KIDNEY DAMAGE, NEURAL IMPAIRMENT.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, HEADACHE, DIZZINESS, NAUSEA,
VOMITING, DIARRHEA, LOSS OF COORDINATION, ABDOMINAL PAIN, WEAKNESS,
CONFUSION, BREATHING DIFFICULTY, EYE DAMAGE, SKIN BURNS
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN
DISORDERS, EYE
PROBLEMS OR IMPAIRED LIVER, KIDNEY, CNS OR
RESPIRATORY FUNCTION MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS
PRODUCT.

===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH
AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15
MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. ORAL:DO
NOT IN DUCE VOMITING. IF CONSCIOUS, RINSE MOUTHWITH WATER. SEEK
IMMEDIATE MEDICAL
ATTENTION. IF SPONTANEOUS VOMITING OCCURS, KEEP
HEAD BELOW HIPS TO PREVENT ASPIRATION OF VOMITUS INTO LUNGS.

===== Fire Fighting Measures =====

Flash Point Method:TOC
Flash Point:=23.3C, 74.F

===== 74 =====

Lower Limits:1.2
Upper Limits:8.0
Extinguishing Media:WATER FOG, FOAM, DRY CHEMICAL/CARBON DIOXIDE. DON'T
USE DIRECT STREAM OF WATER. PRODUCT WILL FLOAT AND CAN BE
REIGNITED.
Fire Fighting

Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE.
Unusual Fire/Explosion Hazard:VAPOR IS HEAVIER THAN AIR AND CAN TRAVEL CONSIDERABLE DISTANCE OR BE MOVED BY VENTILATION TO A SOURCE OF IGNITION AND FLASH BACK. CONTAINER MAY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES OF IGNITION. VENTILATE AREA. CONTAIN SPILL. PICK UP SPILL WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND, EARTH OR VERMICULITE. GROUND ALL HANDLING EQUIPMENTS. PREVENT LIQUID FROM ENTERING SEWERS OR WATERWAYS.
Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL PLACE, OUT OF HOT SUN, BELOW 90F, AWAY FROM SOURCES OF IGNITION & INCOMPATIBLE MATERIALS. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:EMPTY CONTAINERS RETAIN RESIDUE AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS. DO NOT RE-USE CONTAINER. AVOID BREATHING VAPO RS OR MISTS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL(TLV), USE NIOSH APPROVED ORGANIC VAPOR RESPIRATOR OR SELF CONTAINED BREATHING APPARATUS, WITH A FULL FACE PIECE, OPERATED IN POSITIVE PR ESSURE MODE.
Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).
Protective Gloves:COTTON LINED NEOPRENE
Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES
Other Protective Equipment:EYE WASH STATION, SAFETY SHOWER, INDUSTRIAL-TYPE WORK CLOTHING TO PROTECT SKIN
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMI

NATED CLOTHING OR
FOOTWEAR.

Supplemental Safety and Health
KEY1:F3

===== Physical/Chemical Properties =====

HCC:F2
NRC/State Lic Num:NOT RELEVANT
Boiling Pt:=116.1C, 241.F
Vapor Pres:15
Vapor Density:3.5
Spec Gravity:0.83
Evaporation Rate & Reference:1.6 (N-BUTYL ACETATE=1)
Solubility in Water:SLIGHT
Appearance and Odor:CLEAR YELLOW LIQUID WITH PUNGENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to
Avoid:YES
STRONG OXIDIZING AGENTS, STRONG ACIDS
Stability Condition to Avoid:HIGH HEAT (ABOVE 100F/38C), SPARKS, OPEN
FLAMES AND OTHER SOURCES OF IGNITION
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
NITROGEN OXIDES AND AMMONIA MAY BE RELEASED.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE
FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. INCINERATE IN
APPROVED FACILITY.
DO NOT INCINERATE CLOSED CONTAINER.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this in

formation to their
particular situation.