View NSN Online: https://aerobasegroup.tw/nsn/7930-01-398-0887

AMERICAN RESOURCE, INC. -- SAFE-T-SOLV -- 7930-01-398-0887

Product ID:SAFE-T-SOLV MSDS Date:06/01/1987 FSC:7930 NIIN:01-398-0887 MSDS Number: BZLSL === Responsible Party === Company Name: AMERICAN RESOURCE, INC. Box:560065 City:DALAS State:TX ZIP:75247 Country:US Info Phone Num:214-638-1100 Emergency Phone Num:800-638-1209 CAGE:025Y9 === Contractor Identification === Company Name: AMERICAN RESOURCE, INC. Box:560065 City:DALAS State:TX ZIP:75247 Country:US Phone:214-638-1100 CAGE:025Y9 Ingred Name: D-LIMONENE, REDISTILLED CAS:5989-27-5 RTECS #:GW6360000 Other REC Limits:NONE RECOMMENDED **OSHA PEL:NA** ACGIH TLV:NA

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:CAN CAUSE EYE DAMAGE OR IRRITATION. MAY CAUSE DEFATTING OF SKIN OR SKIN IRRITATION. HARMFUL IF SWALLOWED.
Effects of Overexposure:REDNESS OR BURNING OF EYES. DRYNESS OR BURNING OF SKIN. NAUSEA FROM INGESTION.
Medical Cond Aggravated by Exposure:NONE KNOWN
======================================
First Aid:EYES: WASH W/WATER 20 MINUTES. SEE DR. SKIN: REMOVE CLOTHING. WASH SKIN W/SOAP & WATER. SEE DR. INGESTION: DRINK M ILK/WATER TO
DILUTE. GET MEDICAL AID.
======================================
Flash Point Method:TCC Flash Point:142F,61C Lower Limits:0.7 Upper Limits:6.1
Extinguishing Media:DRY POWDER, FOAM, CO2 (FLASH POINT W/METHOD TOC = 153F) Fire Fighting Procedures:CLASS B. Unusual Fire/Explosion Hazard:COMBUSTIBLE LIQUID. KEEP AWAY FROM OPEN FLAME/SPARKS.
======================================
Spill Release Procedures:SMALL: USE S TANDARD ABSORBENT MATERIAL. LARGE: SHOULD BE DIKED/PUMPED TO CONTAINER FOR DISPOSAL.
======================================
Handling and Storage Precautions:STORE AWAY FROM OPEN FLAME/SPARKS. USUAL PRECAUTIONS FOR COMBUSTIBLE LIQUIDS. Other Precautions:NONE
========= Exposure Controls/Personal Protection ====================================
Respiratory Protection:NOT REQUIRED Ventilation:KEEP CONCENTRATIONS BELOW 100 PPM. Protective Gloves:INDUSTRIAL RUBBER Eye Protection

:SAFETY GOGGLES/GLASSES. Work Hygienic Practices:NO SPECIAL REQUIREMENTS. Supplemental Safety and Health NK

Boiling Pt:B.P. Text:358F,181C Melt/Freeze Pt:M.P/F.P Text:NA Vapor Pres:1 MM @ 20C Vapor Density:4.69 AIR=1 Spec Gravity:0.838 (WATER=1) Evaporation Rate & amp; Reference:0.6 (BUAC=1) Solubility in Water:VERY SLIGHTLY SOL. Appearance and Odor:WATER WHITE LIQUID, SLIGHT CITRUS ODOR

======= Stability and React

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Hazardous Decomposition Products:CO2 OR CO ON COMBUSTION

Waste Disposal Methods: INCINERATE SMALL AMOUNTS. MAY BE DILUTED W/WATER & REMOVED TO SEWER. FOLLOW LOCAL, STATE, FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Depar tment

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.