View NSN Online: https://aerobasegroup.tw/nsn/6850-01-354-4322

EASTMAN KODAK COMPANY -- 815 8396 KODAK COLOREDGE BLACK TONER -- 6850-01-354-4322

Product ID:815 8396 KODAK COLOREDGE BLACK TONER

MSDS Date:01/19/1994

FSC:6850

NIIN:01-354-4322

MSDS Number: BZNWF === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650 Country:US

Info Phone Num:716-477-3194 MSDS:800-

242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD Box:City:ROCHESTER

State:NY

ZIP:14650-3129 Country:US

Phone:800-828-6203

CAGE:5K871

====== Composition/Information on Ingredients ======

Ingred Name:BENZYLDIMETHYLOCTADECYLAMMONIUM 3-NITRO-BENZENESULFONATE

CAS:124088-59-1

Fraction by Wt: 90-95%

Other REC Limits: NONE RECOMMENDED

Ingred Name: CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000 Fraction by Wt: 1-5%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3; 9596

Ingred Name: POLYMER - CGH

Fraction by Wt: 1-5%

Other REC Limits: NONE RECOMMENDED

Ingred Name:BENZYLDIMETHYLOCTADECYLAMMONIUM 3-NITRO-BENZENESULFONATE

CAS:124088-59-1 Fraction by Wt: 1-5%

Oth

er REC Limits:NONE RECOMMENDED

========= Hazards Identification =============

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT KNOWN. Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION-EXPECTED TO BE A LOW HAZARD FOR RECOMMENDED HANDLING. EYES-NO SPECIFIC HAZARD KNOWN. MAY CAUSE TRANSIENT IRRITATION. SKIN-EXPECTED TO BE A LOW HAZARD FOR RECOMMENDED HANDLING. INGESTION-

EXP ECTED TO BE A LOW INGESTION HAZARD.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:OVEREXPOSURE TO CARBON BLACK DUST MAY RESULT IN IRRITATION OF THE RESPIRATORY TRACT AND BENIGN DEPOSITION OF CARBON BLACK IN THE LUNG.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid:INHALATION-IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS PERSISTS. EYES-ANY M

ATERIAL THAT CONTACT THE EYES SHOULD BE WASHED OUT IMMEDIATELY WITH WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. SKIN-WASH WITH SOAP & WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION-DRINK 1 OR 2 GLASSES OF WATER. SEEK MEDICAL ATTENTION. Extinguishing Media: WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL. Fire Fighting Procedures: NONE. Unusual Fire/Explosion Hazard:POWDERED MATERIAL MAY FORM EXPLOSIVE DUST-AIR MIXTURE. ======== Accidental Release Measures ============ Spill Release Procedures: DO NOT USE A VACUUM CLEANER TO CLEAN UP SPILLS OF POWDERED TONERS. THE VERY FINE PARTICLES CAN CAUSE A FIRE OR EXPLOSION. SWEEP MATERIAL ONTO PAPER AND PLACE IN A FIBER CARTON. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER. ============= Handling and Storage ========================== Handling and Storage Precautions: KEEP CONTAINER CLOSED. KEEP FROM CONTACT WITH OXIDZING MATERIALS. MINIMIZE DUST GENERATION AND ACCUMULATION. Other Precautions: USE WITH ADEQUATE VENTILATION. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: NONE SHOULD BE NEEDED. Ventilation: GOOD VENTILATION (TYPICALLY 4-6 ROOM VOLUMES/HR) SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS Protective Gloves: MINIMIZE SKIN CONTACT. Eye Protection: MINIMIZE EYE CONTACT. Other Protective Equipment: EYE BATH, WASHING FACILITI ES, SAFETY SHOWER. Work Hygienic Practices: GOOD INDUSTRIAL HYGIENE PRACTICES SHOULD BE FOLLOWED WHICH INCLUDE PREVENTING EYE CONTACT MINIMIZING SKIN CONTACT. Supplemental Safety and Health LOW HAZARD FOR RECOMMENDED HANDLING. ========= Physical/Chemical Properties ===========

HCC:N1

Melt/Freeze Pt:M.P/F.P Text:140F,60C

Vapor Pres:NEGLIGIBLE Vapor Density:NEGLIGIBLE

Spec Gravity:>1.00

Evaporation Rate & Deference: NEGLIGIBLE

Solubility in Water: NEGLIGIBLE

Appearance

Percent Volatiles by Volume:NIL	
========= Stability and Reactivity Data ===========	
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS.	

and Odor:SOLID (POWDER), BLACK, SLIGHT ODOR.

Hazardous Decomposition Products: NONE.

====== Disposal Considerations ==========

Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods:CAN BE INCINERATED WHEN IN COMPLIANCE WITH LOCAL REGULATIONS. CONTRACT WITH A LICENSED DISPOSAL AGENCY. DISCHARGE,

TREATMENT OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE OR LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent profession al advice to verify and assume responsibility for the suitability of this information to their particular situation.