View NSN Online: https://aerobasegroup.tw/nsn/6750-01-165-5425

EASTMAN KODAK COMPANY -- 199 7915 VERSAMAT 885 DEVELOPER STARTER (WORKING SOLUTION) -- 6750-01-165-5425

============= Product Identification =================

Product ID:199 7915 VERSAMAT 885 DEVELOPER STARTER (WORKING SOLUTION)

MSDS Date:06/24/1992

FSC:6750

NIIN:01-165-5425

MSDS Number: BZQYD === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650 Count ry:US

Info Phone Num:716-477-3194 MSDS:800-242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD Box:City:ROCHESTER

State:NY

ZIP:14650-3129 Country:US

Phone:800-828-6203

CAGE:5K871

Company Name: FULLER

AND D ALBERT INC Address:3170 CAMBELL

Box:2706 City:FAIRFAX State:VA

ZIP:22031-2302 Country:US

Phone:703-591-8000

CAGE:82960

======= Composition/Information on Ingredients ========

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000 Fraction by Wt: 90-95%

Other REC Limits: NONE RECOMMENDED

Ingred Name:TRIETHYLENE GLYCOL

CAS:112-27-6

RTECS #:YE4550000 Fraction by Wt: 1-5%

Other REC Limits: NONE RECOMMENDED

Ingred Name:SODIUM SULFITE

CAS:7757-83-7

RTECS #:WE2150000 Fraction by Wt: 1-

5%

Other REC Limits: NONE RECOMMENDED

Ingred Name: HYDROQUINONE (SARA 302/313) (CERCLA)

CAS:123-31-9

RTECS #:MX3500000 Fraction by Wt: 1%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9596

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: POTASSIUM SULFITE

CAS:10117-38-1

RTECS #:WT3530000 Fraction by Wt: 100C Vapor Pres:18MM @ 20C

Vapor Density:0.6 Spec Gravity:1.025

pH:10

Evaporation Rate & Reference: N/P (N-BUTYL ACETATE=1)

Solubility in Water: COMPLETE

Appearance and Odo

Percent Volatiles by Volume:90 %
========== Stability and Reactivity Data ===========
Stability Indicator/Materials to Avoid:YES NONE WITH COMMON MATERIALS AND CONTAMINANTS WITH WHICH MATERIAL MAY REASONABLY COME INTO CONTACT. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:NONE. Conditions to Avoid Polymerization:WILL NOT OCCUR.
======== Disposal Considerations =======

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO LOCAL, STATE AND FEDERAL REGULATIONS. FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any per son utilizing this

r:CLEAR, LIGHT YELLOW SOLUTION; ODORLESS.

========

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.