View NSN Online: https://aerobasegroup.tw/nsn/6750-01-319-6474

EASTMAN KODAK COMPANY -- 102 3208 DURAFLO RT DEVELOPER REPLENISHER (WORKING SOLUTION) -- 6750-01-319-6474

============= Product Identification ==================

Product ID:102 3208 DURAFLO RT DEVELOPER REPLENISHER (WORKING SOLUTION)

MSDS Date:12/08/1993

FSC:6750

NIIN:01-319-6474

MSDS Number: BZQZB === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650

C

ountry:US

Info Phone Num:716-477-3194 MSDS:800-242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD Box:City:ROCHESTER

State:NY

ZIP:14650-3129 Country:US

Phone:800-828-6203

CAGE:5K871

Composition/Information on Ingredients ========

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000 Fraction by Wt: 80 - 85%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Ingred Name: SODIUM BISULFITE (SASA III) (CERCLA)

CAS:7631-90-5

RTECS #:VZ2000000 Fraction by Wt: 1 - 5%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3; 9495

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: POTASSIUM SULFITE

CAS:10117-38-1

RTECS #:WT3530000

Fra

ction by Wt: 1 - 5%

Other REC Limits: NONE RECOMMENDED

Ingred Name:SODIUM SULFITE

CAS:7757-83-7

RTECS #:WE2150000 Fraction by Wt: 1 - 5%

Other REC Limits: NONE RECOMMENDED

Ingred Name: POTASSIUM CARBONATE

CAS:584-08-7

RTECS #:TS7750000 Fraction by Wt: 1 - 5%

Other REC Limits: NONE RECOMMENDED

Ingred Name:GLUTARALDEHYDE BIS(SODIUM BISULFITE)

CAS:7420-89-5

Fraction by Wt: 1 - 5%

Other REC Limits: NONE RECOMMENDED

Ingred Name:POTASSIUM HYDROXIDE (CERCLA)

CAS:1310-58-3

RTECS #:TT2100000

Fraction by W

t: 1 - 5%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:C 2 MG/M3

ACGIH TLV:C 2 MG/M3; 9495

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: HYDROQUINONE (SARA 302/313) (CERCLA)

CAS:123-31-9

RTECS #:MX3500000

Fraction by Wt: 212F,>100C

Vapor Pres:18 @ 68F Vapor Density:0.6 Spec Gravity:1.12

pH:9.6

Solubility in Water: COMPLETE

Appearance and Odor: COLORLESS LIQUID, ODORLESS

Percent Volatiles by Volume:80-85

======== Stability and Reactivity Data ==========

Stability Indicat or/Materials to Avoid:YES STRONG ACIDS Stability Condition to Avoid:NONE Hazardous Decomposition Products:SULFUR DIOXIDE

======= Disposal Considerations ===========

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO FEDERAL, STATE OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE AMOUNT OF WATER IF PERMITTED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Departmen

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.