

SHERWIN-WILLIAMS CO THE SPECIALTY DIV -- 1303/1303A CRYSTAL CLEAR SPECIALTY SPRAY
COATINGS/GRAPHIC -- 8010-01-005-8577

===== Product Identification =====

Product ID:1303/1303A CRYSTAL CLEAR SPECIALTY SPRAY COATINGS/GRAPHIC

MSDS Date:03/01/1995

FSC:8010

NIIN:01-005-8577

MSDS Number: CBSDW

=== Responsible Party ===

Company Name:SHERWIN-WILLIAMS CO THE SPECIALTY DIV

Address:31500 SOLON RD

City:SO

LON

State:OH

ZIP:44146-5000

Country:US

Info Phone Num:800-247-3266/800-797-3332

Emergency Phone Num:216-292-7400

CAGE:DO642

=== Contractor Identification ===

Company Name:SHERWIN-WILLIAMS CO THE SPECIALTY DIV.

Address:6830 COCHRAN RD.

Box:6709

City:SOLON

State:OH

ZIP:44139-3908

Phone:216-292-7400

CAGE:DO642

Company Name:SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.

Address:26300 FARGO AVENUE

Box:City:BEDFORD HEIGHTS

State:OH

ZIP:44146

Country:US

Phone:216-292-7400 OR 216-595-8634

CAGE:09800

=====

=====
Composition/Information on Ingredients
=====

Ingred Name:PROPANE (PROPELLANT)
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 15%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9596

Ingred Name:BUTANE (PROPELLANT)
CAS:106-97-8
RTECS #:EJ4200000
Fraction by Wt: 15%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:800 PPM
ACGIH TLV:800 PPM; 9596

Ingred Name:VM & P NAPHTHA
CAS:64742-89-8
Fraction by Wt: 22%
Other REC Limits:NONE RECOMMENDED

Ingred Name:PETROL
EUM HYDROCARBON, (MINERAL SPIRITS)
CAS:64742-47-8
RTECS #:OA5504000
Fraction by Wt: 2%
Other REC Limits:NONE RECOMMENDED

Ingred Name:TOLUENE (SARA 313) (CERCLA)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 13%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM; Z-2
ACGIH TLV:S, 50 PPM; 9596
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA 313)
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: 3%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/125ST

EL;9596
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA 313) (CERCLA)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 13%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/150STEL;9596
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA 313) (CERCLA)
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 11%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:750PPM/1000STEL;9596
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LB
S

Ingred Name:VOLITILE ORGANIC CONTENT AS LISTED ON MSDS, VOC AS % BY WT
PER BAAQMD RULE 49, 92%
RTECS #:9999999VC
Fraction by Wt: NA
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EXPO MAY BE BY INHAL &/OR SKIN/EYE
CONTACT DEPENDING ON COND
ITIONS OF USE.TO MIN EXPO FOLLOW
RECOMMENDATIONS FOR PROPER USE,VENTI,PPE. ACUTE:IRRIT EYE/SKIN/RESP
SYS.MAY CAUSE CNS DEPRESS.EXTREME OVERE XPO MAY RESULT IN
UNCONSC,POSSIBLE DEATH.CHRONIC:PROL/REP HEXANE EXPO MAY CAUSE DMG
TO NERVE TISSUE OF ARM/LEG.(SUPPLE)
Explanation of Carcinogenicity:PER MSDS:NO INGRED IN PROD LISTED CAR BY
IARC/NTP/OSHA.CA PROP 65:CONTAINS CHEM TO CAUSE CAN,BIRTH DEF,OR
REPROD HARM.
Effects of Overexposure:HEADACHE,DIZZINESS,NAUSEA,LOSS OF COORDIN

ATION

ARE INDICATIONS OF EXCESSIVE EXPO TO VAPOR/SPRAY MISTS.REDNESS & ITCHING OR BURNING SENSATION MAY INDICATE EYE/EXCESSIVE SKIN EXPO.DMG TO NERVE TISSUE OF ARMS/LEGS RESULTING IN MUSCULAR WEAKNESS & LOSS OF SENSATION.

Medical Cond Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

===== First Aid Measures =====

First Aid:INHAL:IF EFFECTED REMOVE FROM EXPO.RESTORE BREATH.KEEP WARM/QUIET.SKIN:WASH AREA THOROUGHLY W/SOAP/WATER.REMOVE C ONTAMIN CLOTHIN.EYE:FLUSH W/LG AMTS OF WATER FOR 15MINS.GET MED ATTN.INGEST:GET MED ATT N.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point: