

DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV. -- PC:PB0006 HYSOL PC29M PART B --
5970-00-242-0505

===== Product Identification =====

Product ID:PC:PB0006 HYSOL PC29M PART B

MSDS Date:07/07/1995

FSC:5970

NIIN:00-242-0505

Kit Part:Y

MSDS Number: CCBZD

=== Responsible Party ===

Company Name:DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV.

Address:211 FRANKLIN ST.

City:OLEAN

State:NY

ZIP:14760-1297

Country:US

Info Phone Num:716-372-6300/FAX 716-372-6864

Emergency Phone Num:800-424-9300(CHEMTREC)/716-372-6309

CAGE:04347

=== Contractor Identification ===

Company Name:DEXTER CORP DEXTER ELECTRONIC MATERIALS DIV

Address:15051 E DON JULIAN RD

Box:City:LA PUENTE

State:CA

ZIP:91746

Country:US

Phone:818-968-6511

CAGE:12405

Company Name:DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV

Address:211 FRANKLIN ST.

Box:City:OLEAN

State:NY

ZIP:14760-1297

Country:US

Phone:716-372-6300/6309

CAGE:04347

Company

Name: MCKEOWN ROBERT CO. INC.
Address: 111 CHAMBERS BROOK RD.
Box: City: SOMERVILLE
State: NJ
ZIP: 08876
Country: US
Phone: 908-218-9000
CAGE: 7B953

=====
===== Composition/Information on Ingredients =====

Ingred Name: PROPYLENEGLYCOL MONOMETHYL ETHER ACETATE
CAS: 108-65-6
RTECS #: AI8295000
Fraction by Wt: 10-30%
Other REC Limits: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED.
ACGIH TLV: NOT ESTABLISHED.

Ingred Name: XYLENES (O-,M-,P- ISOMERS) (SARA 313) (CERCLA)
CAS: 1330-20-7
RTECS #: ZE2100000
Fr
action by Wt: 5-10%
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM/150 STEL; 9596
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Ingred Name: ETHYL BENZENE (SARA 313)
CAS: 100-41-4
RTECS #: DA0700000
Fraction by Wt: 1-5%
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM/125 STEL; 9596
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Ingred Name: CASTOR OIL, ESTER WITH PENTAER
CAS: 68459-68-7
Fraction by Wt: 60-100%
Other REC Limits: NONE RECOMMENDED

=====
===== H

azards Identification =====

LD50 LC50 Mixture:TESTING HAS NOT BEEN PEFORMED ON PRODUCT

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE:IRRIT.SKIN:PROL/REP CONTACT

IRRIT.CONTACT W/PROD @ELEVATED TEMP(>150C)CAN RESULT IN THERMAL

BURNS.INHAL:HARMFUL,MAY CAUSE ALLERGIC RESP

RX(ASTHMA).INGEST:MODERATELY TOXIC,MAY CAUSE VOMIT.

Explanation of Carcinogenicity:PER MSDS:NOT LISTE

D.

Effects of Overexposure:SKIN/EYE IRRITATION, THERMAL BURNS, HARMFUL IF

INHALED, ALLERGIC RESPIRATORY REACTION (ASTHMA). MODERATELY TOXIC

IF INGESTED, VOMITING.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN/EYE DISORDERS MAY

BE AGGRAVATED BY EXPO TO PROD.PRE-EXISTING SKIN/LUNG ALLERGIES MAY

INCREASE CHANCE OF DEVELOPING INCREASED ALLERGIC SYMPTOMS FROM EXPO

PROD.TARORG:EYE,SKIN,RESP TRC

===== First Aid Measures =====

First Aid

:EYE:IMMED WASH/FLUSH W/WATER FOR MIN 10MINS.SEEK MED

ATTN.SKIN:WASH OFF IN WATER/SHOWER.REMOVE CONTAMIN

CLOTH/SHOES.IRRIT DEVELOPS SEEK MED ATTN.INHAL:MOVE TO FRESH

AIR.NOT BREATH GIVE MOUTH-TO-MOUTH RESUSCIT.BREATH DIFF GIVE

OXY.SEEK MED ATTN.INGEST:DO NOT INDUCE VOMIT.SEEK PROMPT MED

ATTN.DR:TREAT SHOULD BE DIRECTED @CNTRL OF SYMPTOMS/CLINICAL

CONDITIONS.ANTIDOTE:NO SPEC ANTIDOTE.

===== Fire Fighting Measures =====

Flash Point Method

:CC

Flash Point:=30.C, 86.F

===== 86 =====

Autoignition Temp:Autoignition Temp Text:NP

Lower Limits:NP

Upper Limits:NP

Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:RECOMMENDED USE OF SELF-CONTAINED BREATHING

APPARATUS (SCBA).

Unusual Fire/Explosion Hazard:NO UNUSUAL FIRE OR EXPLOSION HAZARDS.

===== Accidental Release Measures =====

Spill Release Procedures:CONTA

IN IN NAT FORM/WITH SAND/DIRT(INERT
MATL).ELIMINATE ALL IGN SOURCES.PREVENT RUNOFF TO STORM
SEWERS/DITCHES/WATERWAYS.SHOVEL/SCRAPE(NON-METALLIC)ABSORBED WASTE
MATLS ITNO DISPO CNTNR.SEAL LID TIGH TLY W/TAPE/LOCKING
RING.LABEL.CLEANUP IMMED (SUPP)
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:PLASTIC CNTNR MAY BE SLIPPERY WHEN
HNDLG.