View NSN Online: https://aerobasegroup.tw/nsn/5330-00-548-4806

JOHN CRANE-HOUDAILLE INC MARINE & GOVERNMENT GROUP -- P/N 1580415 T STYLE 100 --5330-00-548-4806 Product ID: P/N 1580415 T STYLE 100 MSDS Date:12/12/1995 FSC:5330 NIIN:00-548-4806 MSDS Number: CCCBK === Responsible Party === Company Name: JOHN CRANE-HOUDAILLE INC MARINE & GOVERNMENT GROUP Address:6400 OAKTON ST ; FORMERLY PACKING CO **City:MORTON GROVE** State:IL ΖI P:60053-2725 Country:US Info Phone Num:708-967-2400 Emergency Phone Num:708-967-2400/2879 CAGE:71724 === Contractor Identification === Company Name: JOHN CRANE-HOUDAILLE INC MARINE & GOVERNMENT GROUP Address:6400 OAKTON ST ; FORMERLY PACKING CO Box:City:MORTON GROVE State:IL ZIP:60053-2725 Country:US Phone:708-967-2400/2879 CAGE:71724 Ingred Name:COTTON TWINE Other REC Limits:NONE RECOMMENDED Ingred Name: REFINED MINERAL OIL O **R ANIMAL FATTY OIL** CAS:8016-28-2 Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST) Ingred Name: LEAD FOIL OR LEAD (SARA 313) (CERCLA) CAS:7439-92-1 RTECS #: OF7525000 Other REC Limits:NONE RECOMMENDED OSHA PEL:SEE 1910.1025 ACGIH TLV:0.05MG/M3, A3; 9596 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB Ingred Name: GRAPHITE, NATURAL CAS:7782-42-5 RTECS #:MD9659600 Other REC Limits:NONE RECOMMENDED OSHA PEL:15 MPPCF; Z-3 ACGIH TLV:2 MG/M3 RDUST: 9596

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:MILD EYE IRRITATION. HANDLING THIS PRODUCT MAY CAUSE LEAD POISONING; ROUTES ARE BY INHALTION OF DUST, SKIN ABSORPTION OR BY INGESTION. ACUTE: ABDOMINAL COLIES, HEMOLYTIC ANEMIA, NEURITIS, ENCEPHALOPAT HY. CHRONIC: ARTHRALGIAS, MOTOR DYSFUNCTION, MALE INFERTILITY, FETAL TOXICITY, GOUT, RENAL FAILURE. ENCEPHALOPATHY. Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN. Effects of Overexposure: ALTERED BOWEL HABITS, FATIGUE, ACHING OF BONES & MUSCLES, HEADACHE, WEAKNESS, DEPRESSION, IMPOTENCE, VAGUE GASTROINTESTINAL DIFFICULTIES, MEMORY DYSFUNCTION. MILD EYE IRRITATION. Medical Cond Aggravated by Exposure: PRE-EXISITING NEUROMUSCULAR, HEMATOLOGICAL, RENAL, LIVER, LUNG AND CENTRAL NER **VOUS SYSTEM DISORDERS.** First Aid:IN ALL CASES GET MEDICAL ATTENTION. EYES-FLUSH WITH WATER FOR 15 MINUTES. SKIN-REMOVE CONTAMINATED CLOTHES. WASH WITH MILD SOAP & WATER. INHALED-REMOVE TO FRESH AIR. INGESTED-IF CONSCIOUS, INDUCE VOMI TING. Flash Point Method:COC Flash Point:565F,296C Lower Limits:NONE Upper Limits:NONE Extinguishing Media:W ATER FOG, CARBON DIOXIDE, DRY CHEMICAL-DOLOMITIC POWDER + SODIUM CHLORIDE + GRAPHITE, FOAM. Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL FIRE FIGHTER'S PROTECTIVE GEAR. Unusual Fire/Explosion Hazard:NOT EXPLOSIVE. LEAD POWDER REACTS VIGOUOUSLY WITH OXIDIZERS. DO NOT EXPOSE MOLTEN LEAD TO WATER AS IT IS EXPLOSIVE. 

Spill Release Procedures: VACUUM DUST IF ANY IS RELEASED BY MECHANICAL

PROCESSING OF THIS MATERIAL. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:STORE AWAY FROM FOOD AREAS AND CHILDREN. AVOID BREATHING DUST BY USING OSHA-APPROVED DUST MASK WHEN CUTTING THIS PRODUCT.

Other Precautions:WASH HANDS WITH SOAP & WATER AFTER HANDLING. CHANGE & CLEAN CLOTHING EVERY DAY WHEN DEALING WITH LEAD CONTAINING MATERIALS.

====== Exposure Controls

/Personal Protection =========

Respiratory Protection: IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED RESPIRATOR WITH DUST CARTRIDGE OR AN AIR-SUPPLIED RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 19 10.134.

Ventilation:NONE NORMALLY REQUIRED.

Protective Gloves: REQUIRED-PVA, BUTYL, RUBBER.

Eye Protection: REQUIRED-SAFETY GLASSES.

Other Protective Equipment: CHANGE & CLEAN CLOTHING DAILY. DO NOT TAKE CONTAMINATED CLOTHES H

OME. DLA-HMIS: EYE WASH STATION & SAFETY

SHOWER.

Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE. Supplemental Safety and Health

## HCC:T6

Boiling Pt:B.P. Text:3164F,1740C Melt/Freeze Pt:M.P/F.P Text:621F,327C Spec Gravity:11.3 Solubility in Water:NOT SOLUBLE Appearance and Odor:FLEXIBLE SILVERY METALLIC PACKING MADE BY SPIRAL WRAPPI NG BABBIT (LEAD) FOIL...

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS (EG PERCHLORATES & PEROXIDES), MILD ACIDS & ALKALIES. DO NOT EXPOSE MOLTEN LEAD TO WATER.
Stability Condition to Avoid:THIS PRODUCT IS USEFUL IN TEMPERATURES UP TO 450F (4-10 PH).
Hazardous Decomposition Products:LEAD VAPORS, FUMES & OXIDES.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

====== Disposal Consi

derations ==============

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document shou

Id seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.