

EASTMAN KODAK COMPANY -- 825 5549 FLEXICOLOR RA BLEACH REPLENISHER NR --
6750-01-360-5171

===== Product Identification =====

Product ID:825 5549 FLEXICOLOR RA BLEACH REPLENISHER NR

MSDS Date:02/07/1997

FSC:6750

NIIN:01-360-5171

MSDS Number: CCJGD

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-477

-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composition/Information on Ingr

edients =====

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 60 - 65%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

Ingred Name:AMMONIUM FERRIC PROPYLENEDIAMINETETRAACETIC ACID
CAS:111687-36-6
Fraction by Wt: 10 - 15%
Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM BROMIDE
CAS:12124-97-9
RTECS #:BO9170000
Fraction by Wt: 5 - 10%
Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM NITRATE
CAS:6484-52-2
RTECS #:BR9050000
Fr
action by Wt: 8%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SUCCINIC ACID
CAS:110-15-6
RTECS #:WM4900000
Fraction by Wt: 1 - 5%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS UNKNOWN.
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS:EYE. ACUTE- EYE:NO
SPECIFIC HAZARD KNOWN. MAY CAUSE TRANSIE

NT IRRITATION. SKIN:LOW

HAZARD FOR RECOMMENDED HANDLING. INHALE:EXPECTED TO BE A LOW HAZARD. ORAL:EXPECTED TO BE A LOW INGESTION HAZARD. CHRONIC-UNKNOWN.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:TRANSIENT EYE IRRITATION

Medical Cond Aggravated by Exposure:NONE

=====
===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:MOVE TO FRESH AIR. EYES:ANY MATERIAL THAT CONTACTS THE EYE SHOULD BE WASHED OUT

IMMEDIATELY WITH WATER. SKIN:WASH WITH SOAP & WATER. ORAL:DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

=====
===== Fire Fighting Measures =====

Flash Point:NONE

Lower Limits:NOT RELEVANT

Upper Limits:NOT RELEVANT

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE (CO2), ALCOHOL FOAM OR DRY CHEMICAL. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED

SELF-CONTAINED BREATHING APPARATUS. HAZARDOUS DECOMPOSITION PRODUCTS MAY BE FORMED.

Unusual Fire/Explosion Hazard:MAY CAUSE DECOMPOSITION. DRIED MATERIAL CAN ACT AS AN OXIDIZER.

=====
===== Accidental Release Measures =====

Spill Release Procedures:FLUSH TO SEWER WITH LARGE AMOUNT OF WATER IF PERMITTED. OTHERWISE, ABSORB SPILL WITH INERT MATERIAL SUCH AS VERMICULITE. PLACE IN A CONTAINER FOR DISPOSAL. CLEAN AREA THOR

OUGHLY TO REMOVE RESIDUAL CONTAMINATION. PREVENT RUNOFF FROM ENTERING SEWERS.

Neutralizing Agent:NOT RELEVANT

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN TIGHTLY CLOSED CONTAINER, AWAY FROM INCOMPATIBLE MATERIALS.

Other Precautions:DO NOT GET IN EYES. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. KEEP OUT OF REACH OF CHILDREN.

=====
===== Exposure Controls/Personal Protection =====

Resp

iratory Protection:NONE SHOULD BE NEEDED.

Ventilation:GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES/HR)

SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS

Protective Gloves:RUBBER FOR PROLONGED/REPEATED CONTACT

Eye Protection:SAFETY GLASSES WITH SIDE SHIELD/GOGGLES

Other Protective Equipment:EYE BATH, SAFETY SHOWER, WASHING FACILITIES

Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES.

Supplemental Safety and Health

FORMULA AN

D/OR PERCENTAGE CHANGED. ECOLOGICAL INFORMATION:A LOW

BIOCHEMICAL OXYGEN DEMAND, A LOW POTENTIAL TO AFFECT AQUATIC

ORGANISMS. AFTER DILUTION WITH LARGE AMOUNT OF WATER, FOLLOWED BY

WASTE TREATMENT, IT IS NOT EXPECTED TO CAUSE ADVERSE ENVIRONMENTAL

EFFECTS.

===== Physical/Chemical Properties =====

HCC:C3

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:>212F,>100C

Decomp Temp:Decomp Text:>419F,>215C

Vapor Pres:18 @ 68F

Vapor Density:0.6

Spec Gravi

ty:1.17

pH:4

Solubility in Water:COMPLETE

Appearance and Odor:DARK GREEN LIQUID - ODORLESS

Percent Volatiles by Volume:60- 65

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

BASES, SODIUM HYPOCHLORITE (BLEACH), STRONG OXIDIZING AGENTS, STRONG
REDUCING AGENTS. BASE LIBERATES FLAMMABLE MATERIAL.

Stability Condition to Avoid:TEMPERATURES ABOVE 115C/239F

Hazardous Decomposition Products:HYDROGEN BROMIDE, AMMONIA, CHLORAMINE,
NI

TROGEN OXIDE, CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT
TO FEDERAL, STATE OR LOCAL REGULATIONS. FLUSH TO SEWER WITH LARGE
AMOUNT OF WATER, IF ALLOWED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.