View NSN Online: https://aerobasegroup.tw/nsn/6850-00-826-0981

Product ID:VP-31A PENETRANT MSDS Date:04/12/1995 FSC:6850 NIIN:00-826-0981 Kit Part:Y MSDS Number: CCJXY === Responsible Party === Company Name:MET-L-CHEK COMPANY Address:1639 EUCLID STREET **City:SANTA MONICA** State:CA ZIP:90404-3770 Country:US Info Phone Num:310-450-1111 Emergency Phone Num:310-450-1111 CA GE:98733 === Contractor Identification === Company Name:MET-L-CHEK COMPANY Address:1639 EUCLID ST Box:00000 **City:SANTA MONICA** State:CA ZIP:90404 Country:US Phone:310-450-1111/FAX 310452-4046 CAGE:98733 Ingred Name: HYDROTREATED MIDDLE PETROLEUM DISTILLATE CAS:64742-46-7

CAS:64742-46-7 RTECS #:JN9379645 Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3

R

outes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE CONTACT PRESUMED NONIRRITATING. SKIN CONTACT SLIGHTLY IRRITATING. INHALATION: VAPORS OR OIL MIST MAY CAUSE MILD IRRITATION OF RESPIRATORY TRACT. INGESTION: MAY RESULT IN VOMITING. ASPIRATION MUST BE AVOIDED. Effects of Overexposure:SKIN: IRRITATION. INGESTION: POSSIBLE VOMITING. Medical Cond Aggravated by Exposure:PREEXISTING SKIN AND RESP IRATORY DISORDERS.
======================================
First Aid:EYES/SKIN: FLUSH W/WATER WASH SKIN W/SOAP & WATER. INHALATION: MOVE TO FRESH AIR. PROVIDE OXYGEN IF BREATHING IS DIFFICULT. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.
======================================
Flash Point Method:PMCC Flash Point:188F,87C Lower Limits:NA Upper Limits:NA Extinguishing Media:USE WATER FOG, FOAM, DRY CHEMICAL, OR CO2 DO NOT USE DIRECT STREAM OF WATER. Fire Fighting Procedures:WILL NOT BURN UNLESS PREHEATED. DO NOT ENTER CONFINED FIRE SPACE W/O FULL BUNKER GEAR (POSITIVE PRESSURE NIOSH APPROVED SCBA). Unusual Fire/Explosion Hazard:NONE
======================================
Spill Release Procedures:SOAK UP WITH AN ABSORBENT SUCH AS (CLAY/SAND/OTHER SUITABLE MATERIAL). DISPOSE ACCORDING TO FEDERAL/STATE REGULATION FOR OIL RESIDUE.
======================================
Handling and Storage Precautions:KEEP AWAY FROM HEAT, OPEN FLAMES, OXIDIZING MATERIALS. Other Precautions:NONE
========= Exposure Controls/Personal Protection ====================================
Respiratory Protection: IF EXPOSURE EXCEEDS TLV USE NIOSH APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE.

Ventilation:LOCAL EXHAUST/MECHANICAL GENERAL TO MAINTAIN TLV. Protective Gloves:CHEMICAL RESISTANT.

Eye Protection:NO SPECIAL PROTECTION REQUIRED. Other Protect ive Equipment:AS REQUIRED TO MINIMIZE SKIN CONTACT.
 Work Hygienic Practices:MINIMIZE SKIN CONTACT, WASH W/SOAP & WATER BEFORE EATING, DRINKING, SMOKING USING TOILET.
 Supplemental Safety and Health NK

Boiling Pt:B.P. Text:>400F,>204C Melt/Freeze Pt:M.P/F.P Text:-75F,-59C Vapor Pres:NA Vapor Density:NA Spec Gravity: 0.86 Viscosity:NA Evaporation Rate & amp; Reference:NA Solubility in Water:INSOLUBLE Appearance and Odor:DEEP REDDISH PURPLE LIQUID WITH HYDROCARBON ODOR

Stability Indicator/Materials to Avoid:YES
OXIDIZING MATERIALS.
Stability Condition to Avoid:HEAT, OPEN FLAME, OXIDIZING MATERIALS.
Hazardous Decomposition Products:CAN PRODUCE CARBON MONOXIDE, OTHER UNIDENTIFED ORGANIC COMPOUNDS.
Conditions to Avoid Polymerization:HEAT, OPEN FLAMES, OXIDIZING MATERIAL.

Was

te Disposal Methods:PLACE IN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE W/LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to ver

ify and assume responsibility for the suitability of this information to their particular situation.