View NSN Online: https://aerobasegroup.tw/nsn/6350-00-611-7991

Product ID:DYMEL 22,MODEL MSR,SSC MSDS Date:07/01/1988 FSC:6350 NIIN:00-611-7991 MSDS Number: CDGGZ === Responsible Party === Company Name: EI DUPONT DE NEMOURS & CO, FREON PROD Address:1007 MARKET ST **City:WILMINGTON** State:DE ZIP:19899 Country:US Info Phone Num:800-441-9450 Emerg ency Phone Num:800-441-3637/800-424-9300(CHEMTREC) Preparer's Name:K. P. BROWN CAGE:5P414 === Contractor Identification === Company Name: EI DUPONT DE NEMOURS & CO, FREON PROD (REPLACED BY 73925) Address:1007 MARKET ST Box:City:WILMINGTON State:DE ZIP:19899 Country:US Phone:800-441-3637-MED 800-424-9300-TRAN CAGE:5P414 **Company Name: FALCON SAFETY PRODUCTS INC** Address:25 CHUBB WAY Box:1299 City:SOMMERVILLE State:NJ ZIP:08876 Country:US Phone:908-707-4900 CAGE:02670

======= Composition/Info

rmation on Ingredients ==========

Ingred Name: CHLORODIFLUOROMETHANE CAS:75-45-6 RTECS #:PA6390000 Fraction by Wt: 100% Other REC Limits:NONE SPECIFIED OSHA PEL:1000 PPM ACGIH TLV:1000PPM; 9192 **Ozone Depleting Chemical:2** LD50 LC50 Mixture:TLV 1000 PPM, 3500 MG/M3 Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE-INHALE:MAY CA USE SUFFOCATION, SHORTNESS OF BREATH, CONFUSION, NARCOSIS, CARDIAC IRREGULARITIES, UNCONSCIOUSNESS OR EVEN DEATH. EYES: CAN CAUSE SLIGHT **IRRITATION & CORNEAL INJURY.SKIN:PROLONGED/ REPEATE D CONTACT CAN** CAUSE DEFATTING.ORAL:LOW TOXICITY BUT HAS ASPIRATION HAZARD.GI & CNS EFFECTS.CHRONIC-MAY CAUSE DERMATITIS. Explanation of Carcinogenicity:NONE Effects of Overexposure: MAY CAUSE SUFFOCATION, SHORTNESS OF BREATH, CONFUSION, NARCOSIS, CARDIAC IRREGULARITIES, UNCONSCIOUSNESS OR Е VEN DEATH. CAN CAUSE SLIGHT EYE IRRITATION & CORNEAL INJURY. PROLONGED/REPEATED SKIN CONTAC T CAN CAUSE DEFATTING AND FROSTBITE. ORALLY HAS LOW TO MODERATE TOXICITY AND HAS ASPIRATION HAZARD, GI & CNS EFFECTS. Medical Cond Aggravated by Exposure: PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO THIS MATERIAL. First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. SKIN:WASH WITH SOAP & WATER.EYE:FLUSH WI TH WATER FOR 15 MINUTES.HOLDING EYELIDS OPEN.INHALED:REMOVE TO FRESH AIR & PROVIDE OXYGEN/CPR IF NEEDED. ORAL:DO NOT INDUCE VOMITING.IF CONSCIOUS, DRINK 2 GLASSES OF WATER & IMMEDIATELY SEEK MEDICAL ATTENTION.DO NOT TAKE ADRENALINE OR OTHER SIMILAR CARDIAC STIMULANTS TO TREAT EFFECTS OF OVEREXPOSURE TO THIS PRODUCT.

Flash Point Method:TOC Flash Point:NONE Extinguishing Media:WATER SPRAY, CO2, FOAM/DRY CHEM ICAL. WATER SPRAY

MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL & FLUSH SPILLS AWAY.

Fire Fighting Procedures: FULL PROTECTIVE CLOTHING & NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN POSITIVE PRESSURE MODE IF CONTENTS ARE RELEASED.

Unusual Fire/Explosion Hazard:OTHER BURNING MATERIAL MAY CAUSE DYMEL 22 TO BURN WEAKLY.CYLINDERS ARE EQUIPPED WITH PRESSURE AND TEMPERATURE RELIEF DEVICES BUT MAY RUPTURE IN FIRE CONDITIONS.

Spill Release Procedures: VENTILATE AREA WELL AND AVOID BREATHING VAPORS. VAPOR CONCENTRATION WILL BE HIGHEST ALONG FLOOR AND IN LOW LYING AREAS. PICK UP LIQUID ON SUITABLE ABSORBENT AND STORE IN SEALED CONTAINERS.

Handling and Storage Precautions:STORAGE-STORE IN COOL,WELL VENTILATED AREA AWAY FROM HEAT & FLAMES. Other Precautions:KEEP THIS AND ALL CHEMICA

LS OUT OF REACH OF CHILDREN.

THIS PRODUCT FOR INDUSTRIAL USE ONLY. DO NOT USE IN CLOSED SPACE. AVOID BREATHING VAPORS OR MISTS. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING.

Respiratory Protection:NON REQUIRED UNDER NORMAL CONDITIONS. IF HIGH VAPOR OR MIST CONCENTRATIONS EXPECTED, USE NIOSH-APPROVED RESPIRATOR FOR ORGANIC VAPORS AND MISTS. WEAR SUPPLIED-AIR RESPIRATOR PROTECTION IN CONFINED OR ENCLOSED S PACES, IF NEEDED.

Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:NEOPRENE OR PVA

Eye Protection: SPLASH-PROOF SAFETY GOGGLES OR GLASSES

Other Protective Equipment: EYE WASH STATION, QUICK DRENCH SHOWER AND IMPERVIOUS CLOTHING

Work Hygienic Practices: GOOD PERSONAL HYGIENE PRACTICES REQUIRE THAT GROSS AMOUNT OF ANY CHEMICAL BE REMOVED FROM THE SKIN AS SOON AS PRACTICAL.

Supplemental Safety and Health FALCON SAFET

Y PRODUCTS, INC. USES DUPONT CHLORODIFLUOROMETHANE FOR MIGHTY SONIC REFILL (MSR).

HCC:G3 Boiling Pt:B.P. Text:-41F,-41C Decomp Temp:Decomp Text:1170F,632C Vapor Pres:7810 @ 77F Vapor Density:3.03 @ 77F Spec Gravity:1.194 Evaporation Rate & Reference:>1 (CCL4=1) Solubility in Water:0.30% @ 77F Appearance and Odor:CLEAR COLORLESS LIQUEFIED GAS WITH SLIGHT ETHEREAL ODOR Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES
ALKALI OR REACTIVE ALKALINE EARTH METALS, POWDERED ALUMINUM, ZINC, BERYLLIUM, ETC..
Stability Condition to Avoid:HIGH HEAT AND OPEN FLAME
Hazardous Decomposition Products:HIGH TEMPERATURES(OPEN FLAMES,GLOWING METAL SURFACE)CAN FORM HYDROCHLORIC, HYDROFLUORIC ACIDS & POSSIBLY CARBONYL HALIDE

Waste Disposal Methods:MATER IAL MAY BE DISPOSED OF BY A LICENSED RECLAIMER OR INCINERATION FACILITY. CONSULT LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek compete nt professional advice to verify and assume responsibility for the suitability of this information to their particular situation.