

CRAWFORD LABORATORIES, INC. -- MIL-C-22750F, ACTIVATOR, PART B FOR SEMI & FLAT, UO-137
-- 8010-01-419-1152

===== Product Identification =====

Product ID:MIL-C-22750F, ACTIVATOR, PART B FOR SEMI & FLAT, UO-137

MSDS Date:03/07/1996

FSC:8010

NIIN:01-419-1152

Kit Part:Y

MSDS Number: CDHPD

=== Responsible Party ===

Company Name:CRAWFORD LABORATORIES, INC.

Address:4165 SOUTH EMERALD AVENUE

City:CHICAGO

State:IL

ZIP:60609

Country:US

Info Phone Num:312-376-7132

Emergency Phone Num:800-424-9300

Preparer's Name:DAVID SCHMETTERER

CAGE:DO165

=== Contractor Identification ===

Company Name:CRAWFORD LABORATIES, INC

Address:4165 SOUTH EMERALD AVENUE

City:CHICAGO

State:IL

ZIP:60609

Phone:800-424-9300 CHEMTREC

CAGE:DO165

Company Name:CRAWFORD LABORATORIES, INC

Address:4165 SOUTH EMERALD AVENUE

Box:City:CHICAGO

State:IL

ZIP:60609

Country:US

Phone:312-376-7132

CAGE:5V430

===== Composition/Informat

ion on Ingredients =====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III) (VP = 71.2 MMHG)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 48.0%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:NH₂CH₂CH(CH₃)(CH₂)₃NH₂ (VP=130.0 MMHG)
CAS:15520-10-2
RTECS #:SA0248500
Fraction by Wt: 14.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT EST.
ACGIH TLV:NOT EST.

Ingred Name:PHENYL CARBINOL (MAY CONTAIN AS IMPURITI
ES: 100-52-7
BENZALDEHYDE 0.3%, 103-50-4 DIBENZYL ETHER 0.1%, 150-76-5 0.025%
CAS:100-51-6
RTECS #:DN3150000
Fraction by Wt: 13.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:EPOXY RESIN
CAS:25085-99-8
Fraction by Wt: 5.7%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:REPEATED/PROLONGED OCC
UPATIONAL

OVEREXPOSURE TO SOLVENTS ASSOCIATED W/PERMANENT BRAIN/NERVOUS
SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND
INHALING THE CONTENTS MAY BE HARMFUL O R FATAL. PROLONGED
OVEREXPOSURE (INHAL)MAY CAUSE DELAYED LUNG DISEASE.
Explanation of Carcinogenicity:MAY CONTAIN TRACE AMTS OF SOME CHEM
KNOWN TO THE STATE OF CATO BE CARCINOGENS OR REPRODCTIVE TOXINS.
Effects of Overexposure:OVEREXPOSURE MAY PRODUCE VARIOUS EFFECTS. ACUTE
TOXICITY (HEADACHE, DI

ZZINESS, NAUSEA, LOSS CONSCIOUSNESS. SEVERE
EYE IRRITATION POSSIBLY RESULTING PERMANENT DAMAGE. IRRITATED
MUCOUS MEMBRANES. VOMITING FROM INGESTION. SKIN DEFATTING/DRYING.
SENSITIZATION AFTER REPEATED CONTACT.

===== First Aid Measures =====

First Aid:EYE: FLUSH W/PLENTY CLEAN H2O 15 MIN, LIFTING LIDS, GET MED
ATTN. INHAL: GET FRESH AIR, PROVIDE OXYGEN IF BREATH DIFFICULT.
GIVE ARTIF RESP IF NOT BREATHING. GET MED ATTN. KEEP VICTIM

WARM/QUIET. NEVER GIVE UNCONS PERSON LIQ. INGEST: CALL DR. IMMED.
DON'T INDUCE VOMIT. IF VOMIT SPONTANEOUSLY, KEEP HEAD BELOW HIPS.
SKIN: FLUSH W/H2O WHILE REMOVING CONTAM CLOTHES/SHOES. IF IRRIT
PERSIST, GET MED AID

===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:22.0F,-5.6C
Lower Limits:1.8
Extinguishing Media:FOAM, CO2, OR DRY CHEMICAL
Fire Fighting Procedures:WATER MAY BE USED TO KEEP EXPOSED CONTAINERS
COOL & KEEP FL
AMMABLE STRUCTURE WETDON'T ENTER FIRE AREA WITHOUT
PROPER PROTECTION, HAZARDOUS DECOMP MAY BE PRESENT
Unusual Fire/Explosion Hazard:WATER PRESSURE MAY SPREAD A FLAMMABLE
LIQUID FIRE. SEALED CONTAINERS MAY EXPLODE IF OVER HEATED.

===== Accidental Release Measures =====

Spill Release Procedures:WARNING - FLAMMABLE. ELIMINATE ALL IGNITION
SOURCES. HANDLING EQUIPMENT MUST BE GROUNDED TO PREVENT SPARKING.
SOAK UP WITHABSORBENT & PLACE IN NON-LEAKING CONAT
INERS. SEAL
TIGHTLY FOR PROPER DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:TREAT AS A HAZARDOUS-FLAMMABLE
MATERIAL. KNOW APPLICABLE D.O.T. REG. BEFORE ATTEMPTING TO
TRANSPORT THIS MATERIAL.
Other Precautions:WARNING: HOT ORGANIC CHEMICAL VAPORS OR MISTS ARE
SUSCEPTIBLE TO SUDDEN SPONTANEOUS COMBUSTION WHEN MIXED W/AIR.
IGNITION MAY OCCUR @ TEMPS BELOW THOSE PUBLISHED AS
AUTOIGNITION/IGNITION TEMPS. IGNIT

ION TEMPS DECREASE W/INCREASING
VAPOR*

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IMPORTANT-MUST PROVIDE ADEQUATE VENT TO MAINTAIN
VAPOR CONCENTRATE BELOW ESTAB- LISHED TLV LIMIT AS GIVEN BY OSHA.
IN MORE CONFINED AREAS A NIOSH/MSHA APPROVED RESPIRATOR EQUIPPED
WITH ORGANIC VAPOR CARTRIDGE SHOULD BE WORN.

Ventilation:MUST PROVIDE ADEQUATE VENTILATION, SEE PARAGRAPH ABOVE.

Protective Gloves:USE RUBBER GLOVES

Eye Protection:APPROV
ED SAFETY GOGGLES &/OR FACE SHIELD

Other Protective Equipment:HAVE EYE BATH & SAFETY SHOWER AVAILABLE.

Supplemental Safety and Health

VOLUME AND VAPOR/AIR CONTACT TIME AND ARE INFLUENCED BY PRESSURE
CHANGES. IGNITION MAY OCCUR AT TYPICAL ELEVATED TEMPERATURE PROCESS
CONDITIONS, ESPECIALLY IN PROCESS OPERATING UNDER VACUUM IF SUBJECT
ED TO SUDDEN INGRESS OF AIR, OUTSIDE PROCESS EQUIPMENT OPERATING
UNDER ELEVATED PRESSURE IF SUDDEN ESCAPE OF VAPORS/MIST

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:175 TO 401F

Vapor Density:>AIR

Spec Gravity:1.06

Viscosity:70 KU

Evaporation Rate & Reference:3.77 X N-BUTYL ACETATE

Solubility in Water:SLIGHT

Appearance and Odor:CLEAR LIQUID

Percent Volatiles by Volume:80.9

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING AGENTS & STRONG ALKALIES. NOT CORROSIVE TO METAL.

Stability Condition to Avoid:HEAT, SPARKS, OPEN F

LAMES, STRONG

ALKALIES, & OXIDIZING AGENTS.

Hazardous Decomposition Products:INCOMPLETE COMBUSTION OR PRODUCTS LIKE
THIS MAY GENERATE HIGHLY POISONOUS CARBON MONOXIDE AND OTHER TOXIC
GASES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE IN ACCORDANCE WITH CURRENT
LOCAL, STATE & FEDERAL REG. CONTACT AN APPROVED DISPOSAL FACILITY

Disclaimer (provided with this information by the compiling agencies):
This information i

s formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.