

EPOXYLITE CORP -- EPOXYLITE #5526, PART B -- 8040-01-332-8875

=====
Product Identification
=====

Product ID:EPOXYLITE #5526, PART B

MSDS Date:11/14/1986

FSC:8040

NIIN:01-332-8875

Kit Part:Y

MSDS Number: CDXWG

=== Responsible Party ===

Company Name:EPOXYLITE CORP

Address:9400 TOLEDO WAY

Box:19671

City:IRVINE

State:CA

ZIP:92713

Country:US

Info Phone Num:714-951-3231 / FAX 714-472-0980

Emergency Pho

ne Num:714-951-3231

CAGE:11147

=== Contractor Identification ===

Company Name:THE EPOXYLITE CORPORATION

Address:9400 TOLEDO WAY

Box:19671

City:IRVINE

State:CA

ZIP:92713-9671

Country:US

Phone:714-951-3231

CAGE:11147

=====
Composition/Information on Ingredients
=====

Ingred Name:4,4-CARBONYLDIPHTHALIC ANHYDRIDE

CAS:2421-28-5

Fraction by Wt: 55-30%

Other REC Limits:0.25 MG/M3

Ingred Name:ALUMINUM (SARA 313)

CAS:7429-90-5

RTECS #:BD0330000

Fraction by Wt: 40-45%

Other REC Limits

:NONE RECOMMENDED
OSHA PEL:5 MG/M3 DUST
ACGIH TLV:5 MG/M3 DUST

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE: IRRITATION W/TEARING. SKIN: MINOR
IRRITATION, ALLERGIC SENSITIVITY. INGEST: IRRITATION, CORROSIVE
ACTION IN MOUTH, STOMACH TISSUE, VOMITING. INHAL: BREATHLESSNESS,
SEVERE COUGHING, CHEST PAIN, IRRITATION T
O MUCOUS MEMBRANE,
REDUCED PULMONARY FUNCTION, SENSITIVITY, (ASTHMA-LIKE SYMPTOMS ON
SUBSEQUENT EXPOSURES 15 MINUTES, CALL DR IMMED.
SKIN: WASH W/SOAP & WATER. ALCOHOL MAY BE HELPFUL. CALL DR. INGEST:
DRINK WARM WATER & INDUCE VOMIT BY TOUCHING BACK OF THROAT W/FINGER
&/OR SYRUP OF EPIKAK. GIVE MILK & MILD CATHARTIC, (MILK OF
MAGNESIA). CALL DR/POISON CONTROL IMMED. INHAL: GET FRESH AIR. IF
BREATH DIFF GIVE OXY, CALL DR IMMED. NEVER GIVE ANYTHING TO
UNCONSCIOUS P
ERSON.

===== Fire Fighting Measures =====

Flash Point:NA
Lower Limits:NE
Upper Limits:NE
Extinguishing Media:WATER FOG, FOAM, ALCOHOL FOAM, CARBON DIOXIDE, OR
DRY CHEMICAL.
Fire Fighting Procedures:USE SCBA W/TURNOUT CLOTHING. USE WATER TO COOL
FIRE EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:AVOID WATER CONTAMINATION IN CLOSED
CONTAINER OR CONFINED AREA, (EXOTHERMIC REACTION).

===== Accidental Release Measures =====

===

Spill Release Procedures:EVAC AREA. CONTAIN SPILL. COVER W/ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS SEALED OR TIGHTLY
CLOSED WHEN NOT IN USE TO AVOID ATMOSPHERE CONTAMINATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED RESPIRATOR W/ACID/GAS FILTER
RECOMMENDED.
Ventilation:GOOD ROOM VENTILATION IS USUALLY ADEQUATE FOR MOST
OPERA

TIONS.

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection:CHEMICAL GOGGLES.

Other Protective Equipment:CLEAN BODY COVERING CLOTHING.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:135F,57C

Vapor Pres:NA

Vapor Density:NA

Spec Gravity:2.0

Evaporation Rate & Reference:NA

Solubility in Water:REACTS W/WATER.

Appearance and Odor:WHITE TO TAN COLORED POWDER.

Percent Volatiles by Volume:NIL

===== Stability
and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER, STRONG ALKALIES, ALCOHOLS, METAL COMPOUNDS, OR SURFACE ACTIVE
AGENTS.

Stability Condition to Avoid:HEAT >168F OR STORAGE