

DIGITAL EQUIPMENT CORP -- EPOXY RESIN PART B (AMBER) P/N H8102-AA -- 6080-01-391-1252

===== Product Identification =====

Product ID:EPOXY RESIN PART B (AMBER) P/N H8102-AA

MSDS Date:07/11/1995

FSC:6080

NIIN:01-391-1252

MSDS Number: CFFKS

=== Responsible Party ===

Company Name:DIGITAL EQUIPMENT CORP

Address:146 MAIN ST

City:MAYNARD

State:MA

ZIP:01754-2504

Country:US

Info Phone Num:508-493-5111 / FA

X 508-493-8780

Emergency Phone Num:800-228-5635 EXT 123

CAGE:15476

=== Contractor Identification ===

Company Name:COMPAQ/ FORMERLY KNOWN AS-DIGITAL EQUIPMENT CORP

Address:111 POWDERMILL RD

Box:City:MAYNARD

State:MA

ZIP:01754-2504

Country:US

Phone:508-479-3046

CAGE:15476

Company Name:DIGITAL EQUIPMENT CORP (800-228-5635)

Box:UNKNOWN

CAGE:06VJ6

Company Name:MABCON INTL (310-316-1831)

Box:UNKNOWN

CAGE:05SX8

===== Composition/Information on Ingredients =====

Ingred Name:SILICA GEL

CAS:112945-52-5
RTECS #:VV7310000
Fraction by Wt: 3%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:6 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:TRIETHYLENE TETRAMINE
CAS:112-24-3
RTECS #:YE6650000
Fraction by Wt: 19%
Other REC Limits:NONE RECOMMENDED

Ingred Name:POLYAMIDE RESIN (REACTIVE POLYAMIDE)
CAS:37189-83-6
Fraction by Wt: 78%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Ca
rcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN & EYE CORROSION. REPEAT EXPOSURE
MAY CAUSE DERMAL SENSITIZATION.
Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1%
OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.
Effects of Overexposure:SKIN-SENSITIZATION, CORROSION. EYES-CORROSION.
NONE GIVEN FOR INHALATION & INGESTION.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid
Measures =====

First Aid:EYES-FLUSH WITH LOTS OF WATER FOR 15 MINUTES. CONTACT A
PHYSICIAN. SKIN-PROMPTLY WASH WITH MILD SOAP & WATER. SEE A
PHYSICIAN IF SYMPTOMS PERSIST. INHALED-NOT APPLICABLE.
INGESTED-SEEK IMMEDIATE MEDIC AL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:264F,129C
Extinguishing Media:HALON, WATER SPRAY/FOG, CARBON DIOXIDE, DRY
CHEMICAL, FOAM.
Fire Fighting Procedures:WEAR SELF-CONTAINED BRE

ATHING APPARATUS AND

FULL FIRE FIGHTER'S PROTECTIVE GEAR WHEN FIGHTING FIRES IN CONFINED AREAS.

Unusual Fire/Explosion Hazard:DENSE SMOKE AND TOXIC GASES MAY BE PRODUCED UPON COMBUSTION.

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP & TRANSFER TO METAL CONTAINER FOR DISPOSAL. USE RAG OR PAPER TOWEL & DETERGENT TO CLEAN RESIDUE.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage

=====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE. DO NOT MIX BATCHES OF GREATER THAN 1 POUND TOTAL. FOLLOW RECOMMENDED CURING PROCEDURES.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SPECIFIED BY MANUFACTURER.

Ventilation:NONE NORMALLY REQUIRED.

Protective Gloves:NONE SPECIFIED BY MANUFACTURER.

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES.

O

ther Protective Equipment:NONE SPECIFIED BY MANUFACTURER. DLA-HMIS: EYE WASH STATION.

Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

KEY1=C2. PART B OF TWO PART KIT. SEE PNI A FOR PART A.

===== Physical/Chemical Properties =====

HCC:B2

Boiling Pt:B.P. Text:531F,277C

Vapor Pres:1

Spec Gravity:0.98

Evaporation Rate & Reference: