

NEW PIG CORP -- PIG REPAIR PUTTY, TPY201

=====
MSDS Safety Information
=====

FSC: 8030
NIIN: 01-436-8318
MSDS Date: 09/05/1995
MSDS Num: CFRBR
Product ID: PIG REPAIR PUTTY, TPY201
MFN: 01
Responsible Party
Cage: 1JA49
Name: NEW PIG CORP
Address: ONE PORK AVE
City: TIPTON PA 16684-0304
Info Phon
e Number: 800-684-0101
Emergency Phone Number: 800-468-4647
Preparer's Name: CAMERON W SHERRY
Proprietary Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: 1JA49
Name: NEW PIG CORPORATION
Address: ONE PORK AVENUE
City: TIPTON PA 16684-0304
Phone: 800-468-4647

=====
Item Description Information
=====

=====
Item Manager: N35
Item Name: CALKING COMPOUND
Unit of Issue: BX
Quantitative Expression: 00000000012EA
UI Container Qty: 1

=====
Ingredients
=====

Name: *** PROPRIETARY ***

=====
Health Hazards Data
=====

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.
R

oute Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: YES

IARC: YES

OSHA: NO

Effects of Exposure: ACUTE: EYES: MAY CAUSE IRRIT & ACT AS SENSITIZER.

INGESTION: MAY CAUSE IRRIT OF INTESTINAL TRACT. INHAL: MAY CAUSE RESPIRATORY DISCOMFORT IN EXCESSIVE CONCENTRATIONS. SKIN: MAY CAUSE IRRIT & ACT AS SENSITIZER. CHRONIC: PROLONGED/REPEATED EXPOSURE TO RESPIRABLE CRYSTALLINE SILICA DUST MAY CAUSE SEVERE SCARRING OF LUNGS.

Explanation Of Carcinogenicity

ty: USERS OF THE "L" VERSION OF SHOULD CONSULT "LR" VERSION (INGREDIENT 7) FOR ADDITIONAL INFORMATION (FP N).

Signs And Symptoms Of Overexposure: SEE HEALTH HAZARDS.

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. CONSULT MD.

INGESTION: INDUCE VOMITING AS DIRECTED BY MEDICAL PERSONNEL. INHALATION: REMOVE TO FRESH AIR. SKIN: WASH WITH SOAP AND WATER.

=====
Hand
ling and Disposal

=====
Spill Release Procedures: SHOVEL OR SWEEP UP MATERIAL AND PLACE INTO A PLASTIC OR METAL DISPOSAL CONTAINER. NOT A LISTED HAZARDOUS WASTE.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: INCINERATE IN FURNACE OR BURY IN LANDFILL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Handling And Storage Precautions: BEST STORAGE CONDITIONS ARE AT ROOM TEMPERATURE, HOWEVER, FREEZING, HUMIDITY, AND HIGH TEMPERATURES WILL NOT AFFECT PERFORMANCE OF UNUSED PUTTY.

Other Precautions: IF FROZEN, WARM FOR A FEW MINUTES FIRST FOR EASIER MIXING. AVOID EYE CONTACT AND EXCESSIVE SKIN CONTACT. SHELF LIFE: SEVERAL YEARS IN ORIGINAL TUBE WITH CAP ON.

=====
Fire and Explosion Hazard Information

=====
Extinguishing Media: WATER SPRAY, FOAM, CARBON DIOXIDE, DRY CHEMICALS.

Fire Fighting Proce

dures: NONE REQUIRED. WEAR NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT (FP N).
Unusual Fire/Explosion Hazard: CARBON MONOXIDE, ALDEHYDES, ACIDS, OXIDES OF SULFUR AND NITROGEN MAY BE FORMED.

=====
Control Measures
=====

Respiratory Protection: FOR PROLONGED EXPOSURE TO SANDING DUST, WEAR NIOSH APPROVED HALF FACE RESPIRATOR WITH DUST FILTERS.
Ventilation: GENERAL VENTILATION: NONE REQUIRED. LOCAL EXHAUST: ONLY IF HEATED ABOVE 100F (38C)/DURING PROLONGED SANDING OPERATIONS.
Protective Gloves: POLYETHYLENE GLOVES FOR PROLONGED USE.
Eye Protection: ANSI APPRVD CHEM WORKERS GOGGLES (FP N).
Other Protective Equipment: EMERGENCY EYEWASH AND DELUGE SHOWER MEETING ANSI DESIGN CRITERIA (FP N).
Work Hygienic Practices: WASH WITH SOAP AND WATER IMMEDIATELY AFTER USE.
Supplemental Safety and Health: USERS OF THE "L" VERSION OF SHOULD CONSULT "LR" VERSION FOR ADDITIONAL INFORMATION (FP N).

=====
Physical/Chemical Properties
=====

Vapor Pres: NONE
Vapor Density: NON VOLAT
Spec Gravity: 1.9
Evaporation Rate & Reference: 0.0 X N-BUTYL ACETATE
Solubility in Water: INSOLUBLE
Appearance and Odor: PUTTY, GREY COLOR AFTER CURE, MILD SULFIDE ODOR

=====
Reactivity Data
=====

Stability Indicator: YES
Stability Condition To Avoid: NONE SPECIFIED BY MANUFACTURER.
Materials To Avoid: AVOID INCOMPATIBLE MATERIALS. FOR COMPATIBILITY GUIDE, CALL 1-800-468-4647.
Hazardous Decomposition Products: CARBON MONOXIDE, ALDEHYDES, ACIDS, OXIDES OF SULFUR AND NITROGEN.
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NOT RELEVANT.

=====
Toxicological Information
=====

=====

=====

Ecological Information

=====

=====

MSDS Transport Information

=====

=====

Regulatory Information

=====

=====

Other Information

=

=====

=====

Transportation Information

=====

Responsible Party Cage: 1JA49

Trans ID NO: 136732

Product ID: PIG REPAIR PUTTY, TPY201

MSDS Prepared Date: 09/05/1995

Review Date: 12/16/1997

MFN: 1

Multiple KIT Number: 0

Review IND: Y

Unit Of Issue: BX

Container QTY: 1

=====

Detail DOT Information

=====

=====

DOT PSN Code: ZZZ

DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====

Detail IMO Information

=====

IMO PSN Code: ZZZ

IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

=====

Detail IATA Information

=====

===

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====

Detail AFI Information

=====

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====

HAZCOM Label

=====

Product ID: PIG REPAIR PUTTY, TPY201

Cage: 1JA49

Compa

ny Name: NEW PIG CORPORATION

Street: ONE PORK AVENUE

City: TIPTON PA

Zipcode: 16684-0304

Health Emergency Phone: 800-468-4647

Label Required IND: Y

Date Of Label Review: 09/25/1997

Status Code: C

Label Date: 09/25/1997

Origination Code: G

Chronic Hazard IND: Y

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: WARNING

Respiratory Protection IND: YES

Health Hazard: Moderate

Contact Hazard: Moderate

Fire Hazard: None

Reactivity Hazard: None

Hazard And Precautions: ACUTE: EYES: MAY CAUSE

IRRITATION AND ACT AS A

SENSITIZER. INGESTION: MAY CAUSE IRRITATION OF INTESTINAL TRACT. INHALATION: MAY CAUSE RESPIRATORY DISCOMFORT IN EXCESSIVE CONCENTRATIONS. SKIN: MAY CAUSE IRRITATION AND ACT AS A SENSITIZER. CHRONIC: CANCER HAZARD. CONTAINS MATERIAL LISTED AS A HUMAN LUNG CARCINOGEN (FP N). PROLONGED OR REPEATED EXPOSURE TO RESPIRABLE CRYSTALLINE SILICA DUST MAY CAUSE SEVERE SCARRING OF LUNGS. SENSITIZATION OF SKIN AND EYES.

=====

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.