

DEL PAINT CORP. -- TT-E-529G GRAY #26622 -- 8010-01-065-7090

===== Product Identification =====

Product ID:TT-E-529G GRAY #26622

MSDS Date:08/05/1997

FSC:8010

NIIN:01-065-7090

MSDS Number: CFXBC

=== Responsible Party ===

Company Name:DEL PAINT CORP.

Address:3105 E. RENO

City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Info Phone Num:405-672-1431/FAX 405-672-0804

Emergency Phone Num:800-424-9300 24

HRS

Preparer's Name:ONEY FLEMING

CAGE:JO954

=== Contractor Identification ===

Company Name:DEL PAINT CORP.

Address:3105 E. RENO

City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431/FAX 405-672-0804

CAGE:JO954

Company Name:DEL PAINT MFG

Address:3105 EAST RENO

Box:City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431

CAGE:39934

===== Composition/Information on Ingredients =====

Ingred Name:MEDIUM ALIPHATIC SOLVENT NAPHTHA

CAS:64742-88-7

Fraction by

Wt: 32.8%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:NON-HAZARDOUS INGREDIENTS  
Fraction by Wt: 67.2%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT RELEVANT  
ACGIH TLV:NOT RELEVANT

Ingred Name:VOC = 3.04 LBS/GL  
RTECS #:9999999VO  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT RELEVANT  
ACGIH TLV:NOT RELEVANT

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health

Hazards Acute and Chronic:EYE: REDNESS, PAIN. SKIN: REDNESS.  
INHAL: LABORED BREATHING, DULLNESS, DROWSINESS. INGEST: ABDOMINAL  
PAIN, NAUSEA. CHRONIC: EYE: IRRITATION, REDNESS, TEARING, BLURRED  
VISION. SKIN: IRRITATION, DEFATTI NG, DERMATITIS. INHAL:  
NASAL/RESPIRATORY IRRIT, DIZZINESS, NAUSEA, HEADACHE. INGEST: GI  
IRRITATION, NAUSEA, VOMITING.

Medical Cond Aggravated by Exposure:RESPIRATORY SYSTEM DISEASES.

===== First Aid Measures =====

First Aid:EYE: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINUTES, LIFT  
LIDS, GET MED AID. SKIN: REMOVE CONTAM CLOTHES, WASH BEFORE REUSE.  
WASH SKIN W/SOAP & WATER. INHAL: REMOVE TO FRESH AIR. GIVE OXYGEN  
IF NEEDED. GET MED AID. INGEST: KEEP WARM/QUIET. GET MED AID. DONT  
INDUCE VOMIT.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:100F,38C  
Autoignition Temp:Autoignition Temp Text:540F  
Lower Limits:1.0  
Upper Limits:6.0  
Exting

uishing Media:CO2, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:USE SCBA & FULL PROTECTIVE GEAR. USE WATER  
SPRAY TO COOL CONTAINERS. (PREVENT PRESSURE  
BUILDUP/AUTOIGNITION/EXPLOSION).

Unusual Fire/Explosion Hazard:WATER MAY SPREAD FIRE. VAPORS >AIR, MAY  
TRAVEL TO IGNITION SOURCE & FLASH BACK.

===== Accidental Release Measures =====

Spill Release Procedures:VENT AREA. COVER W/INERT ABSORBENT. SHOVEL  
W/NONSPARKING TOOLS INTO CONTAINER. REMOVE TO SAFE A  
REA & SEAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN CLEAN, DRY AREA. KEEP AWAY  
FROM IGNITION SOURCES.

Other Precautions:KEEP CONTAINER TIGHTLY CLOSED. KEEP AWAY FROM  
CHILDREN. GROUND EQUIPMENT TO REDUCE STATIC ELECTRICITY HAZARD. USE  
NONSPARKING TOOLS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE A RESPIRATOR W/APPROPRIATE CARTRIDGES (NIOSH  
APPROVED).

Ventil  
ation:LOCAL EXHAUST.  
Protective Gloves:CHEMICAL RESISTANT.  
Eye Protection:SAFETY GLASSES W/SIDE SHIELDS.  
Other Protective Equipment:EYEWASH STATION, SAFETY SHOWER & IMPERVIOUS  
CLOTHING.

Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:305 TO 396F  
Melt/Freeze Pt:M.P/F.P Text:NA  
Decomp Temp:Decomp Text:752F,400C  
Vapor Pres:2.58  
Vapor Density:>AIR  
Spec Gravity:1.11  
pH:NA  
Viscosity:65-72 KU  
Evaporation Rate & Refere

nce: