

DEL PAINT CORP. -- TT-E-2784 LIGHT BROWN #20400 -- 8010-01-396-6763

===== Product Identification =====

Product ID:TT-E-2784 LIGHT BROWN #20400

MSDS Date:06/14/1995

FSC:8010

NIIN:01-396-6763

MSDS Number: CFXLS

=== Responsible Party ===

Company Name:DEL PAINT CORP.

Address:3105 E. RENO

City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Info Phone Num:405-672-1431/FAX 405-672-0804

Emergency Phone Num:8

00-424-9300 24 HRS

Preparer's Name:ONEY FLEMING

CAGE:JO954

=== Contractor Identification ===

Company Name:DEL PAINT CORP.

Address:3105 E. RENO

City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431/FAX 405-672-0804

CAGE:JO954

Company Name:DEL PAINT MFG

Address:3105 EAST RENO

Box:City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431

CAGE:39934

===== Composition/Information on Ingredients =====

Ingred Name:PROPYLENE GLYCOL

CAS:57-55-6

RTECS #:TY200000

0
Fraction by Wt: 6.25%
Other REC Limits:NONE RECOMMENDED

Ingred Name:2,2,4-TRIMETHYL-1-3,3,-PENTANEDIOL MONOISOBUTYRATE
CAS:25265-77-4
RTECS #:UF6000000
Fraction by Wt: 4.86%
Other REC Limits:NONE RECOMMENDED

Ingred Name:DIMETHYLAMINOETHANOL
CAS:108-01-0
RTECS #:KK6125000
Fraction by Wt: 0.38%
Other REC Limits:NONE RECOMMENDED

Ingred Name:2-N-OCTYL-4-ISOTHIAZOLIN-3-ONE
CAS:26530-20-1
Fraction by Wt: 0.18%
Other REC Limits:NONE RECOMMENDED

Ingred Name:NON-HAZARDOUS INGREDIENTS
Fraction by Wt
: 88.33%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

Ingred Name:VOC = 1.7 LBS/GL
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHAL: HEADACHE, NAUSEA, IRRITATION.
EYE: IRRITATION. SKIN: IRRITAT

ION.
Medical Cond Aggravated by Exposure:LUNG DISEASE.

===== First Aid Measures =====

First Aid:EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINUTES, CALL DR.
SKIN: WASH THOROUGHLY W/SOAP & WATER. INGEST: GIVE 2 GLASSES OF
WATER TO DRINK. CALL DR.

===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:>212F,>100C
Autoignition Temp:Autoignition Temp Text:216F
Lower Limits:NONE
Upper Limits:NA
Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL & WATER FOG.
Fire Fighting Procedures:WEAR SCBA & FULL PROTECTIVE GEAR.
Unusual Fire/Explosion Hazard:MATERIAL MAY SPLATTER ABOVE 212F. POLYMER
FILM MAY BURN.

===== Accidental Release Measures =====

Spill Release Procedures:EVAC AREA. FLOOR MAY BE SLIPPERY. CONTAIN
SPILL W/INERT MATERIAL. TRANSFER LIQUID/ABSORBENT TO SEPARATE
SUITABLE CONTAINER FOR RECOVERY/DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM FREEZING.
Other Precautions:KEEP AWAY FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:MECHANICAL FILTER RESPIRATOR.
Ventilation:NORMAL (FAN).
Protective Gloves:RUBBER.
Eye Protection:SAFETY GLASSES OR GOGGLES.
Other Protective Equipment:EYEWASH STATION.
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boili

ng Pt:B.P. Text:212 TO 644F
Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C
Decomp Temp:Decomp Text:350F,177C
Vapor Pres:NONE
Vapor Density:>AIR
Spec Gravity:1.01
pH: