

ACCTECH LLC, CLEANTEX DIV -- TEXPAD,TX-801 -- 7045-01-115-7444

=====
Product Identification
=====

Product ID:TEXPAD,TX-801
MSDS Date:06/01/1997
FSC:7045
NIIN:01-115-7444
MSDS Number: CFYFT
=== Responsible Party ===
Company Name:ACCTECH LLC, CLEANTEX DIV
Address:33 MURRY HILL DRIVE
City:NANUET
State:NY
ZIP:10954
Country:US
Info Phone Num:800-284-5577
Emergency Phone Num:800-284-5577
Chemtec Ind/Ph
one:(800)424-9300
CAGE:09ZF6
=== Contractor Identification ===
Company Name:ACCTECH LLC
Address:33 MURRY HILL DRIVE
Box:City:NANUET
State:NY
ZIP:10954
Country:US
Phone:800-284-5577
CAGE:09ZF6
Company Name:NINETECH INTL INC
Address:1064 ROSELLE PL
Box:City:WOODMERE
State:NY
ZIP:11598
Country:US
Phone:516-887-7943
CAGE:0GKF8

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPROPYL ALCOHOL (SARA 313)
CAS:67-63-0
RTECS #:NT8050000
= Wt:91.
Other REC Limits:NONE R

ECOMMENDED
OSHA PEL:400 PPM
ACGIH TLV:400 PPM/500STEL;9596

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
= Wt:9.

Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS UNKNOWN.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, CNS,
RESPIRATOR
Y & GI TRACTS. ACUTE- EYE CONTACT WILL CAUSE LOCAL
IRRITATION & BURNING SENSATION WITH POSSIBLE INJURY IF NOT REMOVED
PROMPTLY. REPEATED OR PROLONGED CONTACT WITH THE SKIN MAY PRODUCE
IRRITATION & CAUSE DERMATITIS. EXPOSURE ABOVE THE TLV MAY CAUSE
IRRITATION IF THE RESPIRATORY TRACT AND EYES ALONG WITH HEADACHE,
DIZZINESS & CNS EFFECTS. MAY BE HARMFUL IF SWALLOWED.
Explanation of Carcinogenicity:NOT LISTED.
Effects of Overexposure:EYES:LOCAL IRRITATION, BURNING SENSATION.

SKIN:IRRITATION, DERMATITIS. INHALED:RESPIRATORY IRRITATION,
HEADACHE, DIZZINESS, CNS EFFECTS. INGESTED: HARMFUL.
Medical Cond Aggravated by Exposure:NOT LISTED.

===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:MOVE TO FRESH
AIR. RESTORE RESPIRATION/BREATHING. EYES:IMMEDIATELY FLUSH WITH
WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:FLUSH WITH WATER.
ORAL:IN THE UNLIKELY EVENT OF INGESTION OF A
WIPER, IF CONSCIOUS,
REMOVE THE OBJECT TO PREVENT CHOKING. ONCE REMOVED, KEEP AFFECTED
PERSON AT REST. CALL PHYSICIAN IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:=13.3C, 56.F
Extinguishing Media:USE CARBON DIOXIDE, "ALCOHOL" FOAM, OR DRY
CHEMICAL. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.
Fire Fighting Procedures:DO NOT ENTER ANY ENCLOSED OR CONFINED AREA
WITHOUT PROPER PROTECTIVE EQUIPMENT AND NIOSH-

APPROVED

SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:ISOPROPYL ALCOHOL MAY RELEASE VAPORS WHICH MAY IGNITE AT OR ABOVE THE FLASH POINT. FORMULATION IS CLASSIFIED AS AN OSHA CLASS IB FLAMMABLE LIQUID.

===== Accidental Release Measures =====

Spill Release Procedures:ISOPROPYL ALCOHOL IS ABSORBED BY APPLICATOR AND THE AMOUNT IS SMALL. IF A SIGNIFICANT AMOUNT OF LIQUID IS RELEASED, CLEAN-UP PERSONNEL SHOULD WEAR PROTECTIION FROM LIQUID CONTACT & VAPOR INHALATION. E LIMINATE SOURCES OF IGNITION. VENTILATEAREA. PICK UP SPILL WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, VENTILATED AREA AWAY FROM SOURCES OF IGNITION AND OXIDIZERS. HANDLE & STORE IN A MANNER SUITABLE FOR AN OSHA CLASS IB FLAMMABLE LIQUID. ELECTRICAL SERVICES MUST MEET APPLICABLE CO DES. USE NON-SPARKING TOOLS.

Other Precautions:PROVIDE VENTILATION TO MAINTAIN TLV. USE NON-SPARKING TOOLS. AVOID INHALATION OF VAPORS, CONTACT WITH EYES AND REPEATED OR PROLONGED CONTACT WITH SKIN. DO NOT TAKE INTERNALLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SPECIFIED BY MANUFACTURER. DLA-HMIS: IF TLV IS EXCEEDED OR FOR SYMPTOMS OF OVER EXPOSURE, WEAR NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR OR SUPPLIED AIR RESPIRATOR.

Ventilation:PROVIDE MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:RUBBER, NEOPRENE FOR REPEATED CONTACT.

Eye Protection:PREVENT CONTACT WITH EYES. WEAR SAFETY GLASSES/GOGGLES.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER. DLA-HMIS: EYE BATH, WASH FACILITIES

Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT TAKE INTERNALLY.

Su

pplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:F3
NRC/State Lic Num:NOT RELEVANT
Boiling Pt:=82.2C, 180.F
Vapor Pres:33 @ 77F
Vapor Density:1 (N-BUTYL ACETATE=1)
Solubility in Water:COMPLETE (100%)
Appearance and Odor:CLEAR LIQUID (ABSORBED IN PADS) - ALCOHOL ODOR
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, CHLORINATED COMPOUNDS, CAUSTICS, AMINES,
ALKANOLAMINES, ALDEHYDES, AMMONIA.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. DLA-HMIS:
HIGH HEAT, SPARKS, OPEN FLAMES AND OTHER SOURCES OF IGNITION.
Hazardous Decomposition Products:CARBON MONOXIDE.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Toxicological Information =====

Toxicological Information:NOT AVAILABLE.

===== Ecological Information
=====

Ecological:NOT AVAILABLE.

===== Disposal Considerations =====

Waste Disposal Methods:FOLLOW FEDERAL, STATE AND LOCAL REGULATIONS.

===== MSDS Transport Information =====

Transport Information:NOT REGULATED: DOT/IMDG/ICAO.

===== Regulatory Information =====

SARA Title III Information:SARA TITLE III REPORTING: SECTION 313-NONE
LISTED; EHS-NONE LISTED; 302/304/311/312: AC

UTE-YES, CHRONIC-YES,
FIRE-YES, PRESSURE-NO, REACTIVITY-NO.

Federal Regulatory Information:TSCA: ALL COMPONENTS ARE LISTED IN THE
TSCA INVENTORY.

State Regulatory Information:NONE SPECIFIED BY MANUFACTURER.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.