

CANTOL,INC. -- BELIEVE! -- 6850-01-440-1497

===== Product Identification =====

Product ID:BELIEVE!

MSDS Date:09/20/1996

FSC:6850

NIIN:01-440-1497

MSDS Number: CFYJM

=== Responsible Party ===

Company Name:CANTOL,INC.

Address:2211 NORTH AMERICAN STREET

City:PHILADELPHIA

State:PA

ZIP:19133

Country:US

Info Phone Num:215-425-1966

Emergency Phone Num:215-425-1911/800-424-9300(CHEMTREC)

Preparer's Name:R

ICHARD J. PETSCH

Chemtrec Ind/Phone:(800)424-9300

CAGE:58380

=== Contractor Identification ===

Company Name:CANTOL,INC.

Address:2211 NORTH AMERICAN STREET

Box:City:PHILADELPHIA

State:PA

ZIP:19133-3306

Country:US

Phone:215-425-1966

Contract Num:SP0414-01-M-1446

CAGE:58380

===== Composition/Information on Ingredients =====

Ingred Name:ETHYLENE GLYCOL PHENYL ETHER

CAS:122-99-6

RTECS #:KM0350000

Minumum % Wt:10.

Maxumum % Wt:15.

Other REC Limits:25 PPM (SKIN)

OSHA PEL:NONE

ACGIH

TLV:NONE

Ingred Name:PROPYL GLYCOL MONOBUTYL ETHER  
CAS:5131-66-8  
RTECS #:UA7700000  
Minumum % Wt:1.  
Maxumum % Wt:5.  
Other REC Limits:NONE  
OSHA PEL:NONE  
ACGIH TLV:NONE

Ingred Name:MONOETHANOLAMINE  
CAS:141-43-5  
RTECS #:KJ5775000  
Minumum % Wt:5.  
Maxumum % Wt:10.  
Other REC Limits:NONE  
OSHA PEL:3 PPM  
ACGIH TLV:3 PPM

Ingred Name:SODIUM XYLENE SULFONATE  
CAS:1330-72-7  
RTECS #:ZE5100000  
Minumum % Wt:5.  
Maxumum % Wt:10.  
Other REC Limits:NONE  
OSHA PEL:NONE  
ACGIH TLV:NONE

===== Hazards  
Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: EYES: CAUSES IRRITATION.  
SKIN: CAUSES IRRITATION. INGESTION: HARMFUL IF SWALLOWED.  
INHALATION: RPOLONGED BREATHING OF VAPORS MAY BE IRRITATING TO  
MUCOUS MEMBRANES. CHRONIC: NONE KNOWN.  
Effects of Overexposure:EYES: PAIN, IRRITATION. SKIN: REDNESS.  
INHALATION: HEADACHE. INGESTION: IRRITATION T

O GASTROINTESTINAL  
TRACT.

Medical Cond Aggravated by Exposure:NONE KNOWN.

===== First Aid Measures =====

First Aid:EYES: IMMEDIATELY FLUSH W/PLENTY OF WATER FOR AT LEAST  
15MINS. SEEK PROMPT MEDICAL ATTENTION. INGESTION: DONT INDUCE  
VOMIT. DRINK LARGE QUANTITIES OF WATER. CALL PHYSICIAN. SKIN: FLUSH  
WITH WATER. INH ALATION: REMOVE TO FRESH AIR.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flas

h Point:NONE

Autoignition Temp:Autoignition Temp Text:NP

Lower Limits:NO DATA

Upper Limits:NO DATA

Extinguishing Media:FOAM, DRY CHEMICAL, WATER, CARBON DIOXIDE.

Fire Fighting Procedures:WEAR PROTECTIVE EQUIPMENT TO GUARD AGAINST  
ALKALINE WATER VAPOR.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:VENTIALTE AREA. SOAK UP SPILL WITH OIL  
ABSORBANT. REMOVE ANY RESIDUE W/WATER & DETERGENT.

=====

=== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM FREEZING.A VOID CONTACT WITH  
SKIN AND EYES. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY. READ AND  
FOLLOW ALL LABLE DIRECTIONS AND PRECAUTIONS. DONT MIX WITH ANY  
OTHER CHEMICALS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE WITH ADEQUATE VENTILATION.

Ventilation:NONE.

Protective Gloves:RUBBER, NE

OPREN, PLASTIC.  
Eye Protection:EYE GOGGLES.  
Other Protective Equipment:NONE  
Work Hygienic Practices:WASH THOROUGHLY AFTER HANLDING.  
Supplemental Safety and Health  
NFPA: HEALTH, 1; FLAMMABILITY, 0; REACTIVITY, 0; SH, NONE. HMIS:  
HEALTH, 1; FLAMMABILITY, 0; REACTIVITY, 0; PE, B.

===== Physical/Chemical Properties =====

HCC:B3  
Boiling Pt:B.P. Text:208F-212F  
Melt/Freeze Pt:M.P/F.P Text:NA  
Decomp Temp:Decomp Text:NP  
Vapor Pres:NO DATA  
Vapor Density:>1  
Spec Gravity:1.  
034  
pH:NP  
Viscosity:NP  
Evaporation Rate & Reference:>1, BUTYL ACETATE=1  
Solubility in Water:COMPLETE  
Appearance and Odor:CLEAR, FAINT STRAW LIQUID, WITH MILD ODOR  
Percent Volatiles by Volume:NP  
Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
ACIDS, OXIDIZERS  
Stability Condition to Avoid:NONE  
Hazardous Decomposition Products:BURNING GIVES CARBON MONOXIDE, CARON  
DIOXIDE, SULFUR DIOXIDE, HYDROGEN SULFIDE, OXI  
DES OF NITROGEN.

===== Disposal Considerations =====

Waste Disposal Methods:DISCARD USED ABSORBANT IN PROPER RECEPTACLE FOR  
TRASH COLLECTION. UNDILUTED PRODUCT IS A NON-HAZARDOUS WASTE AS  
DEFINED BY EPA-RCRA( PH11.9).

===== Regulatory Information =====

SARA Title III Information:ETHYLENE GLYCOL PHENYL ETHER [122-99-6] -  
\*ALL CHEMICALS MARKED WITH AN ASTERISK (\*) ARE SUBJECT TO THE  
REPORTING REQUIREMENTS OF SECT

ION 313 OF TITLE III OF THE SUPERFUND

AMENDMENTS AND REAUTHORIZATION ACT (SARA) OF 1986 AND 40 CFR PART 372. THIS STATEMENT MUST REMAIN A PART OF THIS MATERIAL SAFETY DATA SHEET. ANY COPY OR REDISTRIBUTION OF THIS MSDS SHALL INCLUDE THIS STATEMENT.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied,

warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.