

DEVOE COATINGS CO DIV OF GROW GROUP INC -- DEVGRIP 138HR HEAVY-DUTY EPOXY
NONSKID COATING BASE 138BHR03 -- 8010-01-397-3820

===== Product Identification =====

Product ID:DEVGRIP 138HR HEAVY-DUTY EPOXY NONSKID COATING BASE 138BHR03

MSDS Date:07/31/1995

FSC:8010

NIIN:01-397-3820

Kit Part:Y

MSDS Number: CGFJB

=== Responsible Party ===

Company Name:DEVOE COATINGS CO DIV OF GROW GROUP INC

Address:4000

DUPONT CIR

Box:7600

City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

Info Phone Num:502-897-9861

Emergency Phone Num:800-424-9300

Preparer's Name:LOUIS F. HOLZKNECHT

CAGE:1HK86

=== Contractor Identification ===

Company Name:DEVOE COATINGS CO

Address:4000 DUPONT CIRCLE

Box:7600

City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

Phone:502-897-9861

CAGE:1HK86

===== Composition/Information on Ingredients =====

Ingred Name:ALPHA-ALUMINA (ALUMINUM OXIDE) (SARA 313)

CAS:1344-28-1

RTECS #:BD1200000
Fraction by Wt: 30.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT EST.
ACGIH TLV:10 MG/M3

Ingred Name:SLAG
CAS:68476-96-0
Fraction by Wt: 15.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TOTAL DUST
ACGIH TLV:10 MG/M3 TOTAL DUST

Ingred Name:EPOXY RESIN
CAS:25068-38-6
RTECS #:KC2100000
Fraction by Wt: 10.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:HIGH FLASH AROMATIC NAPHTHA (VP = 10 MMHG)(SARA 313)
CAS:64742-95-6
Fraction by Wt: 5.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT EST.
ACGIH TLV:100 PPM

Ingred Name:SODIUM POTASIU ALUMINUM SILICATE
CAS:37244-96-5
Fraction by Wt: 35.0%
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:10 MG/M3 TOTAL DUST

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Fraction by Wt: 15 MIN. GET MED AID. SKIN:
WASH W/SOAP & WATER. REMOVE CONTAM CLOTHES. GET MED AID IF IRRIT
PERSISTS. INGESTION: CALL DR. IMMED. DON'T INDUCE VOMITING. CHEM
PNEUMONITIS W/ASPIRATION OF VOMITUS, POSSIBLY FATAL. INHAL: GE

T

FRESH AIR IF TROUBLE BREATHING. IF CONTINUED TROUBLE BREATHING GET IMMEDIATE MED AID. BREATHING STOPPED, RESTORE BREATHING W/CPR. GET IMMEDIATE MED AID.

=====
===== Fire Fighting Measures =====

Flash Point:123F,51C

Lower Limits:1.0

Extinguishing Media:CO2, DRY CHEMICAL, FOAM (CLASS B FIRE).

Fire Fighting Procedures:FULL PROTEC EQUIP W/SCBA. WATER SPRAY MAY BE INEFFECTIVE, FOG NOZZLES PREFERRED. COOL FIRE-HEAT EXPOSED CLOSED CONTAINERS. PREVENT PRESSURE BUILD

-UP/AUTOIGNITION.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. KEEP FROM HEAT/ELECTRICAL EQUIP/SPARKS/FLAME. CLOSED CONTAINERS MAY EXPLODE IN EXTREME HEAT. DON'T CUT/WELD ON/NEAR CONTAINER AS MAY IGNITE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNIT SOURCES. AVOID BREATHING VAPORS. VENTILATE AREA. BEFORE CLEAN-UP REFER TO HAZ CAUTION INFO. CONTAIN SPILL/REMOVE W/INERT ABSORBENT/NONSPARKING TOOLS. STORE IN CLOSED CONTAINER UNTIL PROPERLY DISPOSED OF.

=====
===== Handling and Storage =====

Handling and Storage Precautions:ISOLATE FROM HEAT/SPARKS/FLAMES. DON'T SMOKE. PREVENT VAPOR BUILD-UP W/CONTINUOUS FLOW FRESH AIR. DON'T STORE >120F, NEAR FIRE/OPEN FLAME. STORE LG*

Other Precautions:AMTS IN BUILDINGS TO COMPLY W/OSHA 1910.106. KEEP CONTAINER CLOSED WHEN NOT USING. DON'T TRANSFER TO BOTTLES/UNLABELED CONTAINERS. DON'T REUSE EMPTY CONTAINERS. IF MATERIAL PART OF 2 COMPONENT PRODUCT, MIXTURE WILL HAVE HAZARDS OF BOTH COMPONENTS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:DON'T BREATHE VAPORS/SPRAY MIST/SANDING DUST.NIOSH/MSHA APPROVED MECHANICAL FILTER RESPIRATOR.IN RESTRICTED VENTILATION, NIOSH/MSHA APPROVED CHEM/MECHANICAL FILTER FOR PARTICULATES/VAPOR.CONFINED AREAS, NIOSH/MSHA APPROVED AIR-SUPPLY RESPIRATOR/HOODS

Ventilation:GEN DILUTION/LOCAL EXHAUST VENT. TO KEEP AIR CONTAM CONC