View NSN Online: https://aerobasegroup.tw/nsn/6520-01-394-5421

MINNESOTA MINING MFG CO DENTAL PROD DIV -- 5905WS SCOTCHBOND MULTIPURPOSE PRIMER -- 6520-01-394-5421

Product ID:5905WS SCOTCHBOND MULTIPURPOSE PRIMER MSDS Date:02/26/1997 FSC:6520 NIIN:01-394-5421 Kit Part:Y **MSDS Number: CGKYQ** === Responsible Party === Company Name: MINNESOTA MINING MFG CO DENTAL PROD DIV Address:3M CENTER City:ST PAUL State:MN ZIP:55144-1000 Coun try:US Info Phone Num:612-733-1110 Emergency Phone Num:612-733-1110 CAGE:76381 === Contractor Identification === Company Name: MINNESOTA MINING AND MFG CO, DBA 3M Address:3M CENTER BLDG 224-5S-04 Box:City:SAINT PAUL State:MN ZIP:55144-1000 Country:US Phone:866-556 5712 / 612-733-1110 CAGE:76381 Company Name: MINNESOTA MINING AND MFG CO DENTAL PRODUCTS DIV Address:3M CENTER Box:City:SAINT PAUL State:MN ZIP:55144-1000 Country:US Phone:800-364-3577/651-737-6501 CAGE:0K0U5

======= Composition

/Information on Ingredients =========

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 43%

Ingred Name:HYDROXYETHYL METHACRYLATE, ETHYLENE GLYCOL METHACRYLATE CAS:868-77-9 RTECS #:OZ4725000 Fraction by Wt: 35-40%

Ingred Name:POLYCARBOXYLIC ACID COPOLYMER Fraction by Wt: 10-15%

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards A cute and Chronic:EYES: SEVERE IRRITATION. SKIN: ALLERGIC REACTION & MILD IRRITATION. INHALATION: UPPER RESPIRATORY IRRITATION. INGESTION: GI IRRITATION TISSUES & IRRITATION OF THE ORAL MUCOSA. VEHICLES CAN ALTER SKIN ABSORPTION. Explanation of Carcinogenicity:NONE Effects of Overexposure:IRRITATION, REDNESS, SWELLING, PAIN, TEARING, CLOUDYNESS, IMPAIRED VISION, BLISTERING, ITCHING, SORENESS, COUGHING, SNEEZING, VOMITING, ABDOMINAL TENDERNESS, NAUSEA, BLOOD IN VOMITUS & B LOOD IN FECES, BLEEDING.

First Aid:EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINS. SKIN: FLUSH W/LARGE AMOUNTS OF WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: DRINK 2 GLASSES OF WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Flash Point:207F

Spill Release Procedures:V

ENTILATE AREA. COVER W/ABSORBENT MATERIAL. PLACE IN METAL CONTAINER.

Handling and Storage Precautions: KEEP CONTAINER TIGHTLY CLOSED. STORE
IN A COOL PLACE. USE W/ADEQUATE VENTILATION. WEAR APPROPRIATE
GLOVES WHEN HANDLING THIS MATERIAL.
Other Precautions: AVOID EYE/SKIN CONTACT. AVOID PROLONGED BREATHING OF
VAPORS. DON'T INGEST. ACRYLATE MAY PENETRATE GLOVES. IF PRIMER

CONTACTS GLOVE, REMOVE & DISCARD. WASH

HANDS W/SOAP & WATER & THEN RE-GLOVE.

Protective Gloves:RECOMMENDED Supplemental Safety and Health

Boiling Pt:B.P. Text:>95F Vapor Pres: