

PREDICT TECHNOLOGIES (PREDICTOLI) -- EP074-0015,ACTISOL -- 6640-01-410-9072

===== Product Identification =====

Product ID:EP074-0015,ACTISOL

MSDS Date:04/12/1995

FSC:6640

NIIN:01-410-9072

MSDS Number: CGLHV

=== Responsible Party ===

Company Name:PREDICT TECHNOLOGIES (PREDICTOLI)

Address:9555 ROCKSIDE ROAD,SUITE 350

City:CLEVELAND

State:OH

ZIP:44125-6231

Country:US

Info Phone Num:800-543-8786

Emerg

ency Phone Num:800-543-8786,800-424-9300(CHEMTREC)

CAGE:0MTU5

=== Contractor Identification ===

Company Name:PREDICT TECHNOLOGIES

Address:9555 ROCKSIDE RD SUITE 350

City:CLEVELAND

State:OH

ZIP:44125-6231

Country:US

Phone:800-543-8786

CAGE:0MTU5

===== Composition/Information on Ingredients =====

Ingred Name:ALPHATIC PETROLEUM DISTILLATE. (STODDARD SOLVENT)

CAS:8052-41-3

RTECS #:WJ8925000

Other REC Limits:C 1800 MG/M3 15 MIN.

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9596

Ingred Nam

e:ALPHA-PINENE, (PINENE RESIN)
CAS:80-56-8
RTECS #:DT7000000
Other REC Limits:ACGIH VAL TURBENTINE
ACGIH TLV:100 PPM (STEL150PPM)

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES:CONTACT WITH LIQUID OR VAPOR MAY CAUSE IRRITATION. SKIN: REPEATED/PROLONGED CONTACT MAY CAUSE IRRITATION, DERMATITIS, SENSITIZATION. INHALATION: OVEREXPOSURE TO VAPOR MAY CAUSE IRRITATION AND CNS DEPRESSION. ACUTE ORAL POISONING AND REPEATED DERMAL OR CHRONIC INHALATION MAY PRODUCE KIDNEY OR BLADDER DAMAGE.
Explanation of Carcinogenicity:NO COMPONENT WAS FOUND TO BE CARCINOGENIC IN NTP, IARC, OR OSHA.
Effects of Overexposure:EYES: IRRITATION. SKIN: IRRITATION, DERMATITIS, SKIN SENSITIZATION. INHALATION: IRRITATION, CNS DEPRESSION, KIDNEY OR BLADDER DAMAGE. ACUTE ORAL POISONING AND REPEATED DERMAL, OR CHRONIC INHALATION OR OVEREXPOSURE MAY PRODUCE KIDNEY OR BLADDER DAMAGE.
Medical Cond Aggravated by Exposure:NONE FOUND.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH SKIN AREA WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. INHALATION: MOVE TO FRESH AIR. AID IN BREATHING IF NECESSARY. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. DRINK LARGE QUANTITIES OF WATER AND/OR MILK. GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:79.0F,26.1C
Lower Limits:0.80 %
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL.
Fire Fighting Procedures:A STRAIGHT WATER STREAM WOULD SPREAD FIRES. IF EXPOSED TO HEAT, PRESSURE WILL BUILD UP IN CONTAINER
Unusual Fire/Explosion Hazard:STATIC ELECTRICITY

TY COULD CAUSE IGNITION.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR APPROPRIATE PROTECTIVE EQUIPMENT. REMOVE IGNITION SOURCES. CONTAIN SPILL BY ABSORBING WITH INERT MATERIAL AND DISPOSE PROPERLY.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE OR USE NEAR HEAT, SPARKS, OR FLAME. DO NOT STORE NEAR COMBUSTIBLE MATERIAL. DO NOT STORE IN DIRECT SUNLIGHT.

Other Precautions:WHEN SANDING DRY FILM, USE NIOSH APPROVED DUST MASK. KEEP CONTAINER CLOSED WHEN NOT IN USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED EQUIPMENT WHEN AIRBORNE EXPOSURE LIMITS ARE EXCEEDED.

Ventilation:ADEQUATE VENTILATION TO MAINTAIN EXPOSURE BELOW TLV IS RECOMMENDED.

Protective Gloves:NEOPRENE RUBBER RECOMMENDED.

Eye Protection:SPLASH GOGGLES OR FACE SHIELD.

Other Protective Equipment:PROTECTIVE CLOTHING SUFFICIENT TO PREVENT SKIN CONTACT. PROVIDE EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt.=115.6C, 240.F

Vapor Density:>1 AIR=1.0

Spec Gravity:0.848

Evaporation Rate & Reference:SLOWER THAN W

ATER.
Solubility in Water:NOT SOLUBLE
Appearance and Odor:LIQUID. SOLVENT ODOR.
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS.
Stability Condition to Avoid:AVOID PROLONGED STORAGE AT ELEVATED
TEMPERATURES.
Hazardous Decomposition Products:OXIDES OF CARBON.
Conditions to Avoid Polymerization:MAY OCCUR. AVOID CONTAMINATION WITH
STRONG ACIDS.

===== Disposal Co
nsiderations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek compet
ent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.