

LHB INDUSTRIES -- SO-SURE SILVER 17178 (0014-160)

=====

MSDS Safety Information

=====

FSC: 8010

NIIN: 00-721-9751

MSDS Date: 11/14/1996

MSDS Num: CGNGP

Product ID: SO-SURE SILVER 17178 (0014-160)

MFN: 05

Responsible Party

Cage: 0FTT5

Name: LHB INDUSTRIES

Address: 8833 FLEISCHER PLACE

City: ST. LOUIS MO 6

3134

Info Phone Number: 314-522-3141

Emergency Phone Number: 800-424-9300 CHEMTREC/ 314-522-3141

Preparer's Name: GREGORY M. MCGOWAN

Published: Y

=====

Preparer Co. when other than Responsible Party Co.

=====

Cage: 0FTT5

Name: LHB INDUSTRIES

Address: 8833 FLEISCHER PLACE

City: ST. LOUIS MO 63134

=====

Contractor Summary

=====

=====

Cage: 0FTT5

Name: LHB INDUSTRIES

Address: 8833 FLEISCHER PLACE

City: ST. LOUIS MO 63134

Phone: 314-522-3141

=====

Item Description Information

=====

Item Manager: GSA

Item Name: ENAMEL

Specification Number: A-A-665D

Unit of Issue: PT

UI Container Qty: 0

=====

Ingredients

=====

=====

Cas: 8030-30-6  
RTECS #: DE3030000  
Name: VM&P NAPHTHA (NIOSH #OI6180000)  
% Wt: 5.29%  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: 300 PPM  
ACGIH TLV: 300 PPM

-----

Cas: 108-88-3  
RTECS #: XS5250000  
Name: TOLUENE (SARA III)(NIOSH #XS5250000)  
% Wt: 26.63%  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: 200 PPM  
ACGIH TLV: 100 PPM  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS

-----

Cas: 67-64-1  
RTECS #: AL3150000  
Name: ACETONE (SARA III)(NIOSH #AL3150000)  
% Wt: 30.97%  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: 1000 PPM  
ACGIH TLV: 750 PPM  
EPA Rpt Qty: 5000 LBS  
DOT Rpt Qty: 5000 LBS

-----

Cas: 74-98-6  
RTECS #: TX2275000  
Name: PROPANE (NIOSH #TX2275000)  
% Wt: 16.72%  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: 1000 PPM  
ACGIH TLV: 1000 PPM

-----

Cas: 75-28-5  
RTECS #: TZ4300000  
Name: 2-METHYL PROPANE (NIOSH #TZ4300000)  
% Wt: 4.11%  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: NOT ESTABLISH

ED  
ACGIH TLV: 800 PPM

-----  
Cas: 106-97-8  
RTECS #: EJ4200000  
Name: N-BUTANE (NIOSH #EJ4200000)  
% Wt: 6.58%  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: 800 PPM  
ACGIH TLV: 800 PPM  
=====

#### Health Hazards Data

=====

Route Of Entry Inds - Inhalation: YES  
Skin: YES  
Ingestion: YES  
Carcinogenicity Inds - NTP: NO  
IARC: NO  
OSHA: NO  
Effects of Exposure: INHAL: HEADACHE, VOMIT, HARMFUL, FATAL, BRAIN/NS DAMAGE,  
ANESTHETIC, RESPIRATORY TRACT IRRITATION, LIGHT HEADEDNESS, STAGGERING GAIT,  
GIDDINESS, NAUSEA. INGEST: HARMFUL. SKIN: IRRITATION. EYE: IRRITATION.  
Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS.  
First Aid: SKIN: WASH WITH SOAP AND WATER. WASH CLOTHES BEFORE REUSE. EYE:  
FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. INGEST: DONT INDUCE  
VOMIT. GET MEDICAL ATTENTION. INHAL: GET FRESH AIR. ARTIFICIAL RESPIRATION  
IF NEEDED. GET MEDICAL ATTENTION.

#### Handling and Disposal

=====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA.  
MOP SPILLS WITH INERT ABSORBENT. AVOID BREATHING VAPORS.  
Waste Disposal Methods: DISPOSE IN ACCORDANCE W/FEDERAL, STATE, LOCAL  
REGULATIONS. DONT PUNCTURE, INCINERATE OR STORE >120F. EXPOSURE TO HEAT OR  
PROLONGED EXPOSURE TO SUN MAY CAUSE CAN TO BURST. DISCARD EMPTY CAN IN TRASH  
PICK-UP. DONT PLACE IN HOME TRASH COMPACTOR.  
Handling And Storage Precautions: KEEP OUT OF REACH OF CHILDREN.  
CAUTION-CONTENTS UNDER PRESSURE. DONT STORE WHERE TEMPERATURE MAY EXCEED  
120F. AVOID BREATHING SPRAY, MIST OR VAPORS.  
Other Precautions: AVOID CONTACT WITH EYES AND SKIN. USE WITH GOOD VENTILATION.  
READ ENTIRE LABEL BEFORE USING. FOLLOW ALL LABEL DIRECTIONS. INTENTIONAL  
MISUSE BY DELIBERATELY CONCENTRATING AND INHALING OR SWALLOWING CONTENTS MAY  
BE HARMFUL OR FATAL.

==

=====

Fire and Explosion Hazard Information

=====

Flash Point Text: PROPELLANT 156F\*

Autoignition Temp Text: 874F

Lower Limits: 1.8

Upper Limits: 9.5

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY.

AVOID SPREADING ANY BURNING LIQUID WITH WATER SPRAY.

Fire Fighting Procedures: WATER MAY BE INEFFECTIVE. USE WATER TO COOL

CONTAINERS. WEAR SCBA. USE SHIELDING TO PROTECT

PERSONNEL FROM BURSTING,

RUPTURING OR VENTING OF CONTAINERS.

Unusual Fire/Explosion Hazard: DONT SPRAY NEAR OPEN FLAME. AT ELEVATED

TEMPERATURE (>120F) CONTAINERS MAY VENT, RUPTURE OR BURST. AEROSOL

CONTAINER: DONT EXPOSE TO TEMPERATURE >120F.

=====

Control Measures

=====

Respiratory Protection: NONE BELOW TLV. USE NIOSH/MSHA APPROVED MASK ABOVE TLV.

Ventilation: LOCAL EXHAUST: PREFER

RED. MECHANICAL (GENERAL): ACCEPTABLE AT

POINT OF MIST OR SPRAY RELEASE.

Protective Gloves: RECOMMENDED

Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equipment: IMPERVIOUS CLOTHES TO PROTECT SKIN. EYE WASH

STATION.

Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DONT EAT, DRINK, OR SMOKE

WHILE USING PRODUCT.

Supplemental Safety and Health: \*LIQUID PORTION 24F/4.4C.

=====

Physical/Chemical Properties

=====

=====

B.P. Text: NA

M.P/F.P Text: NA

Decomp Text: NA

Vapor Pres: 60 @ 68F

Vapor Density: >1.5

Spec Gravity: 0.728 (WATER=1)

PH: NA

VOC Grams/Liter: 438

Viscosity: NA

Solubility in Water: INSOLUBLE

Appearance and Odor: SILVER PAINT

Corrosion Rate: NA

=====

Reactivity Data

=====

Stability Indicator: YES

Stability Condition To Avoid: EXTREME HEAT

Materials To Avoid: NA

Ha

zardous Decomposition Products: CARBON MONOXIDE AND POSSIBLE HYDROGEN CHLORIDE.

Hazardous Polymerization Indicator: NO  
Conditions To Avoid Polymerization: NA

=====

Toxicological Information

=====

Ecological Information

=====

MSDS Tran  
sport Information

=====

Regulatory Information

=====

Other Information

Other Information: VOC = 438 G/L

=====

Transportation Information

=====

Responsible Party Cage: 0FTT5  
Trans ID NO: 83200  
Product ID: SO-SURE SILVER 17178 (0014-160)  
MSDS Prepared Date: 11/14/1996  
Review Date: 01/13/1998  
MFN: 5  
Multiple KIT Number: 0  
Review IND: Y  
Unit Of Issue: PT  
Container QTY: 0

=====

Detail DOT Information

=====

DOT PSN Code: DTJ  
Symbols: D  
DOT Proper Shipping Name: CONSUMER COMMODITY  
Hazard Class: ORM-D  
Label: NONE  
Non Bulk Pack: 1

56,306  
Bulk Pack: NONE  
Max Qty Pass: 30KGGROSS  
Max Qty Cargo: 30KGGROSS  
Vessel Stow Req: A

=====

Detail IMO Information

=====

IMO PSN Code: AKH  
IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODUCT ?  
IMDG Page Number: SEE 9022  
UN Number: 1950  
UN Hazard Class: 9?  
IMO Packaging Group: -  
Subsidiary Risk Label: -  
EMS Number: 2-13

=====

Detail IATA Inform  
ation

=====

IATA PSN Code: ALS  
IATA UN ID Num: 1950  
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE  
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)  
IATA UN Class: 2.1  
IATA Label: FLAMMABLE GAS  
Packing Note Passenger: 203  
Max Quant Pass: 75KG  
Max Quant Cargo: 150KG  
Packaging Note Cargo: 203

=====

Detail AFI Information

=====

AFI PSN Code: ALR  
AFI Symbols: \*  
AFI Proper Shipping Name: AEROSOLS, FLAMMABLE, N.O.S.  
AFI PSN Modifier: (EACH NOT EXCEEDING 1L CAPACITY)  
AFI Hazard Class: 2.1  
AFI UN ID NUM: UN1950  
Special Provisions: P4  
Back Pack Reference: A6.3

=====

HAZCOM Label

=====

Product ID: SO-SURE SILVER 17178 (0014-160)  
Cage: 0FTT5  
Company Name: LHB INDUSTRIES  
Street: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO  
Zipcode: 63134  
Health Emerge

ncy Phone: 800-424-9300 CHEMTREC/ 314-522-3141

Label Required IND: Y

Date Of Label Review: 10/12/1999

Status Code: A

Origination Code: G

Hazard And Precautions: INHAL: HEADACHE, VOMIT, HARMFUL, FATAL, BRAIN/NS  
DAMAGE, ANESTHETIC, RESPIRATORY TRACT IRRITATION, LIGHT HEADEDNESS,  
STAGGERING GAIT, GIDDINESS, NAUSEA. INGEST: HARMFUL. SKIN: IRRITATION. EYE:  
IRRITAT ION.

=====

Disclaimer (provided with this information by the compiling agencies):

This

information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied

warrants, states, or intends said information to have any application, use or

viability by or to any person or persons outside the Department of Defense

nor any person or persons contracting with any instrumentality of the United

States of America and disclaims all liability for such use. Any person

utilizing this instruction who

is not a military or civilian employee of the

United States of America should seek competent professional advice to verify

and assume responsibility for the suitability of this information to their

particular situation regardless of similarity to a corresponding Department

of Defense or other government situation.