View NSN Online: https://aerobasegroup.tw/nsn/9150-01-422-8746

WARREN DISTRIBUTION, INC. -- MAGI ALL FLEET SAE 15W40 DIESEL MOTOR OIL 9150-01-422-8746

============= Product Identification =================

Product ID:MAGI ALL FLEET SAE 15W40 DIESEL MOTOR OIL

MSDS Date:01/16/1996

FSC:9150

NIIN:01-422-8746

MSDS Number: CGXHG === Responsible Party ===

Company Name: WARREN DISTRIBUTION, INC.

Address:727 SOUTH 13TH STREET

City:OMAHA State:NE ZIP:68102 Country:US

Emergency Phone Num

:403-341-9397/ 402-977-5754(FAX)

CAGE:KO526

=== Contractor Identification ===

Company Name: CASCADE DISTRIBUTING Address: 136 E. MAIN STREET SUITE 6

Box:City:KENT State:OH

ZIP:44240 Country:US

Phone:330-677-1118/FAX 330-677-1014

CAGE:082N2

Company Name: WARREN DISTRIBUTION, INC.

Address:727 SOUTH 13TH STREET

City:OMAHA State:NE ZIP:68102 Country:US

Phone:402-341-9397

CAGE:KO526

======= Composition/Information on Ingredients ========

Ingred Name: MINERAL OIL, PETROLEUM DISTILLATES, HYDRO

TREATED (MILD), HEAVY PARAFFINIC OR 64742-65-0 CAS:64742-54-7 RTECS #:PY8035500 Fraction by Wt: < 88% Other REC Limits: NONE RECOMMENDED OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST) Ingred Name: PROPRIETARY ADDITIVES Fraction by Wt: > 12% Other REC Limits:5 MG/M3 (OIL MIST) ============= Hazards Identification ======================== LD50 LC50 Mixture: NOT GIVEN FOR PRODUCT AS A WHOLE Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: CONTACT WITH EYES MAY CAUSE IRRITATION. PROLONGED OR REPEATED SKIN CONTACT MAY RESULT IN IRRITATION OR DERMATITIS. BREATHING OIL MIST IN CONCENTRATIONS THAT EXCEED THE TLV & PEL MAY RESULT IN RESPIRAT ORY DISCOMFORT & IRRITATION. ASPIRATIONOF LIQUID INTO LUNGS DURING INGESTION OR **VOMITING MAY CAUSE CHEMICAL PNEUMONITIS** Explanation of Carcinogenicity: THIS COMPOUND CONTAINS NO INGREDIENTS AT **CONCENTRATIONS OF 0.1% OR GREATE** R THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS. Effects of Overexposure: SKIN IRRITATION, EYE IRRITATION, RESPIRATORY TRACT IRRITATION. Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER. First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF IRRITATION PERSIST, GET MEDICAL ATTENTION. INH ALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. CALL MEDICAL ATTENTION IMMEDIATELY. Flash Point Method:COC Flash Point:>420F,>216C Lower Limits:NOT GIVEN **Upper Limits: NOT GIVEN** Extinguishing Media: WATER SPRAY, DRY CHEMICAL, FOAM, CARBON DIOXIDE. WATER SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURES.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD W

EAR SELF CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. COOL TANKS AND CONTAINERS EXPOSED TO FIRE WITH WATER. Unusual Fire/Explosion Hazard: EMPTY CONTAINERS RETAIN RESIDUE AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS ======== Accidental Release Measures ============ Spill Release Procedures: ADD SAND, EARTH OR OTHER SUITABLE ABSORBANT TO SPILL AREA. KEEP PRODUCT OUT OF SEWERS AND WATERWAYS BY DIKING OR IMPOUNDING. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER. ============= Handling and Storage ========================== Handling and Storage Precautions: STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. DO NOT EXPOSE TO EXTREME TEMPERATURE OR FLAMES. KEEP CONTAINERS CLOSED WHEN NOT IN USE. Other Precautions: NONE SPECIFIED BY MANUFACTURER. ====== Exposure Controls/Personal Protection ======== **Respiratory Protection** :USE SUPPLIED-AIR RESPIRATORY PROTECTION IN CONFINED SPACE, IF NEEDED. Ventilation: USE LOCAL EXHAUST TO CAPTURE VAPOR, MIST OR FUME, IF NECESSARY. PROVIDE SUFFICIENT VENTILATION TO PREVENT EXCEEDING TLVS Protective Gloves: NEOPRENE TO AVOID REPEATED/PROLONGED Eye Protection: GOGGLES IF CONTACT LIKELY. Other Protective Equipment: CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH HANDS TH

OROUGHLY AFTER CONTACT, BEFORE

BREAKS & MEALS, AND AT THE END OF THE WORK PERIOD.

Supplemental Safety and Health

THOROUGHLY CLEAN CONTAMINATED CLOTHING, INCLUDING SHOES, BEFORE RE-USE.

========= Physical/Chemical Properties ==========

HCC:V6

Boiling Pt:B.P. Text:NOT GIVEN

Melt/Freeze Pt:M.P/F.P Text:-15F,-26C

Vapor Pres:NOT GIVEN Vapor Density:NOT GIVEN

Spec Gravity:.887 Viscosity:NOT GIVEN

Evaporation Rate & Dr. Reference: NOT GIVEN

Solubility in Water: INSOLUBLE

Appearan

========= Stability and Reactivity Data ==========
Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS SUCH AS LIQUID CHLORINE, CONCENTRATED OXYGEN, SODIUM
HYPOCHLORITE OR CALCIUM HYPOCHLORITE.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products: CARBON MONOXIDE, WATER VAPOR, OXIDES
OF SULFUR, NITROGEN, PHOSPHORUS, CARBON DIOXIDE.
======== Disposal Considerations

Waste Disposal Methods:PLACE IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek com petent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

ce and Odor: DARK BROWN LIQUID, PETROLEUM ODOR
