

THE W.W. HENRY COMPANY -- HENRY 150 LINOLEUM PASTE -- 8040-00-273-8714

=====
Product Identification
=====

Product ID:HENRY 150 LINOLEUM PASTE

MSDS Date:01/01/1995

FSC:8040

NIIN:00-273-8714

MSDS Number: CGXKP

=== Responsible Party ===

Company Name:THE W.W. HENRY COMPANY

Address:5608 SOTO STREET

City:HUNTINGTON PARK

State:CA

ZIP:90255-2629

Country:US

Info Phone Num:213-583-4961 / FAX 213-582-8451

Em

ergency Phone Num:800-424-9300 (CHEMTREC)

Preparer's Name:EISENHARD

CAGE:EO968

=== Contractor Identification ===

Company Name:CHEMICAL COMMODITIES AGENCY, INC.

Address:27447 PACIFIC STREET

Box:City:HIGHLAND

State:CA

ZIP:92346-2640

Country:US

Phone:909-864-2310

CAGE:60777

Company Name:HENRY W W CO

Address:Box:3001

City:LANCASTER

State:PA

ZIP:17604

Country:US

Phone:717-396-2328;717-396-2935

CAGE:11761

Company Name:THE W.W. HENRY CO/HUNTINGTON PARK, CA 90255

CAGE:EO968

=====
Composition/I

Information on Ingredients =====

Ingred Name:NON-HAZARDOUS INGREDIENTS
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE: IRRIT.

===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER. SKIN: FLUSH W/
WATER. INGEST: DRINK WATER.
GET MED AID.

===== Fire Fighting Measures =====

Flash Point:NA
Lower Limits:NA
Upper Limits:NA
Extinguishing Media:NA
Fire Fighting Procedures:USE PROTECTIVE EQUIPMENT INCLUDING RESPIRATORY
PROTECTION AS CONDITION WARRANTS.
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP MATERIAL INTO DOT APPROVED CONTAINER.
REMOVE TO A SAFE PLACE WHERE
MATERIAL CAN DRY.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AT TEMPS BELOW 120F.
Other Precautions:KEEP AWAY FROM CHILDREN. USE ONLY AS DIRECTED ON
LABEL. CLOSE CONTAINER AFTER EACH USE. DONT REUSE CONTAINER.

===== Exposure Controls/Personal Protection =====

Ventilation:USE W/ADEQUATE VENTILATION. OPEN DOORS, WINDOWS & UTILIZE
OTHER MEANS TO ENSURE FRESH AIR ENTRY AND EXHAUST.
Protective Gloves:RECO

MMENDED

Eye Protection:SPLASH PROOF GOGGLES

Work Hygienic Practices:WASH W/SOAP & WATER OR HAND CLEANSER.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:24 @ 68F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:APPROX. 55% BT WT.

Appearance and Odor:BROWN PASTE, W/CHARACTERISTIC ODOR.

Percent Volatiles by Volume:28.32

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:CONTACT W/STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:SULFUR DIOXIDE, CARBON MONOXIDE & CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE W/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated

for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.