

LHB INDUSTRIES -- SO-SURE BLUE 25184 (0014-253)

=====

MSDS Safety Information

=====

FSC: 8010

NIIN: 00-721-9753

MSDS Date: 10/09/1995

MSDS Num: CGXMS

Product ID: SO-SURE BLUE 25184 (0014-253)

MFN: 05

Responsible Party

Cage: 0FTT5

Name: LHB INDUSTRIES

Address: 8833 FLEISCHER PLACE

City: ST. LOUIS MO 631

34

Info Phone Number: 314-522-3141

Emergency Phone Number: 314-522-3141 800-424-9300(CHEMTREC)

Preparer's Name: GREGORY M. MCGOWAN

Published: Y

=====

Preparer Co. when other than Responsible Party Co.

=====

Cage: 0FTT5

Name: LHB INDUSTRIES

Address: 8833 FLEISCHER PLACE

City: ST. LOUIS MO 63134

=====

Contractor Summary

=====

=====

Cage: 0FTT5

Name: LHB INDUSTRIES

Address: 8833 FLEISCHER PLACE

City: ST. LOUIS MO 63134

Phone: 314-522-3141

=====

Item Description Information

=====

Item Manager: GSA

Item Name: ENAMEL

Unit of Issue: PT

UI Container Qty: 0

=====

Ingredients

=====

Cas: 8030-30-6

RTECS #:

DE3030000
Name: VM & P NAPHTHA
% Wt: 4.37
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 300 PPM
ACGIH TLV: 300 PPM

Cas: 108-88-3
RTECS #: XS5250000
Name: TOLUENE (SARA 313)
% Wt: 30.07
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 200 PPM
ACGIH TLV: 100 PPM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 67-64-1
RTECS #: AL3150000
Name: ACETONE (SARA 313)
% Wt: 17.75
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 1000 PPM
ACGIH TLV:
750 PPM
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS

Cas: 1330-20-7
RTECS #: ZE2100000
Name: XYLENE (SARA 313)
% Wt: <1.46
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 64742-94-6
RTECS #: SE7546000
Name: AROMATIC 150
% Wt: <1.46
Other REC Limits: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: 5 PPM

Cas: 74-98-6
RTECS

#: TX2275000
Name: PROPANE
% Wt: 16.72
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 1000 PPM
ACGIH TLV: 1000 PPM

Cas: 75-28-5
RTECS #: TZ4300000
Name: 2-METHYL PROPANE
% Wt: 4.11
Other REC Limits: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: 800 PPM

Cas: 106-97-8
RTECS #: EJ4200000
Name: N-BUTANE
% Wt: 6.58
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 800 PPM
ACGIH TLV: 800 PPM

=====

Health Hazards Data

=====

Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: YES
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO
Effects of Exposure: EYE: IRRIT. SKIN: IRRIT. INHAL: HARMFUL, FATAL, BRAIN/NS
DAMAGE, ANESTHETIC, RESPIRATORY TRACT IRRIT, LIGHT HEADEDNESS, STAGGERING
GAIT, GIDDY, NAUSEA, VOMIT, HEADACHE. INGEST: HARMFUL.
Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS
First Aid: EYE: FLUSH W/WATER FOR
15 MINUTES. SKIN: WASH W/SOAP & WATER.
WASH CLOTHES BEFORE REUSE. INHAL: REMOVE TO FRESH AIR. ARTIF RESP IF NEEDED.
INGEST: DONT INDUCE VOMIT. IN ALL CASES, GET MEDICAL ATTENTIO N.

=====

Handling and Disposal

=====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA.
MOP SPILLS W/INERT ABSORBENT. AVOID BREATHING VAPORS.
Waste Disposal Methods: IN ACCORDANCE W/LOCA

L, STATE & FEDERAL REGULATIONS.

DONT PUNCTURE, INCINERATE OR STORE >120F. EXPOSURE TO HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE CAN TO BURST. DISCARD EMPTY CAN IN TRASH PICK-UP. DONT PLACE EMPTY IN HOME TRASH COMPACTOR.

Handling And Storage Precautions: KEEP OUT OF REACH OF CHILDREN.

CAUTION-CONTENTS UNDER PRESSURE. DONT STORE WHERE TEMPS MAY EXCEED 120F.

Other Precautions: USE WITH GOOD VENTILATION. READ ENTIRE LABEL BEFORE USING.

FOLLOW ALL LABEL DIRECTIONS.

=====

=====

Fire and Explosion Hazard Information

=====

Flash Point Text: -156F,-104C

Lower Limits: 1.8

Upper Limits: 9.5

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY.

AVOID SPREADING ANY BURNING LIQUID W/WATER SPRAY.

Fire Fighting Procedures: WATER MAY BE INEFFECTIVE. USE WATER TO COOL

CONTAINERS. USE SCBA. USE SHIELDING TO PROTECT PERSONNEL FROM BURST, RUPTURE, VENT OF CONTAINERS

.

Unusual Fire/Explosion Hazard: DONT SPRAY NEAR OPEN FLAME. ELEVATED TEMPERATURE (OVER 120F) CONTAINER MAY VENT, RUPTURE, BURST. AEROSOL CONTAINERS: DONT EXPOSE TO TEMPERATURES ABOVE 120F.

=====

Control Measures

=====

Respiratory Protection: NONE BELOW TLV. USE NIOSH/MSHA APPROVED MASK ABOVE TLV.

Ventilation: LOCAL EXHAUST: PREFERRED. MECHANICAL: ACCEPTABLE AT POINT OF MIST OR SPRAY RELEASE

E.

Protective Gloves: REQUIRED

Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equipment: IMPERVIOUS CLOTHES TO PROTECT SKIN. EYE WASH STATION.

Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DONT EAT, SMOKE WHILE USING PRODUCT.

=====

Physical/Chemical Properties

=====

B.P. Text: NA

Decomp Text: NA

Vapor Pres: 60 @ 68 F

Vapor Density: >1.5 AIR=1

Spec Gravity: 0.795 AEROSOL

PH:

NA
VOC Grams/Liter: 502
Solubility in Water: INSOLUBLE
Appearance and Odor: BLUE PAINT

Reactivity Data

Stability Indicator: YES
Stability Condition To Avoid: EXTREME HEAT
Materials To Avoid: NA
Hazardous Decomposition Products: CARBON MONOXIDE AND POSSIBLE HYDROGEN CHLORIDE.
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NA

Toxicological Information

Ecological Information

MSDS Transport Information

Regulatory Information

Other Information

Other Information: VOC = 502 G/L

Transportation Information

Responsible Party Cage: 0FTT5
Trans ID NO: 83218
Product ID: SO-SURE BLUE 25184 (0014-253)
MSDS Prepared Date: 10/09/1995
Review Date: 04/17/1998
MFN: 5
Multiple KIT Number: 0

Review IND: Y
Unit Of Issue: PT
Container QTY: 0

=====
Detail DOT Information
=====

DOT PSN Code: DTJ
Symbols: D
DOT Proper Shipping Name: CONSUMER COMMODITY
Hazard Class: ORM-D
Label: NONE
Non Bulk Pack: 156,306
Bulk Pack: NONE
Max Qty Pass: 30KGGROSS
Max Qty Cargo: 30KGGROSS
Vessel Stow Req: A
=====

Detail IMO Information
=====

=====

IMO PSN Code: AKH
IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODUCT ?
IMDG Page Number: SEE 9022
UN Number: 1950
UN Hazard Class: 9?
IMO Packaging Group: -
Subsidiary Risk Label: -
EMS Number: 2-13
=====

Detail IATA Information
=====

IATA PSN Code: ALS
IATA UN ID Num: 1950
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L
CAPACITY)
IATA UN Class: 2.1
IATA Label: FLAMMABLE GAS
Packing Note Passenger: 203
Max Quant Pass: 75KG
Max Quant Cargo: 150KG
Packaging Note Cargo: 203
=====

Detail AFI Information
=====

AFI PSN Code: ALR
AFI Symbols: *
AFI Proper Shipping Name: AEROSOLS, FLAMMABLE, N.O.S.
AFI PSN Modifier: (EACH NOT EXCEEDING 1L CAPACITY)
AFI Hazard Class: 2.1
AFI UN ID NUM: UN1950
Special Provisions: P4
Back

Pack Reference: A6.3
=====

HAZCOM Label
=====

Product ID: SO-SURE BLUE 25184 (0014-253)
Cage: 0FTT5
Company Name: LHB INDUSTRIES
Street: 8833 FLEISCHER PLACE
City: ST. LOUIS MO
Zipcode: 63134
Health Emergency Phone: 314-522-3141 800-424-9300(CHEMTREC)
Label Required IND: Y
Date Of Label Review: 10/12/1999
Status Code: A
Origination Code: G
Hazard And Precautions: EYE: IRRIT. SKIN: IRRIT. INHAL: H
ARMFUL, FATAL,
BRAIN/NS DAMAGE, ANESTHETIC, RESPIRATORY TRACT IRRIT, LIGHT HEADEDNESS,
STAGGERING GAIT, GIDDY, NAUSEA, VOMIT, HEADACHE. INGEST: HARMFUL.

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have a ny application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.