

HY-KLAS PAINTS, INC. -- LATEX WOOD OR MASONRY GRAY #36176 -- 8010-01-396-6785
===== Product Identification =====

Product ID:LATEX WOOD OR MASONRY GRAY #36176

MSDS Date:07/02/1990

FSC:8010

NIIN:01-396-6785

MSDS Number: CGXVM

=== Responsible Party ===

Company Name:HY-KLAS PAINTS, INC.

Box:3607

City:LOUISVILLE

State:KY

ZIP:40201-3607

Country:US

Info Phone Num:502-634-9406

Emergency Phone Num:502-634-

9406, 502-589-8222 POISON

CAGE:KO343

=== Contractor Identification ===

Company Name:HY-KLAS PAINTS INC

Box:3607

City:LOUISVILLE

State:KY

ZIP:40201-3607

Country:US

Phone:502-634-9406

CAGE:0HN95

Company Name:HY-KLAS PAINTS, INC

Box:10205

City:LOUISVILLE

State:KY

ZIP:40210

Phone:(502) 634-9406

CAGE:KO343

===== Composition/Information on Ingredients =====

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 24.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL

:10 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:NEPHELINE SYENITE
CAS:37244-96-5
Fraction by Wt: 25.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG/M3

Ingred Name:MUSCOVITE MICA
CAS:12003-26-2
Fraction by Wt: 2.5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:3 MG/M3
ACGIH TLV:3 MG/M3

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 41.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:BICYCLIC OXAZOLIDINES
CAS:56709-13-8
Fraction by Wt: 0.12%
Other REC Limits:NONE RECOMMENDED

Ingr
ed Name:2,2,4-TRIMETHYL-1,3 PENTANEDIOL MONOISOBUTYRATE
CAS:25265-77-4
Fraction by Wt: 1.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:TETRA CHLOROISOPHTHALONITRILE
CAS:1897-45-8
Fraction by Wt: 0.6%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHYLENE GLYCOL (SARA 313) (CERCLA)
CAS:107-21-1
RTECS #:KW2975000
Fraction by Wt: 1.0%
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:50 PPM
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:AMMONIA (SARA 302/313) (CERCLA)
CAS:7664-41-7
RTECS #:BO0875000

Fraction by Wt: 0.2%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:50 PPM
ACGIH TLV:25 PPM
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:FORMALDEHYDE (SARA 3023/313) (CERCLA)
CAS:50-00-0
RTECS #:LP8925000
Fraction by Wt: 0.02%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 PPM
ACGIH TLV:0.3 PPM
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO
IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE: IRRIT. SKIN: IRRIT. INHAL:
HEADACHE, NAUSEA, IRRIT TO NOSE/THROAT/LUNGS, LIVER/KIDNEY/CNS
DAMAGE.
Medical Cond Aggravated by Exposure:NA

===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER. SKIN: FLUSH W/WATER. INHAL: REMOVE TO
FRESH AIR. INGEST: DRINK 1-2 GLASSES OF WATER. DONT INDUCE VOMIT.
CALL DR.

===== Fire Fighting Measures =====

Extinguishing Media:NA
Fire Fighting Procedures:CLOSED CONTAINERS MAY EXPLODE IN EXTREME HEAT.
Unusual Fire/Explosion Hazard:NA

===== Accidental Release Measures =====

Spill Release Procedures:DIKE AND CONTAIN SPILL W/INERT MATERIAL (SAND,
EARTH). TRANSFER LIQUID TO CONTAINER FOR RECOVERY/DISPOSAL & SOLID
DIKING MATERIAL TO SEPARATE CONTAINER FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP

FROM FREEZING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NA
Ventilation:MECHANICAL LOCAL EXHAUST
Protective Gloves:IMPERVIOUS
Eye Protection:SPLASH GOGGLES
Work Hygienic Practices:WASH BEFORE EATING.
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:55-57

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NA
Stability Condition to Avoid:NA
Hazardous Decomposition Products:NA

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/FEDERAL, STATE AND
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The U
nited States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.