

METAL LUBRICANTS CO GRAFO COLLOIDS DIV -- MIL-L-3572A, GRADE B -- 9150-01-020-6710

===== Product Identification =====

Product ID:MIL-L-3572A, GRADE B

MSDS Date:01/21/1994

FSC:9150

NIIN:01-020-6710

Kit Part:Y

MSDS Number: CHHQQ

=== Responsible Party ===

Company Name:METAL LUBRICANTS CO GRAFO COLLOIDS DIV

Address:105 8TH

City:EMLENTON

State:PA

ZIP:16373

Country:US

Info Phone Num:412-867-5000

Emergen

cy Phone Num:412-867-5000

CAGE:4M367

=== Contractor Identification ===

Company Name:METAL LUBRICANTS CO GRAFO COLLOIDS DIV

Address:105 8TH

Box:City:EMLENTON

State:PA

ZIP:16373

Country:US

Phone:412-867-5000

CAGE:4M367

===== Composition/Information on Ingredients =====

Ingred Name:GRAPHITE, NATURAL

CAS:7782-42-5

RTECS #:MD9659600

Fraction by Wt: 10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15 MPPCF; Z-3

ACGIH TLV:2 MG/M3 RDUST; 9596

===== Hazards Identificat

ion =====

LD50 LC50 Mixture:5 MG/M3 FOR OIL MIST.

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:REPEATED AND PROLONGED SKIN CONTACT
MAY CAUSE MILD IRRITATION.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT
CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT
CARCINOGENS.

Effects of Overexposure:SKIN CONTACT.

Medical Cond Aggravated by E

xposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:SKIN: WASH WITH SOAP AND WATER. EYES: FLUSH WITH COPIOUS
AMOUNTS OF WARM WATER; SEEK MEDICAL AID IF IRRITATION PERSISTS.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:325F,163C

Lower Limits:1 %

Upper Limits:6 %

Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL, WATER SPRAY OR
FOG.

Fire Fighting Procedures

:USE AIR-SUPPLIES RESCUE EQUIPMENT FOR ENCLOSED
AREAS. COOL FIRE EXPOSED CONTAINERS WITH WATER.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE PRODUCT. ADD ABSORBENT TO SPILL
AREA. BURY IN LANDFILL IF ACCEPTABLE. KEEP OUT OF STREAMS AND
WATERWAYS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

=====

Handling and Storage Precautions:STORE AT ROOM TEMPERATURE. KEEP THE CONTAINER CLOSED AND AWAY FROM OPEN FLAMES. CAUSES BLACK STAINS ON FABRIC WHICH ARE DIFFICULT TO REMOVE.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AIR SUPPLIED EQUIPMENT IF EXPOSED TO HOT FUMES.
Ventilation:LOCAL EXHAUST TO CAPTURE OR REMOVE HOT FUMES.
Protective Gloves:OIL RESISTANT
Eye Protection:GOGGLES,
IF SPLASHING LIKELY
Other Protective Equipment:CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE.
Work Hygienic Practices:WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:NOT GIVEN
Melt/Freeze Pt:M.P/F.P
Text:NOT GIVEN
Vapor Pres:NOT GIVEN
Vapor Density:NOT GIVEN
Spec Gravity:0.95
Evaporation Rate & Reference:= 1 (BUTYL ACETATE=1)
Solubility in Water:IMMISCIBLE
Appearance and Odor:BLACK LIQUID, PETROLEUM OIL ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS (OXYGEN, CHLORINE).
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:CARBON MONOXIDE.

=====

Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS FOR WASTE PERTOLEUM
OIL IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. KEEP
OUT OF STREAMS AND WATERWAYS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate an

d

disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.