View NSN Online: https://aerobasegroup.tw/nsn/6750-01-354-2815

EASTMAN KODAK COMPANY -- 160 6854 KODAK ROYALPRINT FIXER AND REPLENISHER, SOLUTION -- 6750-01-354-2815

Product ID:160 6854 KODAK ROYALPRINT FIXER AND REPLENISHER, SOLUTION MSDS Date:03/04/1998 FSC:6750 NIIN:01-354-2815 Kit Part:Y MSDS Number: CHKZG === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14 650 Country:US Info Phone Num:716-477-3194 MSDS :800- 242-2424 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES Address:800 LEE RD Box:City:ROCHESTER State:NY ZIP:14650-3129 Country:US Phone:800-828-6203 CAGE:5K871

========

==== Composition/Information on Ingredients ==========

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 80-90% Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Ingred Name:AMMONIUM THIOSULFATE CAS:7783-18-8 RTECS #:XN6465000 Fraction by Wt: 5-15% Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM THIOSULFATE CAS:7772-98-7 RTECS #:XN6476000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM SULFITE (CERCLA) CAS:101 96-04-0 Fraction by Wt: 1 - 5% Other REC Limits:NONE RECOMMENDED EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:ACETIC ACID (CERCLA) CAS:64-19-7 RTECS #:AF1225000 Fraction by Wt: 100C Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN Vapor Pres:18 Vapor Density:0.6 Spec Gravity:1.05-1.15 pH:6.0 Evaporation Rate & amp; Reference:NOT GIVEN Solubility in Water:COMPLETE Appearance and Odor:COLORLESS LIQUID, SLIGHT ODOR. Percent Volatiles by Volume:85-90%

======== Stability and Reactivity Data

Stability Indicator/Materials to Avoid:YES
BASES, SODIUM HYPOCHLORITE (BLEACH), STRONG OXIDIZING AGENTS, STRONG ACIDS.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:AMMONIA, NITROGEN OXIDES, SULFUR DIOXIDE, CHLORAMINE.

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE AMOUNTS

OF WATER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to th eir

particular situation.