View NSN Online: https://aerobasegroup.tw/nsn/5610-00-236-4964

GIBSON-HOMANS CO -- BLACK JACK ALL WEATHER RF CMT -- 5610-00-236-4964

Product ID:BLACK JACK ALL WEATHER RF CMT MSDS Date:10/12/1990 FSC:5610 NIIN:00-236-4964 Status Code:A MSDS Number: CHXQB === Responsible Party === Company Name: GIBSON-HOMANS CO Address:1755 ENTERPRISE PARKWAY City:TWINSBURG State:OH ZIP:44087 Country:US Info Phone Num:216-467-8128 **Emergency Pho** ne Num:216-425-3255 CAGE:GIBHO === Contractor Identification === Company Name: GIBBSON-HOMANS CO Address:1755 ENTERPRISE PARKWAY Box:City:TWINSBURG State:OH ZIP:44087 Country:US Phone:216-467-8128 CAGE:0U534 Company Name: GIBSON-HOMANS CO Address:1755 ENTERPRISE PARKWAY City:TWINSBURG State:OH ZIP:44087 Country:US Phone:216-425-3255 CAGE:GIBHO

Ingred Name:STODDARD SOLVENT CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 10-30% O LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: SKIN: PROLONGED/REPEATED CONTACT MAY CAUSE IRRITATION. EYES: MAY CAUSE IRRITATION, BLURRED VISION. INHALATION: EXCESSIVE BREATHING OF HIGH VAPOR CONCENTRATIONS CAN CAUSE NASAL AND RES **PIRATORY I RRITATION,** DIZZINESS, NAUSEA, POSSIBLE UNCONSCIOUSNESS AND EVEN ASPHYXIATION. INGESTION: CAN CAUSE (EFTS OF OVEREXP) Explanation of Carcinogenicity:NOT RELEVANT. Effects of Overexposure: HLTH HAZ: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. Medical Cond Aggravated by Exposure: PRE-EXISTING LUNG AND SKIN **DISORDERS.** _____ First Aid: SKIN: WASH WITH SOAP AND WATER. EYES: FLUSH WITH LARGE

AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. INHALATION: REMOVE PERSON FROM AFFECTED AREA. IF BREATHING IS DIFFICULT ADMINISTER OXYGEN. IF BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION. INGESTION: DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION IMMEDIATELY.

Flash Point Method:PMCC Flash Point:105F,41C Lower Limits:0.8% Upper Lim its:7.0% Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICALS. Fire Fighting Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . WATER MAY CAUSE FROTHING, APPLY CAUTIOUSLY. Unusual Fire/Explosion Hazard:KEEP AWAY FROM SOURCES OF IGNITION.

Spill Release Procedures:DIKE SPILL AREA. RECOVER FREE LIQUID, ADD ABSORBENT TO SPILL AREA. REMOVE SOURCES OF IGNITION. VENTILATE AREA IF NECESSARY. Neutralizing A

gent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: KEEP AWAY FROM SOURCES OF IGNITION.
USE ONLY WITH ADEQUATE VENTILATION. AVOID PROLONGED/REPEATED CONTACT WITH SKIN.
Other Precautions: KEEP OUT OF THE REACH OF CHILDREN.

Respiratory Protection:NOT NORMALLY NEEDED IN WELL VENTILATED AREA. IF TLV IS EXCEEDED, A NIOSH APPROVED BREA THING APPARATUS IS RECOMMENDED. Ventilation:AS NECESSARY TO MAINTAIN EXPOSURE BELOW TLV LEVEL. Protective Gloves:OIL RESISTANT GLOVES. Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES . Other Protective Equipment:ANSI APPRVD EYE WASH & DELUGE SHOWER . AS NECESSARY. Work Hygienic Practices:REMOVE CONTAMINATED CLOTHING, LAUNDER BEFORE REUSE. Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

Boiling Pt:B. P. Text:>300F,>149C Vapor Pres:21 @ 25C Vapor Density:>1 Spec Gravity:1.1 Evaporation Rate & amp; Reference: