

NILES CHEMICAL PAINT CO. -- N-6483A 2K RED PRIMER T-IIIF#156 -- 8010-01-350-4745

=====
Product Identification
=====

Product ID:N-6483A 2K RED PRIMER T-IIIF#156

MSDS Date:12/03/1997

FSC:8010

NIIN:01-350-4745

Status Code:A

MSDS Number: CHXTB

=== Responsible Party ===

Company Name:NILES CHEMICAL PAINT CO.

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Info Phone Num:616-683-

3377

Emergency Phone Num:219-236-5856

Preparer's Name:MICHAEL LICHATOWICH

CAGE:02388

=== Contractor Identification ===

Company Name:NILES CHEMICAL PAINT

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Phone:616-683-3377/219-236-5856

CAGE:02388

=====
Composition/Information on Ingredients
=====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES

Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: SEVERE IRRITATION, LACRIMATION, REDNESS, BLURRED VISION; SKIN: REDNESS/IRRITATION, DEFATTING, LEADING TO DERMOTITIS INHALE: NASAL/RESP IRRITATION, CNS DEPRESSION, NAUSEA, HEADACHE, VERTIGO, UN CONSCIOUSNESS, ASPHYXIATION; SWALLOWING: GI IRRITATION, ABDOMINAL PAIN, NAUSEA, VOMITING, DIARRHEA.

Explanation of Carcinogenicity:NO

Effects of Overexposure:LIVER/KID

NEY/CNS/LUNG HAZZARDS. DUST MAY CAUSE PNEUMOCONIOSIS AND PLURAL THICKENING

=====
===== First Aid Measures =====

First Aid:INHALE: REMOVE TO FRESH AIR IMMEDIATELY; GIVE CPR; GET MEDICAL AID ASAP. SKIN: ** EYE: IMMEDIATELY FLUSH WITH MUCH WATER AT LEAST 15 MINUTES LIFTING UPPER/LOWER LIDS; GET MEDICAL AID IMMEDIATELY; DO NOT WEAR CONTACT LENSES WHILE WORKING. INGEST: DRINK 1 OR 2 GLASSES OF WATER; DO NOT INDUCE VOMITING; GET MEDICAL AID IMMEDIATELY; TREAT SYMPTOMATICALLY.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:107F,38C

Lower Limits:1.9

Upper Limits:12.0

Extinguishing Media:DRY CHEMICAL, FOAM, CO2

Fire Fighting Procedures:WEAR SCUBA WITH FULL FACEPIECE IN POSITIVE PRESSURE MODE; FULL PROTECTIVE CLOTHING; WATER MAY BE USED TO COOL CONTAINERS TO PREVENT EXPLOSION.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED; ISOLATE FROM ALL IGNITABLES; CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT; EXPOSURE TO DECOMP PRODUCTS MAY CAUSE HAZARDS.*

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITABLES; MINIMIZE ALL CONTACT WITH PRODUCT;DIKE; AVOID RUNOFF INTO SOIL, SEWERS, OR WATERWAYS. ABSORB WITH INERT MATERIAL SUCH AS CLAY, SOIL, OR A COMMERCIALY AVAILABLE ABSORBENT; SHOVEL INTO SALVAGE DRUMS FOR DISPOSAL.

=====
===== Handling and Storage =====

Handling and Storage

Precautions:AVLOID STORAGE IN HIGH TEMPERATURE AREAS OR NEAR IGNITABLES; KEEP CONTAINERS CLOSED; AVOID ROUGH HANDLING.

Other Precautions:EMPTY CONTAINERS MAY BE HAZARDOUS; DO NOT WELD/FLAME CUT ON EMPTY DRUMS; SHOCK FROM DROPPING MAY SPLIT CONTAINER.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR AN APPROPRIATE (TYPE TC-23C-75) PROPERLY FITTED HALF-MASK OR FULL FACEPIECE RESPIRATOR (NIOSH/MSHA).

Ventilation:SUFFICIENT VENTILATION REQUIRED; REMOVE DECOMP PRODUCTS FORMED DURING WELDING/FLAME CUTTING.

Protective Gloves:CHEMICAL RESISTANT NITRILE/VITON

Eye Protection:CHEMICAL SAFETY GOGGLES/FACE SHIELD.

Other Protective Equipment:CHEMICAL RESISTANT CLOTHING.

Work Hygienic Practices:WASH IMMEDIATELY UPON CONTAMINATION; REMOVE ANY WET CLOTHING AND WASH BEFORE REUSE; WASH BEFORE EATING, SMOKING, USING TOILET

Supplemental Safety and Health

VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG GROUND TO AN IGNITION SOURCE **S

KIN: IMMEDIATELY FLUSH WITH MUCH WATER. IMMEDIATELY REMOVE CONTAMINATED CLOTHING. FLUSH SKIN WITH WATER. GET MEDICAL AID WASH CLOTHING AND DECONTAMINATE SHOES BEFORE REUSE

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:242F,100C

Vapor Density:>AIR

Spec Gravity:1.216

Evaporation Rate & Reference: