View NSN Online: https://aerobasegroup.com/nsn/9150-00-186-6681

GARD CORPORATION

-- GARDFLEET SAE 30 MIL-L-2104F

MSDS Safety Information

FSC: 9150

NIIN: 00-186-6681 MSDS Date: 04/19/1999 MSDS Num: CJLVQ

Product ID: GARDFLEET SAE 30 MIL-L-2104F

MFN: 02

Responsible Party Cage: 3K676

Name: GARD CORPORATION Address: 2840 ROE LANE City: KANSAS CITY KS 66103 Info Phone Number: 913-236-5000

Emergency Phone Number: 913-236-5000, CHEMTREC 800-424-9300

Item Description Information

Item Manager: S9G

Item Name: LUBRICATING OIL, ENGINE

Specification Number: MIL-L-2104 Type/Grade/Class: GRADE 30

Unit of Issue: QT UI Container Qty: G Type of Container: CAN

Ingredients

Name: *** PROPRIETARY ***

Health Hazards Data

LD50 LC50 Mixture: NO INFORMATION GIVEN BY MFR ON THE MSDS.

Route Of Entry Inds - Inhalation: YES

Skin: NO Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO OSHA: NO

Effects of Exposure: EYE CONTACT: MAY CAUSE MILD EYE DISCOMFORT, TESRING, OR

BLEARING OF VISION. SKIN: REP

EATED CONTACT MAY LEAD TO AN ALLERGIC SKIN

SENEITIZATION. INHALATION: OVEREXPOSURE BY INHALATION OF HAOT MATERIAL MAY CAUSE NAUSEA, HEADACHE, OR WEAKNESS. INGESTION: DO NOT INGEST. ASPIRATION MAY LEAD TO CHEMICAL PNUMONITIS WHIC IS CHARACTERIZED BY PULMONARY EDEMA AND HEMORAGE AND MAY BE FATAL. GASTROINTESTINAL DISC OMFORT MAY DEVELOP. THIS PRODUCT HAS LAXATIVE PROPERTIES AND MAY RESULT IN ABDOMINAL CRAMPS AND DIARRHEA.

Explanation Of Carcinogenicity: MFR LISTED NO INFORMATION ABOUT THE

CARCINOGENICITY OF THIS MATERIAL. DOES NOT EXPECT IT TO BE CARCINOGENIC. Signs And Symptions Of Overexposure: EYE: IRRITATION, TEARING, OR BLURRING OF VOSION. SKIN: POSSIBLE IRRITATION, RASH, DERMATITIS. INHALED: RESPIRATORY IRRITATION, NAUSEA, HEADACHE, OR WEAKNESS. INGESTED: G/I IRRITATION, VOMITING, CRAM PS AND DIARRHEA. LUNG ASPIRATION MAY OCCUR. ASPIRATION MAY LEAD TO CHEMICAL PEUNMONITIS WHICH MAY BE FATAL. SIGNS OF LUNG INVOLVEMENT INCLUDE INCREASED RESPIRATORY RATE. IN

CREASED HEART RATE. COUGHING, CHOKING,

AND GAGGING ARE OFTEN NOTED AT TIME OF ASPIRATION.

Medical Cond Aggravated By Exposure: NO INFORMATION GIVEN BY MFR ON THE MSDS.

First Aid: IF IRRITATION PERSISTS OR IS SEVERE, SEE A DOCTOR. EYE:FLUSH W/WATER 15 MIN, HOLD LIDS OPEN.IF MATERIAL HOT TREAT FOR THERMAL BURNS. SKIN:WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING. IF MATE RIAL HOT SUBMERGE INJURED AREA IN COLD WATER, SEE A DOCTOR. INHALED:REMOVE TO FRESH AIR. AID/RESTORE BREA

THING IF NECESSARY. INGESTED:DO NOT INDUCE VOMITING. GIVE 2 LARGE GLASSES OF WATER TO DILUTE & LARGE GLASSES OF WATER TO DILUTE & LOWER HEAD MEDICAL CARE. NOTHING BY MOUTH IF UNCONSCIOUS. IF VOMITING OCCURS LOWER HEAD BELOW KNEES TO AVOID ASPIRATION.

Handling and Disposal

Spill Release Procedures: TURN OF ANY SOURCE OF IGNITION. EVACUATE AREA AND VENTILATE. PERSONNEL WITH PROPER PROTECTIVE EQUIPMENT SHO ULD CONTAIN SPILL

IMMEDIATELY WITH INERT MATERIALS SUCH AS SAND EARTH CHEMICAL SPILL PADS BY FORMING DIKES TO PREVENT MATERIAL FROM ENTERING SWERES AND WATER WAYS. LARGE SPILLS ONCE CONTAINED MAY BE PICKED UP BY VACUUM PUMPS, SHOVEL OR BUCKETS. DISPOSE OF IN SUITABLE CONTAINERS.

Neutralizing Agent: NO INFORMATION GIVEN BY MFR ON THE MSDS.

Waste Disposal Methods: ALL DISPOSALS MUST BE I/A/W FEDERAL, STATE & DISPOSALS MUST BE I/A/W FEDERAL & DISPOSALS MUS

ED WASTE.

IF SPILLED MATERIAL IS CLEANED UP USING A REGULATED SOLVENT, THE RESULT ING WASTE MAY BE REGULATED. DOT REGULATION MAY APPLY FOR TRANSPORTING THIS MATERIAL WHEN SPILLED.

Handling And Storage Precautions: DO NOT TRANSFER TO UNMARKED CONTAINERS. STORE IN CLOSED CONTAINERS AWAY FROM HEAT, SPARKS, OPEN FLAME, OR OXIDIZING MATERIALS.EMPTY CONATINERS RETAIN PRODUCT RESIDUE DO NOT PRESSURIZE, CUT, GLAZE, WEL D FOR ANY OTHER PURPOSE. RETURN DRUMS TO RECLAMATION CENTER FOR PROPER

CLEANING AND REUSE.

Other Precautions: KEEP FIRE EXTINGUISHERS READILY AVAILABLE. SEE NFPA 30 AND OSHA 1910.106.

Fire and Explosion Hazard Information

Flash Point Method: COC Flash Point: =242.8C, 469.F Autoignition Temp Text: N/D

Lower Limits: N/D Upper Limits: N/D

Extinguishing Media: DRY CHEMICAL, FOAM, WATER FOG OR CARBON DIOXIDE

Fire Fighting Procedures: WATER MAY BE INEFFECTIVE

BUT CAN BE USED TO COOL

CONTAINERS EXPOSED TO HEAT OR FLAME. CAUTION SHOULD BE EXERCISED WHEN USING WATER OR FOAM AS FROTHING AND SPLASHING MAY OCCUR., ESPECIALLY IF SPRAYED IN TO CONTAINERS OF HOT, BURNING LIQUID.

Unusual Fire/Explosion Hazard: DENSE SMOKE MAY BE GENERATED.TOXIC FUMES, GASES OR VAPORS MAY EVOLVE DURING BURNING.HEAVY FLAMMABLE VAPORS MAY SETTLE ALONG GROUND LEVEL AND LOW SPOTS TO CREATE AN INVISIBLE FIRE HAZARD. THE VAPORS MAY EXTEND TO SOURCES OF IGNITION AND FLASH BA

CK.

Control Measures

Respiratory Protection: NONE REQUIRED IF AIRBORNE CONCENTRATIONS ARE MAINTAINED BELOW THRESHOLD LIMITS.WEAR MSHA/NIOSH APPROVED (EQUIVALENT)HALF-MASK FORM DUST/MIST AIR PURIFYING RESPIRATOR.

Ventilation: MECHANICAL METHODS=FUME HOODS OR AREA FANS MAY BE USED TO REDUCE LOCALIZED VAPOR/MIST AREAS.

Protective Gloves: IMPERVIOUS GLOVES SUCH AS NEOPRENE OR NITRIL

E RUBBER

Eye Protection: SAFETY GLASSES W/SIDE SHIELDS OR VENTED/SPLASH PROOF GOGGLES

Other Protective Equipment: APRON AND OVERBOOTS OF CHEMICALLY IMPERVIOUS

MATERIALS NEOPRENE OR NITRILE RUBBER; IF HANDLING HOT MATERIAL USE INSULATED PROTECTIVE EQUIPMENT. EYE WASH STATIONS AND SHOWERS SHOULD BE AVAILABLE.

Work Hygienic Practices: LAUNDER SOILED CLOTHES.PROPERLY DISPOSE OF CONTAMINATED LEATHER ARTICLES AND OTHER MATERIALS WHICH CANNOT BE DECONTAMINATED.CONSUMPTION OF FOOD AND DRINK SHOUL

D BE AVOIDED IN WORK AREAS.

WASH HANDS/FACE

Supplemental Safety and Health: KEY2:KT

Physical/Chemical Properties

HCC: V6

NRC/State LIC No: NONE Boiling Point: >260.C, 500.F

B.P. Text: NOT DETERMINED EXPECT>260

M.P/F.P Text: UNKNOWN Decomp Text: UNKNOWN

Vapor Pres: 25C@1ATM NEGLIGIBLE

Vapor Density: >1AT STP Spec Gravity: 0.888@15C Viscosity: 10.3CST@100C Evaporation Rate &a

mp; Reference: NEG@STP BUTYL ACETATE=1

Solubility in Water: NEGLIGIBLE.

Appearance and Odor: DARK BROWN CLEAR FLUID. MILD PETROLEUM HYDROCARBON ODOR.

Percent Volatiles by Volume: NIL Corrosion Rate: UNKNOWN

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: AVOID HIGH TEMPERATURES AND PRODUCT CONTAMINATION

Materials To Avoid: AVOID CONTACT WITH ACIDS AND OXIDIZING

MATERIALS.

Hazardous Decomposition Products: SMOKE, CARBON MONOXIDE, DIOXIDE, AND OTHER ALDEHYDES OF INCOMPLETE COMBUSTION (C,ZN,CA,P AND S) HYDROGEN SULFIDE AND ALKYL MERCAPTANS AND OTHER SULFIDES MAY BE RELEASED

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: WILL NOT OCCUR

Toxicological Information

Toxicological Information: THIS PRODUCT CONTAIN PETROL

UM BASE OILS WHICH MAY BE

REFINED BY VARIOUS PROCESSES INCLUDING SEVERS SOLVENT EXTRACTION, SEVERE HYDROCRACKING, OR SEVERE HYDROTRATING. NONE OF THE OILS REQUIRE A CANCER W ARNING UNDER OSHA.THESE OILS HAVE NOT BEEN CLASSIFIED BY NTP, NOR HAVE THEY BEEN CLASSIFIED BY IARC AS CARCINOGENIC TO HUMANS.

Ecological Information

Ecological: THIS MATERIAL MAY BE TOXIC TO AQUATIC ORGAN

IZMS AND SHOULS BE KEPT

OUT OF SEWAGE AND DRAINAGE SYSTEMS AND ALL BODIES OF WATER.

MSDS Transport Information

Transport Information: DOES NOT APPLY TO BULK OIL SHIPPING NOR DOES IT APPLY TO

NON-BULK OIL SHIPPING.

Regulatory Information

Sara Title III Information: ACUTE

(IMMEDIATE HEALTH EFFECT):YES. CHRONIC: NO.

FIRE:NO. REACTIVITY:NO. PRESSURE(SUDDEN RELEASE HAZARD):NO. SECTION 313

TOXIC CHEMICALS: ZINC &It; 0.10%

Federal Regulatory Information: UNDER SECTION 311 OF THE CLEAN WATER ACT AND THE OIL POLLUTIN CONTROL ACT OF 1990. THIS MATERIAL IS CONSIDERED AIL OIL. ANY SPILLS OR DISCHARGES THAT PRODUCE A VISIBLE SHEEN OR FILM ON SURFACE OF WATER, OR IN WATERWAYS, DITCHES OR SEWERS LEADING TO SURFACE WATER MUST BE REPORTED. CONTANCT THE NATIONAL RE

SPONCE CENTER AT 800-424-8802

State Regulatory Information: RECOMMEND CONTACTING THE LOCAL AUTHORITIES IN THE EVENT OF ANY TYPE OF SPILL TO DETERMINE LOCAL REPORTING REQUIREMENTS AND ALSO TO AID IN THE CLEAN UP.

Other Information

Transportation Information

Responsible P arty Cage: 3K676 Trans ID NO: 148213

Product ID: GARDFLEET SAE 30 MIL-L-2104F

MSDS Prepared Date: 04/19/1999

Review Date: 09/13/1999

MFN: 2

Multiple KIT Number: 0 Unit Of Issue: QT Container QTY: G Type Of Container: CAN

Detail DOT Information

DOT PSN Code: ZZZ

DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=

Detail IMO Information

IMO PSN Code: ZZZ

IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

Detail IATA Information

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail AFI Information

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

HAZCOM Label

Product ID: GARDFLEET SAE 30 MIL-L-2104F

Cage: 3K676

Company Name: UNIMARK OIL COMPANY (FORMERLY GARD OIL)

Street: 2727 ROE LANE City: KANSAS CITY KS Zipcode: 66103-1543

Health Emergency Phone: 913-236-5000, CHEMTREC 800-424-9300

Label Required IND:

Υ

Date Of Label Review: 09/13/1999

Status Code: A
Origination Code: F
Signal Word: CAUTION
Health Hazard: Slight
Contact Hazard: Slight
Fire Hazard: Slight
Reactivity Hazard: None

Hazard And Precautions: EYE CONTACT: MAY CAUSE MILD EYE DISCOMFORT, TESRING, OR BLEARING OF VISION. SKIN: REPEATED CONTACT MAY LEAD TO AN ALLERGIC SKIN SENEITIZATION. INHALATION: OVEREXPOSURE BY INHALATION OF HAOT MATERIAL MAY CAUSE NAUSEA, HEADACHE, OR WEAKNESS. INGESTION: DO NOT INGEST. ASPIRATION MAY LEAD TO

CHEMICAL PNUMONITIS WHIC IS CHARACTERIZED BY PULMONARY EDEMA AND HEMORAGE AND MAY BE FATAL. GASTROINTESTINAL DISC OMFORT MAY DEVELOP. THIS PRODUCT HAS LAXATIVE PROPERTIES AND MAY RESULT IN ABDOMINAL CRAMPS AND DIARRHEA.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied

warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume respons

ibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.