View NSN Online: https://aerobasegroup.tw/nsn/5999-01-262-9041

Product ID:CS 3201 CLASS B BLACK (PART A) MSDS Date:06/13/1997 FSC:8030 NIIN:01-262-9041 Status Code:A **MSDS Number: CJZRQ** === Responsible Party === Company Name: FLAMEMASTER CORP THE CHEM SEAL DIV Address:11120 SHERMAN WAY City:SUN VALLEY State:CA ZIP:91352-4949 Country:US Inf o Phone Num:818-982-1650 Emergency Phone Num: (800) 424-9300 Chemtrec Ind/Phone:(800)424-9300 CAGE:14439 === Contractor Identification === Company Name: FLAMEMASTER CORP THE CHEM SEAL DIV Address:11120 SHERMAN WAY Box:City:SUN VALLEY State:CA ZIP:91352-4949 Country:US Phone:818-982-1650 CAGE:14439

Ingred Name:LIQUID POLYSULFIDE POLYMER CAS:68611-50-7 = Wt:65.

Health Hazards Acute and Chronic: POSSIBLE SKIN IRRITATION AFTER PROLONGED CONTACT, WITH RESULTING DERMATITIS. NOT CONSIDERED TO BE A PRIMARY SKIN IRRITANT.
Effects of Overexposure:SKIN OR IRRITATION.
======================================
First Aid:EYES-FLUSH WITH LARGE AMOUNTS OF WATER, CONSULT PHYSICIAN. SKIN-WASH WITH SOAP AND WATER. INGESTION- INDUCE VOMITING, CONSULT PHYSICIAN.
======================================
Flash Point Method:TCC Flash Point:=93.3C, 200.F 200F
Extinguishing Media:DRY CHEMICAL, FOAM, CO2, WATER.
======================================
Spill Release Procedures: SCOOP UP AND TRANSFER TO CONTAINER FOR REACTION WITH CURING AGENT. CLEANUP RESIDUE WITH AEROMATIC NAPHTHA/SAND/SWEEPING COMPOUND. WASH AREA WITH SOAP AND WATER.
======================================
Handling and Storage Precautions:STORE IN COOL DRY AREA AWAY FROM STRONG ACIDS.
Other Precautions:WASH HANDS BEFORE EATING, SMOKING OR DRINKING AFTER HANDLING THIS PRODUCT.
======================================
Respiratory Protection:NONE Ventilation:LOCAL EXHAUST: AIR. MECHANICAL: FAN. Protective Gloves:RUBBER Eye Protection:SAFETY GLASSES
Other Protective Equipment:APPROPRIATE TO AVOID PROLONGED CONTACT. Work Hygienic Practices:TRAIN EMPLOYEES IN SAFE HANDLING OF THIS PRODUCT. Supplemental Safety

and Health

Vapor Density:NIL Spec Gravity:1.50 Evaporation Rate & amp; Reference:1 Solubility in Water:NEGLEGABLE Appearance and Odor:BLACK PASTE, POLYSULFIDE ODOR.

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS AND STRONG ACIDS Stability Condition to Avoid:OPEN FLAME Hazardous Decomposition Products:H2S, CO, CO2, SO2, SMOKE.

\_\_\_\_\_

Waste Disposal Methods:REACT WITH CURING AGENT AND DISPOSE AS HAZARDOUS WASTE, NON-MIX, NON-HAZARDOUS.

Transport Information:UNIT CONTAINER: 6 OZ IN 1/2-PINT METAL CAN.SHIPPING NAME: ADHESIVE N.O.S. HAZARD CLASS: NON-HAZARDOUS UNIT CAONTAINER: 12 OZ IN 16 OZ METAL CAN. US POSTAL REGULATIONS: PARA 124.142 HARMFUL M ATTER. DISPOSAL INFO:

NCINERATION OR LAND DISPOSAL, MIXED WITH PART B, HAZARDOUS WASTE, NON-MIX, NON-HAZARDOUS. EPA CODE: CADO62064746. WASTE CHARACTERISTICS: SLUDGE. DISPOSAL METHODS: INCINER ATION OR LAND DISPOSAL, DISPOSE WASTE ACCORDING TO FEDERAL, STATE AND LOCAL REGULATIONS. APPLICABLE REGULATIONS: 49 CFR, IMO, IATA.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department

of Defense. The United States

of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.