

SHERWIN WILLIAMS CO. -- B44V20 HEAVY DUTY POLYURETHANE VARNISH -- 8010-00-604-2014

===== Product Identification =====

Product ID:B44V20 HEAVY DUTY POLYURETHANE VARNISH

MSDS Date:01/01/1991

FSC:8010

NIIN:00-604-2014

Status Code:A

MSDS Number: CKDGD

==== Responsible Party ===

Company Name:SHERWIN WILLIAMS CO.

Address:101 PROSPECT AVE N.W.

City:CLEVELAND

State:OH

ZIP:44115

Country:US

Info Phone Num:216

-566-2902

Emergency Phone Num:(216) 566-2917

CAGE:88573

==== Contractor Identification ===

Company Name:THE SHERWIN WILLIAMS CO. DIVERSIFIED BRANDS

Address:101 PROSPECT AVE N.W.

Box:City:CLEVELAND

State:OH

ZIP:44115

Country:US

Phone:(800)-832-2541/ EMER: 216-566-2917

CAGE:88573

===== Composition/Information on Ingredients =====

Ingred Name:ETHYLBENZENE

CAS:100-41-4

RTECS #:DA0700000

= Wt:9.

OSHA PEL:435 MG/M3;100 PPM

ACGIH TLV:434 MG/M3;100 PPM

ACGIH STEL:543 MG/M3;125 PPM

EPA

Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENE  
CAS:1330-20-7  
RTECS #:ZE2100000  
= Wt:51.  
ACGIH TLV:434 MG/M3;100 PPM  
ACGIH STEL:651 MG/M3;150 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE 2,4-DIISOCYANATE  
CAS:584-84-9  
RTECS #:CZ6300000  
= Wt:.8  
OSHA PEL:C0.14 MG/M3;C.02 PPM  
ACGIH TLV:0.036 MG/M3;.005 PPM  
ACGIH STEL:0.14 MG/M3;0.02 PPM  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

Ingred Name:TOLUENE DIISOCYANATE POLYMER  
= Wt:40.

===== Hazards Identific  
ation =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: IRRITATION OF EYES, SKIN &  
RESPIRATORY SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. MAY RESULT  
IN DEATH.

Explanation of Carcinogenicity:TOLUENE DIISOCYANATE IS A SUSPECTED  
HUMAN CARCINOGEN.

Effects of Overexposure:IRRITATION, UNCONSCIOUSNESS, HEADACHE,  
DIZZINESS, NAUSEA, LOSS OF COORDINATION, REDN  
ESS, ITCHING, BURNING  
SENSATION.

Medical Cond Aggravated by Exposure:SENSITIVITY TO ISOCYANATES,  
LUNG/BREATHING PROBLEMS

===== First Aid Measures =====

First Aid:INHALATION: LEAVE THE AREA & GET FRESH AIR. SKIN: WASH  
THOROUGHLY W/SOAP & WATER. EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR  
15 MINS. OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point:=23.3C, 74.F  
Lower Limits:1

Upper Limits:7

Extinguishing Media:CO2, DRY CHEMICAL, FOAM

Fire Fighting Procedures:USE FULL PROTECTIVE EQUIP/SCBA. WATER SPRAY:

INEFFECTIVE. FOG NOZZLES: PREFERABLE. USE WATER TO COOL FIRE

EXPOSED CONTAINERS TO PREVENT PRESSURE BUILDUP.

Unusual Fire/Explosion Hazard:KEEP CLOSED CONTAINERS TIGHTLY CLOSED.

ISOLATE FROM IGNITION SOURCES. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS.

===== Ac  
cidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA. ALL PERSONNEL IN THE AREA SHOULD BE PROTECTED. COVER RELEASE W/ABSORBENT MATERIAL. DEACTIVATE MATERIAL W/A 10% AMMONIUM HYDROXIDE SOLUTION (HOUSEHOLD AM MONIA) COVER LOOSELY. WASH AREA W/SOAP & WATER.

Neutralizing Agent:10% AMMONIUM HYDROXIDE SOLUTION

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY  
FROM IGNITION SOURCES.

DURING USE & UNTIL ALL VAPORS ARE GONE; KEEP AREA VENTILATED, DON'T SMOKE. USE APPROVED BONDING & GROUNDING PROCEDURES. KEEP CONTAINERS CLOSED WHEN NOT IN USE. TRANSFER ONLY TO APPROVED CONTAINERS W/COMPLETE & APPROPRIATE LABELING. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:AVOID CONTACT W/SKIN/EYES/BREATHING VAPOR/SPRAY MIST. TRANSFER ONLY TO APPROVED CONTAINERS. DON'T TAKE INTERNALLY. EXTINGUISH FLAMES/PILOT LIGHTS/HEATERS. TURN OFF STOVES  
/ELEC  
TOOLS/APPLIANCES. CONTEN TS ARE FLAMMABLE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA TC19C POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR, WHERE OVERSPRAY IS PRESENT. IF UNAVAILABLE, USE NIOSH/MSHA PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR. USE NIOSH/MSHA RESPIRATOR, WHEN SANDING/ABRADING THE DRIED FILM.

Ventilation:LOCAL EXHAUST: PREFERABLE. MECHANICAL: ACCEPTABLE IF THE EXPOSURE TO MATERIALS

IS MAINTAINED BELOW APPLICABLE EXPOSURE

LIMITS.

Protective Gloves:RECOMMENDED

Eye Protection:SAFETY GLASSES W/UNPERFORATED SIDESHIELD

Other Protective Equipment:BARRIER CREAM

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE  
REUSE. WASH HANDS AFTER USING.

Supplemental Safety and Health

BOILING RANGE: 277-292F. INTENTIONAL MISUSE BY DELIBERATELY  
CONCENTRATING & INHALING THE CONTENTS CAN BE HARMFUL/ FATAL. NO  
PERSON SHOULD USE THIS PRODUCT/ BE IN THE AREA WHERE IT  
IS BEING  
USED, IF THEY HAVE CHRONIC (LONG TERM) LUNG/ BREATHING PROBLEMS/  
IF THEY EVER HAD A REACTION TO ISOCYANATES.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:277-292F

Vapor Density:>1

Spec Gravity:0.96

VOC Grams/Liter:4.8

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:66

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER/ALCOHOLS/AMINES

/OTHER COMPOUNDS WHICH REACT W/ISOCYANATES

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME, HOT SURFACES/  
OTHER SOURCES OF IGNITION

Hazardous Decomposition Products:BY FIRE: CO<sub>2</sub>, CO, OXIDES OF NITROGEN,  
HYDROGEN CYANIDE

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DON'T  
INCINERATE CLOSED CONTAINER. DISPOSE OF IN ACCORDANCE  
W/FED/STATE/LOCAL REGS REGARDING POLLUTION. WASTE MAY BE HAZARDOUS  
U

NDER RCRA & MUST BE TESTED FOR IGNITABILITY TO DETERMINE EPA  
HAZARDOUS WASTE NUMBERS.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing t

his

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.