

DISTEC INC -- TFL 50 DRY LUBE (SEE SUPPLEMENTAL) -- 9150-01-339-6225

===== Product Identification =====

Product ID:TFL 50 DRY LUBE (SEE SUPPLEMENTAL)

MSDS Date:04/29/1999

FSC:9150

NIIN:01-339-6225

MSDS Number: CKJHQ

=== Responsible Party ===

Company Name:DISTEC INC

Address:INTNTL ENTERPRISE PK BDG 777 939 BARNUM

City:BRIDGEPORT

State:CT

ZIP:06608

Country:US

Info Phone Num:203-334-0383

Emergency Ph

one Num:800-643-6735

Chemtrec Ind/Phone:(800)424-9300

CAGE:0TGR5

=== Contractor Identification ===

Company Name:DISTEC INC

Address:914 ARTIC STREET BLDG #777

Box:City:BRIDGEPORT

State:CT

ZIP:06608

Country:US

Phone:203-334-0383 / 800-643-6735

Contract Num:SP0450-00-W-2022

CAGE:0TGR5

Company Name:WET N DRY LUBES INC

Address:242 N JAMES ST RM 106

Box:City:WILMINGTON

State:DE

ZIP:19804

Country:US

Phone:302-995-7537

CAGE:0NH67

===== Composition/Information on Ingredients =====

Ing

red Name:SOLVENT NAPHTHA, LIGHT ALIPHATIC
CAS:64742-89-8
< Wt:30.

Ingred Name:FLUOROCARBON TELOMER
< Wt:10.

Ingred Name:PROPANE (20 % OF PROPELLANT)
CAS:74-98-6
RTECS #:TX2275000
< Wt:14.
Code:F
OSHA PEL:1800 MG/M3;1000 PPM

Ingred Name:ISOBUTANE (80 % OF PROPELLANT)
CAS:75-28-5
RTECS #:TI4300000
< Wt:56.
Code:F

Ingred Name:PROPELLANT (PROPANE + ISOBUTANE = TOTAL PROPELLANT)
< Wt:70.

===== Hazards Identification =====

Routes of Entry: Inhalat
ion:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SHORT TERM: INHALATION: MAY CAUSE
IRRITATION OF RESPIRATORY TRACT, NAUSEA, DIZZINESS, HEADACHE, AND
DEPRESSION OF THE CENTRAL NERVOUS SYSTEM, AND IRREGULAR HEARTBEAT.
INTENTIONAL MISUSE OF THIS PRODUC T BY DELIBERATELY CONCENTRATING
AND INHALING CAN BE HARMFUL OR FATAL. INGESTION: MAY CAUSE
GASTROINTESTINAL IRRITATION AND DEPRESSION OF THE CENTRAL NERVOUS
SYSTEM. SKIN CONTACT: MAY CAUSE IRRITATION. EYE CONTACT: MAY CAUSE
IRRITATION. LONG TERM: PROLONGED OR REPEATED CONTACT MAY CAUSE
DERMITITIS. MAY CAUSE SKIN IRRITATION ON PROLONGED OR REPEATED
CONTACT.
Effects of Overexposure:INHALATION: IRRITATION OF RESPIRATORY TRACT,
NAUSEA, DIZZINESS, HEADACHE, AND DEPRESSION OF CENTRAL NERVOUS
SYSTEM, AND IRREGULAR HEARTBEAT. DELIBERATELY CONCENTRATING AND
INHALING CAN BE HARMFUL OR FATAL. INGESTION: GASTROINTESTINAL
IRRITATI

ON, AND DEPRESSION OF CENTRAL NERVOUS SYSTEM. SKIN
CONTACT: IRRITATION, DERMATITIS. EYE CONTACT: IRRITATION.
Medical Cond Aggravated by Exposure:NONE RECOGNIZED.

===== First Aid Measures =====

First Aid:INHALATION: IF USER EXPERIENCES BREATHING DIFFICULTY, MOVE TO
AIR FREE OF VAPORS. ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION
UNTIL MEDICAL ASSISTANCE CAN BE RENDERED. INGESTION: DO NOT INDUCE
VOMITIN G. CALL POISON CONTROL CENTER, HOSPITAL
, EMERGENCY ROOM, OR
PHYSICIAN IMMEDIATELY. SKIN CONTACT: WASH WITH SOAP AND WATER. EYE
CONTACT: FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15
MINUTES. IF IRRITATION FROM CONTACT PERSISTS, GET MEDICAL
ATTENTION.

===== Fire Fighting Measures =====

Flash Point:FLAMM. AEROSOL
Extinguishing Media:USE CARBON DIOXIDE, DRY POWDER, OR FOAM.
Fire Fighting Procedures:EXTREMELY FLAMMABLE AEROSOL! CONTENTS UNDER
PRESSURE. DO NOT PUNCTURE, INCI
NERATE OR STORE ABOVE 120 F.
EXPOSURE TO HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE BURSTING.
ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, OPEN FLAMES AND
HOT SURFACE.
Unusual Fire/Explosion Hazard:SELF-CONTAINED RESPIRATORY PROTECTION
SHOULD BE PROVIDED FOR FIREFIGHTERS FIGHTING FLAMES IN BUILDINGS OR
CONFINED AREAS. STORAGE CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT
COOL WITH WATER TO PREVENT P RESSURE BUILD-UP.

===== Accidental Release Measures ====
=====

Spill Release Procedures:AVOID BREATHING VAPORS. VENTILATE AREA. FLUSH
LARGE SPILLS OF MATERIAL INTO SUITABLE RETAINING AREA OR CONTAINERS
WITH LARGE QUANTITIES OF WATER. SMALL SPILL CAN BE ABSORBED BY
APPROPRIATE INERT ABSOR BENT.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE NEAR FLAMES OR AT
ELEVATED TEMPERATURES.
Other Precautions:READ CAREFULLY ALL CAUTIONS AND DIRECTIONS ON PRODUCT
LA

BEL BEFORE USE. SINCE EMPTY CONTAINER RETAINS RESIDUE, FOLLOW ALL LABEL WARNINGS EVEN AFTER CONTAINER IS EMPTY. DISPOSE OF EMPTY CONTAINER ACCORDING TO LOCAL REGULATIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FOR OSHA CONTROLLED WORK PLACE, USE ONLY WITH ADEQUATE VENTILATION UNDER ENGINEERED AIR CONTROL SYSTEMS DESIGNED TO PROVIDE MAXIMUM APPROPRIATE TLV. FOR OCCASIONAL USE WHERE ENGINEERED AIR CONTROL IS NOT FEASIBLE,

USE NIOSH APPROVED

RESPIRATORS. FOR OCCASIONAL CONSUMER USE, USE ONLY WITH ADEQUATE VENTILATION.

Ventilation:ADEQUATE VENTILATION MUST BE PROVIDED. SEE RESPIRATORY PROTECTION ABOVE.

Protective Gloves:USE IMPERMEABLE GLOVES TO PREVENT SKIN IRRITATION.

Eye Protection:SAFETY GLASSES, CHEMICAL GOGGLES AND/OR FACE SHIELDS ARE RECOMMENDED.

Other Protective Equipment:USUALLY NONE REQUIRED.

Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER USE. BEFORE REUSE, THOROUGHLY CLEAN ANY CL

OTHING OR PROTECTIVE EQUIPMENT WHICH HAS BEEN CONTAMINATED BY PRIOR USE.

Supplemental Safety and Health

PRODUCT NUMBER: 60132-5 OZ AND 60133-10 OZ

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:>85.C, 185.F

B.P. Text:185-230F

Vapor Density:>AIR

Spec Gravity:0.846 (7.058 LBS/GAL)

Evaporation Rate & Reference:SLOWER THAN ETHER.

Appearance and Odor:5.0 FLUID OZ/ SPRAY CAN. TWELVE 5 OZ SPRAY CANS PER BOX.

Percent Volatiles by Volume:95.0

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY PRODUCE HYDROGEN CHLORIDE, HYDROGEN FLUORIDE, AND SMALL AMOUNTS OF PHOSGENE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH APPLICABLE LOCAL, STATE, AND FEDERAL REGULATION

S.

===== MSDS Transport Information =====

Transport Information:DOT CONSUMER COMMODITY ORM-D

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.