View NSN Online: https://aerobasegroup.com/nsn/6140-00-410-2632

## EXIDE CORP -- 4DLT-DRY, BATTERY, STORAGE, DRY -- 6140-00-410-2632

============ Product Identification ==============

Product ID:4DLT-DRY, BATTERY, STORAGE, DRY

MSDS Date:04/01/1996

FSC:6140

NIIN:00-410-2632

Status Code:A

MSDS Number: CKSGT
=== Responsible Party ===
Company Name: EXIDE CORP

Address:645 PENN STREET

Box:14205 City:READING

State:PA

ZIP:19612-4205

Country:US

Info Phone Num:610-378-0500/0798

**Emergency** 

Phone Num:610-378-0500/800-424-9300(CHEMTREC)

CAGE:20038

=== Contractor Identification ===

Company Name: ADVANCED INDUSTRIES INC

Address:415 NORTHCUTT STREET

Box:5666

City:LONGVIEW

State:TX ZIP:75608 Country:US

Phone:214-236-4101

CAGE:0GA21

Company Name: BATTERY OUTLET INC

Address: 1608 CAMPOSTELLA RD

Box:City:CHESAPEAKE

State:VA ZIP:23324 Country:US

Phone:757-545-4442

Contract Num:SP0413-00-M-0837

CAGE:0FGN2

Company Name: ENERSYS INC

Address:8306PATUXENT RANGE RS SUITE 103

Box:City:JESSUP

State:MD

ZIP:20794-8609 Country:US

Phone:301-381-8500 OR 215-378-0757

CAGE:90660

Company Name: EXIDE CORP Address: 645 PENN STREET

Box:14205 City:READING State:PA

ZIP:19612-4205 Country:US

Phone:610-378-0500/0798

CAGE:20038

Company Name: EXIDE CORP/YUASA EXIDE INC.

Address:645 PENN STREET

Box:14145 City:READING

State:PA

ZIP:19612-4205 Country:US

Phone:610-378-0550/208-1975

CAGE:KO556

======= Composition/Information on Ingredients ========

Ingred Name: LEAD (SARA 313) (CERCLA)

CAS:7439-92-1

**RTE** 

CS #:OF7525000

Fraction by Wt: 92 - 93%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:SEE 1910.1025 ACGIH TLV:0.05MG/M3, A3; 9596

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: ANTIMONY (SARA 313) (CERCLA)

CAS:7440-36-0

RTECS #:CC4025000 Fraction by Wt: 0.2%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:0.5 MG/M3

ACGIH TLV:0.5 MG (SB)/M3; 9596

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: ARSENIC (SARA 313) (CERCLA)

CAS:7440-38-2

RTECS #:CG0525000 Fraction by Wt: 0.003% Other REC Limits:NONE RECOMMENDED

OSHA PEL:SEE 1910.1018

ACGIH TLV:0.01 MG/M3, A1; 9596

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: CALCIUM, METAL

CAS:7440-70-2

RTECS #:EV8040000 Fraction by Wt: 0.02%

Other REC Limits: NONE RECOMMENDED

Ingred Name:TIN CAS:7440-31-5

RTECS #:XP7320000 Fraction by Wt: 0.06%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9596

Ingred Name: CASE MATERIAL (INCLUDING INGREDIENTS 7 AND 8)

Fraction by Wt: 6 - 8%

Other REC Limits: NONE RECOMMENDED

Ingred Name:POLYPROPY

LENE

CAS:9003-07-0

RTECS #:TR5000000 Fraction by Wt: SEE # 6%

Other REC Limits: NONE RECOMMENDED

Ingred Name: HARD RUBBER Fraction by Wt: SEE # 6%

Other REC Limits: NONE RECOMMENDED

========= Hazards Identification =============

LD50 LC50 Mixture: NONE WHILE DRY.

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:NONE UNDER NORMAL USE.

ACUTE- INTERNAL COMPONENTS CONTAI

N LEAD. IF HEATED/BURNED, LEAD

FUME/DUST CAN CAUSE POISONING, RESPIRATORY & LUNGS IRRITATION. MAY CAUSE EYE IRRITATION. TOXIC IF I NGESTED. LEAD ACCUMULATES IN BONE & BODY ORGANS. CHRONIC- ANEMIA, NERVE & KIDNEY DAMAGE, REPRODUCTIVE CHANGES.

Explanation of Carcinogenicity: CONTAINS LEAD.

Effects of Overexposure:IF BATTERY IS BROKEN/HEATED OR IN FIRE:IRRITATION, HEADACHE, NAUSEA, VOMITING, FATIGUE, WEIGHT LOSS, ANEMIA, PAIN IN LEGS, ARMS AND JOINTS, COUGHING, SEVERE ABDOMIN

AL

CRAMPING AND PAIN, LOSS OF APPETI TE, SLEEP DISTURBANCES AND IRRITABILITY

Medical Cond Aggravated by Exposure:IF BROKEN OR IN FIRE: PREGNANT WOMEN AND CHILDREN MUST BE PROTECTED FROM LEAD EXPOSURE. LEAD AND ITS COMPOUNDS CAN AGGRAVATE PRE-EXISTING KIDNEY, LIVER AND NEUROLOGICAL DISEASES.

First Aid:NONE UNDER NORMAL USE. IF LEAD EXPOSURE IS SUSPECTED OR BATTERY IS IN FIRE: EYE:IMMEDIATELY FLUSH WITH WATER FOR 15

MINUTES. HOLD EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. INHALED:MOVE TO FRESH AIR. PROVIDE OXYGEN/CPR IF NEEDED. ORAL:CALL PHYSICIAN IMMEDIATELY.

============ Fire Fighting Measures ==============

Flash Point:NONE

Lower Limits:NOT RELEVANT Upper Limits:NOT RELEVANT


Extinguishing Media:CARBON DIOXIDE, SAND, FOAM/DRY CHEMICAL. WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL. Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND

NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:BATTERY CELLS MAY RUPTURE WHEN EXPOSED TO EXCESSIVE HEAT. HYDROGEN GAS, IF PRESENT, IS EXPLOSIVE/FLAMMABLE. MAY FORM TOXIC DUSTS OR FUMES.

======== Accidental Release Measures ===========

Spill Release Procedures:IF BROKEN, LEAD DUST SHOULD BE VACUUMED (USING HEPA FILTER) OR WET-SWEPT. DO NOT DRY SWEEP OR USE FORCED AIR.



====== Disposal Considerations ===========

Waste Disposal Methods:SEND TO SECONDARY LEAD SMELTER FOR RECYCLING. OBSERVE LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any p erson utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.