View NSN Online: https://aerobasegroup.com/nsn/8010-00-926-1488

Product ID:AP-582 MSDS Date:01/01/1987 FSC:8010 NIIN:00-926-1488 Status Code:A MSDS Number: CKSYN === Responsible Party === Company Name: INMONT CORP. Address:1255 BROAD STREET Box:698 City:CLIFTON State:NJ ZIP:07013-4219 Country:US Info Phone Num:201-365-3511 EX12 Emergency Phone Num:201-365-3511 EX12 CAGE:9C182 === C ontractor Identification === Company Name: INLAND SPECIALTY CHEM CORP SUB OF GREAT LAKE CHEM Address:3151 AIRWAY AVE SUITE J-3 Box:City:COSTA MESA State:CA ZIP:92626-4617 Country:US CAGE:59987 Company Name: INMONT CORP. Address:1255 BROAD STREET Box:698 City:CLIFTON State:NJ ZIP:07013-4219 Country:US Phone:201-365-3511 EX12 CAGE:9C182 

Ingred Name:METHYLENE CHLORIDE (SARA III) CAS:75-09-2 RTECS #:PA8050000 Fraction by Wt: 50% O SHA PEL:500 PPM/C,1000; Z2 ACGIH TLV:50 PPM, A2; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:PERCHLOROETHYLENE (TETRACHLOROETHYLENE) (SARA III) CAS:127-18-4 RTECS #:KX3850000 Fraction by Wt: 2% OSHA PEL:100 PPM ACGIH TLV:25PPM/100,A3 STEL;94 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name:PHENOL CAS:108-95-2 RTECS #:SJ3325000 Fraction by Wt: 17% OSHA PEL:S, 5 PPM ACGIH TLV:S, 5 PPM; 8990 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:SODIUM CHROMATE (SARA III) CAS: 7775-11-3 RTECS #:GB2955000 Fraction by Wt: 1% OSHA PEL:0.1 PPM CRO3;CEILING ACGIH TLV:0.05 MG CR/M3; 9192 EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

Effects of Overexposure:INHAL:HEADACHE,DIZZINESS, NAUSEA. SKIN:SEVERE BURNS, LOSS OF SKIN COLOR.EYES:SEE SUPP DATA

First Aid:INHALATION:REMOVE TO FRESH AIR.GIVE ARTIF.RESP.GIVE OXYGEN AFTER BREATHING START

S.C/	ALL DOCTOR.EYES:FLUSH IMMEDIATELY W/WATER
F	OR 15 MIN.CALL DOCTOR.SKIN:WASH W/SOAP AND WATER FOLLOWED BY
R	UBBING.SEE S UPP DATA

Extinguishing Media:CO\*2, DRY CHEMICAL, FOAM OR WATER FOG Fire Fighting Procedures:REMOVE SEALED DRUMS FROM VICINTY OF FIRE. SEALED DRU

Unusual Fire/Explosion Hazard:MS HEATED BY FLAM OR HIGH TEMP. CAN RUPTURE.TOXIC CHLORINE OXIDES PRODUCED

====== Accidental Re

lease Measures ===============

Spill Release Procedures: VENTILATE AREA. ABSORB AND DISPOSE OF IN ACCORDANCE WITH LOCAL APPLICABLE REGULATIONS.

Handling and Storage Precautions: TRANSPORT AND STORE IN CLOSED CONTAINERS AT TEMPETATURES BETWEEN 40F AND 95F. DO NOT STORE IN DIRECT SUN, HEAT, FRESH AIR INTAKES OR UNVENTILATED AREAS. Other Precautions: OPEN BUNGS CAUTIOUSLY TO AVOID SPURTING

Respiratory Protection:NOT REQUIRED UNDER NORMAL OPERATING CONDITIONS. Ventilation:USE DOWN DRAFT IF APPLIED BY SPRAY Protective Gloves:SOLVENT RESIST Eye Protection:FACE SHIELD OR GLASSES Other Protective Equipment:SOLVINT RESISTANT APRON AND BOOTS. Supplemental Safety and Health SEVER CHEMICAL BURNS.INGESTION:POISON. ALCOHOL. INGESTION:CALL DOCTOR.INDUCE VIMITING WITH SALT WATER,THEN GIVE BAKING SODA SOLUTION.LIE DOWN,COVER EYE

HCC:T4 Boiling Pt:B.P. Text:110F,43.3C Vapor Pres:137 Vapor Density:1.52 Spec Gravity:1.2000 Evaporation Rate & amp; Reference:212F,100C TCC Appearance and Odor:THICK YELLOW BROWN TO BROWN EMULSION-PHENOLIC ODOR Percent Volatiles by Volume:77.5

Stability Indicator/Materials to Avoid:YES STRONG ACIDS AND STRONG OXIDIZERS. Hazardous Decomposition Products:TOXIC OXIDES OF CHLO Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL APPLICABLE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.