MASTER AUTOMOTIVE GROUP -- BTC-8, BATTERY TERMINAL CLEANER -- 6850-01-332-7633

Product ID:BTC-8, BATTERY TERMINAL CLEANER MSDS Date:09/01/1996 FSC:6850 NIIN:01-332-7633 Status Code:A MSDS Number: CLCQY === Responsible Party === Company Name: MASTER AUTOMOTIVE GROUP Box:381900 **City:GERMANTOWN** State:TN ZIP:38138-1900 Country:US Info Phone Num:901-757-5700 Emergency Phone Num:800-255-3924 Preparer's Name:ESP CAGE:UO444 === Contractor Identification === Company Name: AUGUSTA ENGINE PARTS CO INC Address:2622 MILLEDGEVILLE ROAD Box:City:AUGUSTA State:GA ZIP:30904 Country:US Phone:706-736-1288 Contract Num:SP0400-01-A-AF95-0103 CAGE:1JQZ6 Company Name: MASTER AUTOMOTIVE GROUP Address:Box:381900 **City:GERMANTOWN** State:TN ZIP:38138-1900 Country:US Phone:901-757-5700 CAGE:UO444

======= Composition/Information on Ingredients ==========

Ingred Name:PETROLE

UM DISTILLATE CAS:64742-88-7 = Wt:15. OSHA PEL:400 PPM

Ingred Name:PROPANE CAS:74-98-6 RTECS #:TX2275000 = Wt:2. OSHA PEL:1800 MG/M3;1000 PPM

Ingred Name:BUTANE CAS:106-97-8 RTECS #:EJ4200000 = Wt:2. OSHA PEL:800 PPM ACGIH TLV:1900 MG/M3;800 PPM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: EYES: IRRITANT. SKIN: IRRITANT.
CONTACT MAY DRY THE SKIN; PROLONGED CONTACT MAY CAUSE IRRITATION.
CAN BE ABSORBED. SOLVENT ACTION CAN DRY AND DEFAT THE SKIN CAUSING THE SKIN TO CRACK, LEADING T O DERMATITIS. INGESTION: NOT A LIKELY ROUTE OF EXPOSURE. CHRONIC:UNKINOWN
Effects of Overexposure:EYES: IRRITATION. SKIN: IRRITATION, DEFATTING, CRACKING, DERMATITIS. INHALATION: RESPIRATORY IRRITATION, HEADACHE, NAUSEA, FATIGUE, DROWINESS, IMPAIRED CO-ORDINATION.

=

First Aid:INHALATION: REMOVE TO FRESH AIR, ADMINISTER OXYGEN IF NEEDED. APPLY ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. GET MEDICAL ATTENTION. SKIN: WIPE OFF WITH TOWEL. WASH WITH SOAP AND WATER. GET MED ICAL ATTENTION IF IRRITATION PERSISTS. EYES: WASH IMMEDIATELY WITH LARGE VOLUMES OF FRESH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.

Flash Point Method:CALC Flash Point:=-104.4C, -156.F ESTIMATED. Lower Limits:.9 Upper Limits:9.5 Extinguishing Media: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG. Fire Fighting Procedures: WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP AND EXPLOSION WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, FOG NOZZLES PREFERRED. WEAR GOGGLES AND SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard: CLOSED CONTAIN ERS MAY EXPLODE FROM INTERNAL PRESSURE BUILD-UP WHEN EXPOSED TO EXTREME HEAT AND DISCHARGE CONTENTS, LIQUID CONTENT OF CONTAINER WILL NOT SUPPORT COMBUSTION. OVEREXPOSURE TO DECOMPSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE READILY APPARENT.

Spill Release Procedures: AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE ALL SOURCES OF IGNITION. CLEAN UP AREA WITH ABSORBENT MATERIAL AND PLACE

IN CLOSED CONTAINERS FOR DISPOSAL.

Handling and Storage Precautions:STORE AND USE IN COOL, DRY,
WELL-VENTILATED AREAS. DO NOT STORE ABOVE 120F. DO NOT PUNCTURE OR
INCINERATE (BURN) CANS. DO NOT STICK PIN, NAIL OR ANY OTHER SHARP
OBJECT INTO OPENING ON TOP OF CAN. DO N OT SPRAY IN EYES. DO NOT
TAKE INTERNALLY. SEE PRODUCT LAVEL FOR ADDITIONAL INFORMATION.
Other Precautions:THE STORAGE OF NON-FLAMMABLE PRODUCTS
WITH

NON-FLAMMABLE OR FLAMMABLE PRESSURIZING AGENTS, IN CARTONS, IS THE SAMEAS FOR ORDINARY CANNED GOODS IN CARTONS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE UNDER NORMAL USE. AVOID BREATHING VAPORS. IN RESTRICTED AREAS, USE APPROVED CHEMICAL/MECHANICAL FILTERS DESIGNED TO REMOVE A COMBINATION OF PARTICLES AND VAPOR. IN CONFINED AREAS, USE APPROVED AIR LINE TYPE RESPIRATOR OR HOOD. SELF-CONTAINED BREATHING APPAR ATUS IS REQUIRED FOR VAPOR CONCENTRATIONS ABOVE PEL/TLV LIMITS. Ventilation:PROVIDE ADEQUATE GENERAL DILUTION AND/OR LOCAL EXHAUST VENTILATION TO KEEP PEL/TLV OF HAZARDOUS INGREDIENTS BELOW ACCEPTABLE LIMIT AND LEL BELOW STATED LIMIT. Protective Gloves:NONE UNDER NORMAL USE, SOLVENT RESISTANT FOR PROLONGED OR REPEATED CONTACT. Eye Protection:NONE UNDER NORMAL USE,SAFETY GLASSES,SPLASH GUARD,FULL FACE SHIELD RECOMMENDED. Other Protective Equipment:NONE UNDER NORMAL USE. HOWEVE R, USE OF SOLVENT RESISTANT APRONS OR OTHER CLOTHING IS RECOMMENDED. EYE WASH AND SAFETY SHOWERS IN THE WORKPLACE ARE RECOMMENDED. Supplemental Safety and Health

HCC:V3 Boiling Pt:=-42.2C, -44.F B.P. Text:PROPELLANT Vapor Density:UNK Spec Gravity:0.94 (H2O=1) Solubility in Water:COMPLETE Appearance and Odor:AEROSOL PRODUCT

Stability Indicator/Materi als to Avoid:YES OXIDIZING AGENTS. Stability Condition to Avoid:APPLICATION TO HOT SURFACES. STORAGE ABOVE 120F. EXPOSURE TO OPEN FLAME. Hazardous Decomposition Products:MAY PRODUCE FUMES WHEN HEATED TO

DECOMPOSITION. FUMES MAY CONTAIN CARBON MONOXIDE. Conditions to Avoid Polymerization:WILLNOT OCCUR.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS, BEFORE ATTEMPTING CLEAN

UP, REFER TO OTHER SECTIONS OF THIS MSDS FOR HAZARD CAUTION INFORMATION.

SARA Title III Information:NO TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE I I I AND OF 40 CFR 372 ARE PRESENT.

State Regulatory Information:

Disclaimer (provided with this information by the compiling agencies):

This information is formu

lated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.