View NSN Online: https://aerobasegroup.tw/nsn/6850-01-439-7872

EASTMAN KODAK COMPANY -- 150 0719,CONC,KODAK DEVELOPER SYSTEM CLEANER(SEE SUPPL DATA) -- 6850-01-439-7872

============= Product Identification ==================

Product ID:150 0719, CONC, KODAK DEVELOPER SYSTEM CLEANER (SEE SUPPL DATA)

MSDS Date:08/01/2000

FSC:6850

NIIN:01-439-7872 Status Code:A

Kit Part:Y

MSDS Number: CLDDK === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHE

STER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-477-3194 MSDS:800-242-2424

Emergency Phone Num:716-722-5151 Preparer's Name:NOT PROVIDED

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

======= Composition/Information on Ingredients ========

Ingred Name:WATER CAS:7732-18-5

RTECS #:ZC0110000

Minumum %

Wt:70.

Maxumum % Wt:75.

Other REC Limits:NOT PROVIDED

OSHA PEL:NOT RELEVANT

Code:F

ACGIH TLV:NOT RELEVANT

Code:F

Ingred Name: SODIUM SULFITE

CAS:7757-83-7

RTECS #:WE2150000

Minumum % Wt:5.

Maxumum % Wt:10.

Other REC Limits:NOT PROVIDED

OSHA PEL:NOT PROVIDED

ACGIH TLV:NOT PROVIDED

Ingred Name:SODIUM CITRATE

CAS:68-04-2

RTECS #:GE8300000

< Wt:1.

Other REC Limits:NOT PROVIDED

OSHA PEL:NOT PROVIDED
ACGIH TLV:NOT PROVIDED

Ingred Name:SODIUM BISULFITE

CAS:7631-90-5

RTECS #:VZ2000000

Minumum % Wt:

15.

Maxumum % Wt:20.

Other REC Limits: NOT PROVIDED

OSHA PEL:NOT PROVIDED

ACGIH TLV:5 MG/M3

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

LD50 LC50 Mixture: NOT PROVIDED

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: EFFECTS OF EXPOSURE: INHALATION:

EXPECTED TO BE A LOW HAZARD FOR USUAL INDUSTRIAL OR COMMERCIAL HANDLING BY TRAINED PERSONNEL. IN CONTACT WITH STRONG ACIDS OR IF HEATE

D, SULFITES MAY LIBERATE SULFUR D IOXIDE GAS. SULFUR DIOXIDE GAS IS IRRITATING TO THE RESPIRATORY TRACT. SOME ASTHMATICS OR HYPERSENSITIVE INDIVIDUALS MAY EXPERIENCE DIFFICULT BREATHING. EYES: CAUSES IRRITATION. SKIN: CAUSES IRRITATI ON. THIS MATERIAL HAS A LOW POTENTIAL TO CAUSE ALLERGIC SKIN REACTIONS; HOWEVER, CASES OF HUMAN SKIN SENSITIZATION HAVE BEEN REPORTED. INGESTION: MAY BE HARMFUL IF SWALLOWED. MAY CAUSE IRRITATION OF GI TRACT IF SWALLOWED.

Explanation

- of Carcinogenicity:(COMPONENTS PRESENT AT 0.1% OR MORE):
 - INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC): NONE AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS (ACGIH): SODIUM BISULFITE, A4, N OT CLASSIFIABLE AS A HUMAN CARCINOGEN.
 - NATIONAL TOXICOLOGY PROGRAM (NTP): NONE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA): NONE
- Effects of Overexposure:INHALATION: IN CONTACT WITH STRONG ACIDS OR IF HEATED, SULFITES MAY LIBERATE SULFUR DIOXID
- E GAS. SULFUR DIOXIDE
 - GAS IS IRRITATING TO THE RESPIRATORY TRACT. SOME ASTHMATICS OR HYPERSENSITIVE INDIVIDUA LS MAY EXPERIENCE DIFFICULT BREATHING. EYES: CAUSES IRRITATION. SKIN: CAUSES IRRITATION. INGESTION: MAY CAUSE IRRITATION OF GI TRACT IF SWALLOWED.
- Medical Cond Aggravated by Exposure:SOME ASTHMATICS, HYPERSENSITIVE OR SULFITE-SENSITIVE INDIVIDUALS MAY EXPERIENCE DIFFICULT BREATHING, WHEEZING, CHEST TIGHTNESS, STOMACH UPSET, HIVES, FAINTNESS, WEAKNESS AND DIA

RRHEA.

======= First Aid N	Measures ===========
---------------------	----------------------

First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. TREAT SYMPTOMATICALLY. GETMEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENT ION IF SYMPTOMS OCCUR. SKIN: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING AND SHOES. WASH CONTAMINATED CLOTHING BEFORE REUSE. DESTR

OY OR THOROUG HLY CLEAN CONTAMINATED SHOES. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION: DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

============ Fire Fighting Measures =========================

Flash Point:NONE

Extinguishing Media:USE APPROPIATE AGENT FOR ADJACENT FIRE.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOU


S DECOMPOSITION PRODUCTS. Unusual Fire/Explosion Hazard:NONE.
========= Accidental Release Measures ===========
Spill Release Procedures:FLUSH TO SEWER WITH LARGE AMOUNT OF WATER. OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER INERT MATERIAL, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE THOROUGHLY TO REMOVE RESIDUAL C ONTAMINATION. Neutralizing Agent:NOT PROVIDED
============ Handling and Storage =============
Handling a nd Storage Precautions:KEEP CONTAINER CLOSED. KEEP AWAY FROM INCOMPATIBLE SUBSTANCES (SEE INCOMPATIBILITY SECTION). Other Precautions:AVOID BREATHING MIST OR VAPOR. AVOID CONTACT WITH EYES, SKIN, AND CLOTHING. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NONE SHOULD BE NEEDED. A RESPIRATOR SHOULD BE WORN IF HAZARDOUS DECOMPOSITION PRODUCTS ARE LIKELY TO BE OR HAVE
BEEN RELEASED. RESPIRATOR TYPE: ACID GAS. SEE STABILITY AND REACTIVITY SECTION. IF RE SPIRATORS ARE USED, A PROGRAM SHOULD BE INSTITUTED TO ASSURE COMPLIANCE WITH OSHA STANDARD 29 CFR 1910.134.
Ventilation: GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES PER
HOUR) Protective Gloves:WEAR IMPERVIOUS GLOVES APPROPRIATE FOR THE RISK OF
EXPOSURE. Eye Protection:WEAR SAFETY GLASSES WITH SIDE SHIELDS (OR GOGGLES). Other Protective Equipment:EYE BATH, SAFETY SHOWER, WASHING FA CILITIES.
Work Hygienic Practices:NOT PROVIDED Supplemental Safety and Health CONTD FROM PRODUCT ID: AND NEUTRALIZER, NEUTRALIZER. PART A HAS SULFURIC ACID. ABBREVIATION: N/A = NOT APPLICABLE. N/AV = NOT AVAILABLE. N/K = UNKNOWN. N/P = NOT PROVIDED. N/R = NOT RELEVANT. N/D = NO T DETERMINED. N/E = NOT ESTABLISHED. CNS = CENTRAL NERVOUS SYSTEM. GI = GASTROINTESTINAL.

========= Physical/Chemical Properties ==========

HCC:C1 NRC/State Lic Num:NOT RELEVANT Boilin

g Pt:>100.C, 212.F Melt/Freeze Pt:M.P/F.P Text:NOT PROVIDED Decomp Temp:Decomp Text:NOT PROVIDED Vapor Pres:18 @ 20C/68F Vapor Density:0.6 Spec Gravity:1.239 pH:5.7 Viscosity:NOT PROVIDED Evaporation Rate & amp; Reference:NOT PROVIDED Solubility in Water:COMPLETE Appearance and Odor:LIQUID, COLORLESS, ODORLESS. Percent Volatiles by Volume:70-75 Corrosion Rate:NOT PROVIDED
======== Stability and Reactivity Data ========
Stability Indicator/Materials to Avoid:YES STRONG ACIDS.
Stability Condition to Avoid:NOT PROVIDED Hazardous Decomposition Products:SULFUR DIOXIDE.
======== Toxicological Information =========
Toxicological Information:EFFECTS OF EXPOSURE: INHALATION: EXPECTED TO BE A LOW HAZARD FOR USUAL INDUSTRIAL OR COMMERCIAL HANDLING BY TRAINED PERSONNEL. IN CONTACT WITH STRONG ACIDS OR IF HEATED, SULFITES MAY LIBERATE SULFUR D IOXIDE GAS. SULFUR DIOXIDE GAS IS IRRITATING TO THE RESPIRATORY TRACT. SOME ASTHMATICS OR HY
PERSENSITIVE INDIVIDUALS MAY EXPERIENCE DIFFICULT BREATHING. EYES: CAUSES IRRITATION. SKIN: CAUSES IRRITATI ON. THIS MATERIAL HAS A LOW POTENTIAL TO CAUSE ALLERGIC SKIN REACTIONS; HOWEVER, CASES OF HUMAN SKIN SENSITIZATION HAVE BEEN REPORTED. INGESTION: MAY BE HARMFUL IF SWALLOWED. MAY CAUSE IRRITATION O F GI TRACT IF SWALLOWED.
Ecological Information

Ecological:THE FOLLOWING PROPERTIES ARE ESTIMATED FROM THE COMPONENTS O



Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.