View NSN Online: https://aerobasegroup.com/nsn/8010-00-848-6424

PRATT AND LAMBERT INC -- ENAMEL: LUSTERLESS, QUICK DRY, STYRENATED ALKYD, YELLOW 33538 -- 8010-00-848-6424

============= Product Identification ========================

Product ID:ENAMEL: LUSTERLESS, QUICK DRY, STYRENATED ALKYD, YELLOW 33538

MSDS Date:06/29/1999

FSC:8010

NIIN:00-848-6424 Status Code:A

MSDS Number: CLGRK === Responsible Party ===

Company Name: PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH ZIP:44101-10

27

Country:US

Info Phone Num:216-566-2902

Emergency Phone Num:216-566-2917 Preparer's Name:ERNEST CARTER Chemtrec Ind/Phone:(800)424-9300

CAGE:61196

=== Contractor Identification ===

Company Name: PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027 Country:US

Phone:216-566-2902

CAGE:61196

======= Composition/Information on Ingredients ========

Ingred Name: V.M.&P. NAPHTHA

CAS:64742-89-8

Code:F = Wt:29.

OSHA PEL:300 PPM ACGIH TLV:300

Ingred Name:TOLUENE

CAS:108-88-

```
3
RTECS #:XS5250000
= Wt:5.
OSHA PEL:SEE TABLE Z-2
ACGIH TLV:188 MG/M3;50 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ingred Name:XYLENE
CAS:1330-20-7
RTECS #:ZE2100000
= Wt:1.
OSHA PEL:100
ACGIH TLV:434 MG/M3;100 PPM
ACGIH STEL:651 MG/M3;150 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ingred Name:2-METHYL-1-PROPANOL
CAS:78-83-1
RTECS #:NP9625000
= Wt:4.
OSHA PEL:300 MG/M3;100 PPM
ACGIH TLV:152 MG/M3;50 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS
Ingred Name: COBALT 2-ETHYLHEXANOATE (1:2
)
CAS:136-52-7
= Wt:.2
Ingred Name: N-BUTYL ACETATE
CAS:123-86-4
RTECS #:AF7350000
= Wt:2.
OSHA PEL:710 MG/M3;150 PPM
ACGIH TLV:713 MG/M3;150 PPM
ACGIH STEL:950 MG/M3;200 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS
Ingred Name:QUARTZ
CAS:14808-60-7
RTECS #:VV7330000
= Wt:.4
OSHA PEL:SEE TABLE Z-3
ACGIH TLV:0.1 MG/M3
Ingred Name: CRISTOBALITE
CAS:14464-46-1
RTECS #:VV7325000
= Wt:4.
OSHA PEL:SEE TABLE Z-3
ACGIH TLV:0.05 MG/M3
```

Ingred Name:TALC CAS:14807-96-6 RTECS #:WW2710000 :SEE TABLE Z-3 ACGIH TLV:2 MG/M3

Ingred Name:LEAD CHROMATE

CAS:1344-37-2

Code:F = Wt:18.

OSHA PEL:0.05MG/M3

ACGIH TLV:0.05

Ingred Name:LEAD (AS PB) = Wt:12.02

OSHA PEL:0.05MG/M3

ACGIH TLV:0.15

Ingred Name: CHROMIUM VI (AS CR)

= Wt:2.56

ACGIH TLV:0.05

========= Hazards Identification ==============

LD50 LC50 Mixture:NONE

Health Hazards Acute and Chronic:EXPOSURE MAY BE BY INHALATION AND/OR SKIN OR EYE CONTACT, DEPENDING ON CONDITIONS OF USE. TO MINIMIZE EXPOSURE,

FOLLOW RECOMMENDATIONS FOR PROPER USE, VENTILATION, AND PERSONAL PROTECTIVE EQUIPMENT.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION OF EYES, SKIN AND RESPIRATORY
SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME OVEREXPOSURE
MAY RESULT IN UNCONSCIOUSNESS AND POSSIBLY DEATH.

Medical Cond Aggravated by Exposure: MAY CAUSE ALLERGIC SKIN REACTION IN SUSCEPTIBLE PERSONS OR SKIN SENSITIZATION.

=====

First Aid:IF INHALED: REMOVE FROM EXPOSURE. RESTORE BREATHING. IF ON SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER. IF IN EYES: FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. IF SWALLOWED: GET MEDICAL ATTENTION.

Flash Point Method:PMCC Flash Point:=6.7C, 44.F

Autoignition Temp: Autoignition Temp Text: NONE

Lower Limits:0.9 Upper Limits:10.9

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL,

FOAM. Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED. Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.
========= Accidental Release Measures ==========
Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT. Neutralizing Agent:NONE
======================================
Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE. TRANSFER ONLY TO APPROVED CONTAINERS WITH COMPLETE AND APPRO[RIATE LABELING. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.
Other Precautions:DO NOT APPLY ON TOYS AND OTHER CHILDREN'S ARTICLES, FURNITURE, OR ANY INTERIOR SURFACE OF A DWELLING OR FACILITY WHICH MAY BE OCCUPIED OR USED BY CHILDREN. DO NOT APPLY ON ANY EXTERIOR SURFACE OF DWEL LING UNITS, SUCH AS WINDOW SILLS, PORCHES, STAIRS,
OR RAILINGS TO WHICH CHILDREN MAY BE COMMONLY EXP OSED.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR.
Ventilation:LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF THE EXPOSURE TO MATERIALS IN SECTION 11 IS MAINTAINED BELOW APPLICABLE EXPOSURE LIMITS.
Protective Gloves:WEAR GLOVES WHICH ARE RECOMMENDED BY GLOVES. Eye Protection:WEAR SAFETY SPECTACLE
S WITH UNPERFORATED SIDE SHIELDS. Other Protective Equipment:USE BARRIER CREAM ON EXPOSED SKIN. Work Hygienic Practices:NONE Supplemental Safety and Health NONE
======================================

Boiling Pt:B.P. Text:222-325 F

Melt/Freeze Pt:M.P/F.P Text:NONE Decomp Temp:Decomp Text:NONE

Vapor Density:HEAVIER

Spec Gravity:1.19

VOC Pounds/Gallon:507

VOC Grams/Liter:4.23

Evaporation Rate & Deference: SLOWER THAN ETHER

Appearance and Odor:NONE Percent Volatile

========= Stability and Reactivity Data ==========
Stability Indicator/Materials to Avoid:YES NONE Stability Condition to Avoid:NONE Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF METALS IN SECTION11. Conditions to Avoid Polymerization:WILL NOT OCCUR.
======== Disposal Considerations ==========
Waste Disposal Methods:WASTE MUST BE TESTED FOR OGNITABILITY AND EXTRACTABILITY TO DETERMINE THE APPLICABL E EPA HAZARDOUS WASTE NUMBERS. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINER. DISPOSE OF IN ACC ORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS REGARDING POLLUTION.
========== Regulatory Information ============
State Regulatory Information: CALIFORNIA PROPOSITION65: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. TSCA CERTIFICATION.ALL CHEMICALS IN THIS PRODUC T ARE LISTED, OR ARE EXEMPT FROM LISTING, ON THE TSCA INVENTORY.
============ Other Information ===============
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document shoul

d seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

s by Volume:65%