

GRIGGS PAINT -- MIL-L-81352A #37886 WHITE -- 8010-01-303-0236

=====
Product Identification
=====

Product ID:MIL-L-81352A #37886 WHITE

MSDS Date:01/01/1997

FSC:8010

NIIN:01-303-0236

Status Code:A

MSDS Number: CLGSP

=== Responsible Party ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

City:PHOENIX

State:AZ

ZIP:85040

Country:US

Info Phone Num:602-243-3293

Emergency Phone Num:800-424-9300

Pre

parer's Name:ERNEST CARTER

Chemtre Ind/Phone:(800)424-9300

CAGE:58963

=== Contractor Identification ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

Box:City:PHOENIX

State:AZ

ZIP:85040

Country:US

Phone:602-243-3293

CAGE:58963

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENE

CAS:1330-20-7

RTECS #:ZE2100000

= Wt:21.

ACGIH TLV:434 MG/M3;100 PPM

ACGIH STEL:651 MG/M3;150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYL METHACRYLATE RES

IN
= Wt:30.

Ingred Name:ETHYLENE GLYCOL MONOBUTYL ETHER
CAS:111-76-2
RTECS #:KJ8575000
= Wt:5.
OSHA PEL:240 MG/M3;50 PPM
ACGIH TLV:121 MG/M3;25 PPM

Ingred Name:MAGSIL 2628
CAS:14807-96-6
RTECS #:WW2710000
= Wt:25.
OSHA PEL:SEE TABLE Z-3
ACGIH TLV:2 MG/M3

===== Hazards Identification =====

LD50 LC50 Mixture:NONE
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:DIRECT CONTACT TO EYES MAY CAUSE
IRRITATION. PROLONGED
AND/OR REPEATED CONTACT MAY CAUSE SKIN
IRRITATION. INHALATION OFHIGH CONCENTRATIONS OF VAPORS MAY LEAD TO
LUNG CHANGES, NAUSEA, VOMITING, COUGH, PULMONARY IRRITATION, AND
CENTRAL NERVOUS SYSTEM DEPRESSION. INGESTION MAY CAUSE
GASTROINTESTINAL DISTURBANCES.

Explanation of Carcinogenicity:NONE
Effects of Overexposure:INHALATION: BREATHING OF HIGH VAPOR
CONCENTRATIONS MAY CAUSE DROWSINESS, DIZZINESS, FATIGUE, FOLLOWED
BY COMA. EYE: DIRECT CONTACT AND/OR CONTACT WITH VAPORS
MAY CAUSE
IRRITATION. SKIN: PROLONGED AND/ OR REPEATED CONTACT MAY CAUSE
IRRITATION AND/OR DERMITITIS. MAY BE ABSORBED THROUGH THE SKIN.
ASPIRATION OF THIS PRODUCT INTO THE LUNGS MAY CAUSE PNEUMONTITIS,
PULMONARY EDEMA AND HEMORRAGE. INGESTION MAY CAUSE
GASTROINTESTINAL DISTURBANCES.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING
DISEASES IN OR HISTORY OF AILMENTS INVOLVING SKIN CENTRAL NERVOUS
SYSTEM, LIVER AND KIDNEY.

===== Fi

First Aid Measures =====

First Aid:EYE CONTACT: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. SEEK MEDICAL AID. SKIN: WASH THOROUGHLY WITH SOAP AND WATER. SEEK MEDICAL AID. INGESTION: IMMEDIATELY SEEK MEDICAL AID.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:=26.7C, 80.F

Autoignition Temp:Autoignition Temp Text:NONE

Lower Limits:1.0%

Upper Limits:NONE

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:APPROVED GAS MASK REQUIRED FOR FIRE FIGHTING PERSONNEL. WATER MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CONTAINERS. IF WATER IS USED, FOG NOZZLES ARE PREFERRED.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:ST

OP LEAK IF NO RISK INVOLVED. REMOVE ALL

SOURCES OF IGNITION. STAY UPWIND. ABSORB WITH INERT MATERIAL. FLUSH AREA WITH WATER.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED AND UPRIGHT TO PREVENT LEAKAGE. AVOID FLAMES, WELDING, OPEN LIGHTS, ETC. AVOID BREATHING OF VAPOR AND SPRAY MIST. AVOID SKIN AND EYES CONTACT.

Other Precautions:MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN

CONFINED AREAS, TANK OR PIT, WITH ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION

EXPOSURES BELOW TLV (PEL). USE MSHA/NIOSH APPROVED UNITS. USE UNITS PER CURRENT 29 CFR 1910.134 AND FOLLOW MANUFACTURERS' INSTRUCTIONS AND WARNINGS. IF WITH IN OSHA PROTECTION FACTOR, AIR PURIFYING OV/FILTER UNITS OK FOR USE.

Ventilation:LOCAL AND MECHANICAL EXHAUST.

Protective Gloves:RUB

BER GLOVES.

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS OR GOGGLES.

Other Protective Equipment:EYE BATH AND SAFETY SHOWER.

Work Hygienic Practices:MAINTAIN GOOD PERSONAL HYGIENE.

Supplemental Safety and Health

AS THE CONDITIONS OR METHODS ARE BEYOUND OUR CONTROL, WE DO NOT ASSUME ANY RESPONSIBILITY REGARDING USE OF PRODUCT. WE EXPRESSLY DISCLAIM ANY LIABILITY FORANY USE OF THE MATERIAL. INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE ALL STATEMENTS OR SUGGESTIONS ARE

MADE.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:280 TO336 DEG F.

Melt/Freeze Pt:M.P/F.P Text:NONE

Decomp Temp:Decomp Text:NONE

Vapor Density:HEAVIER

Spec Gravity:(H2O=1):1.4

VOC Pounds/Gallon:363

VOC Grams/Liter:3.03

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:VISCIOUS LIQUID WITH STRONG SOLVENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG

OXIDIZING AGENTS.

Stability Condition to Avoid:FLAMES, SPARKS, SMOKING AND HEAT.

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:USE INERT ABSORBENT MATERIALS ON SPILLS. DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This informatio

n is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.